(+) 188 1699 6168

		hongrunplastics.com	
SAFETY DATA SHEET			lyondellbasel
Alathan 114250			Gen. Variant: SDS US GHS
Alathon H4250 Version 1.2 Revision Date	10/	01/2019 Print Date 0	
	10/		1/04/2022 0D0 No D12
. IDENTIFICATION OF THE SUB	STA	NCE/MIXTURE AND OF	THE COMPANY/UNDERTAKING
Trade name	:	Alathon H4250	
CAS Number:	:	26221-73-8	
Chemical characterization Chemical name	÷	Polyethylene copolymer	thana
Synonyms	•	1-Octene, polymer with effective the second	mer, 1-Octene-ethylene copolymer
	•		
Identified uses	:	Manufacture of plastic art or other conversion proce	icles by injection molding, extrusion ss.
Prohibited uses	:	devices; Health Canada d	manent implantation into the body;
<u>Company Address</u> Equistar Chemicals, LP		<u>Company Tel</u> Customer Ser	<u>ephone</u> vice 888 777-0232
LyondellBasell Tower, Suite 30 1221 McKinney St. P.O. Box 2583	00	product.safety	@lyb.com
Houston Texas 77252-2583 <u>Emergency telephone numb</u> EQUISTAR 800-245-4532	<u>per</u>		
E-mail address	:	product.safety@lyb.com	
Responsible/issuing person			
. HAZARDS IDENTIFICATION			
GHS Classification			
Combustible dust			
Label elements			
Signal word	:	Warning	
Hazard Statements	:		nerated during further processing, ns, may form combustible dust
Other hazards			
		1 / 13	

	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbase
Alathon H4250		Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	te 10/01/2019 Print Date 01/0	4/2022 SDS No.: BE
No additional information	available.	
COMPOSITION/INFORMATIO	N ON INGREDIENTS	
ixtures		
Components		
Chemical name	CAS-No.	<u>Weight %</u>
1-Octene, polymer with ethen	ne 26221-73-8	> 99.5 %
Container Stabilizera	·	
Contains: Stabilizers		
FIRST AID MEASURES		
General advice	· Take proper precautions to	ensure your own health and safe
	before attempting rescue a	
If inhaled	•	. If signs/symptoms continue, get
	medical attention. In case of excessive inhalat	ion of fumes that may be generat
	during heating of this mater Obtain medical attention.	ial, move the person to fresh air.
	Keep person warm, if neces	ssary give Cardio-Pulmonary
	Resuscitation (CPR)	
In case of skin contact	· If molten material contacts	the skin, immediately flush with
	large amounts of water to c	ool the affected tissue and polym
	Do not attempt to peel poly skin.	mer from skin as this will remove
	Obtain immediate emergen	cy medical attention if burn is dee
	or extensive.	
In case of eye contact	: Flush eves thoroughly with	water for several minutes and see
-	medical attention if discomf	
	: In case of eye contact with	
	Continuously flush eye(s) w minutes.	rith cool running water for at least
	Beyond flushing, DO NOT a	attempt to remove the material
	adherent to the eye(s). Immediately seek medical a	attention.
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
		-
	2 / 13	
	2/13	

Alathon H4250 Gen. Variant: SDS_US_GI Version 1.2 Revision Date 10/01/2019 Print Date 01/04/2022 SDS No.: E Notes to physician Symptoms : Inhalation of process fumes and vapors may cause sorenear the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient. Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. LARGE FIRES: Use water spray hose nozzles from a safe location. : None known. Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (grnoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible paticulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire any melt, decompose polymer, and generate fammable vapors. Move containers from fire area if it can be done without risk Evacuate irmselide dvices or discoloration of cortage container pressure relied devices or discoloration of contain Al		hongrunplastics.com
Version 1.2 Revision Date 10/01/2019 Print Date 01/04/2022 SDS No.: E Notes to physician Symptoms : Inhalation of process fumes and vapors may cause sorenee the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARCE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Special protective equipment for fire-fighters : Nee approved positive pressure self-contained breathing appratus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may media the ore of storage containers involved fire. Do not attempt to get on top of storage container sinvolved fire. Do not attempt to get on top of storage containers involved fire.	SAFETY DATA SHEET	lyondellbasel
Notes to physician Symptoms : Inhalation of process fumes and vapors may cause sorenee the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Motten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the contronsymptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location. : None known. : Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing aparatus and firefighter protective clothing. : Wuter information : Combustible particulate solid, will decompose outer fire conditions. Calorific Value: 8000 - 11000 kcal/kg : Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate firamable vapors. Move containers from fire area if it can be done without ths Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stora anks engulfed in fire. Do not attempt to get on top of storage containers involved fire. <	Alathon H4250	Gen. Variant: SDS_US_GHS
Symptoms : Inhalation of process fumes and vapors may cause sorenest the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient. S. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. Suitable extinguishing media : SMALL FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calofic Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may metit, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from taks engulied in fire. Do not attempt to get on top of storage containers involved fire.	Version 1.2 Revision Date	10/01/2019 Print Date 01/04/2022 SDS No.: BE2
Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. : Unther information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate farmable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulied in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even a		: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
symptoms and the clinical condition of the patient. suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media Specific hazards during fire fighting : None known. : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even a	Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
 Use dry chemical, CO2, or water spray. LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media Specific hazards during fire fighting Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even a 	Treatment	: Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.
 LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media Specific hazards during fire fighting Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. 		
 media Specific hazards during fire fighting Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke). Special protective equipment for fire-fighters Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noza Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. 		: LARGE FIRES:
fightingIn case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarb (smoke).Special protective equipment for fire-fighters: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.Further information: Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even a		: None known.
for fire-fighters apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even a		In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons
conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozz Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even a		
	Further information	 conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after
3 / 13		3/13

	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbase
Alathon H4250		Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 1	0/01/2019 Print Date 0	1/04/2022 SDS No.: BE2
6. ACCIDENTAL RELEASE MEASU	IRES	
Personal precautions	surface. Equip emergency respone equipment (PPE) Avoid generating dust. Avoid dispersal of dust ir with compressed air). Potential combustible du	ing hazard on any hard smooth nders with proper personal protective n the air (i.e., clearing dust surfaces
Environmental precautions	: Do not flush into surface	water or sanitary sewer system.
Methods for containment / Methods for cleaning up	vacuum using equipment On water, material is inso solid. All recovered material sho transported and disposed	to suitable disposal containers or which avoids ignition risk. oluble; collect and contain as any ould be packaged, labeled, d of or reclaimed in conformance with lations and in conformance with good eclaim where possible.
7. Handling and storage Precautions for safe handling		
Advice on safe handling	handling, or by other mean concentrations in air. Avoid dust accumulation Use dust collection syste dust accumulation. Avoid generating dust; fin presence of an ignition so hazard. Static discharge (spark), environments may ignite explosion Electrostatic charge may	cles during further processing, ans, may form combustible dust in enclosed space. Ims designed per NFPA 654 to avoid the dust suspended in air and in the burce is a potential dust explosion or other ignition sources, in high dust the dust and result in a dust build during conveying or handling. mer should be conductive and
	g	

	nongrunplastics.com		
SAFETY DATA SHEET		lyond	ellbasell
Alathon H4250		Gen. Variant	t: SDS_US_GHS
Version 1.2 Revision Date 1	0/01/2019 Print Date 0	1/04/2022	SDS No.: BE29
	Metal containers involved should be grounded and All electrical equipment s codes and regulatory req combustible dusts. After handling, always wa water. When bringing the materi may develop may conder section 10. Refer to NFPA 654, Stan Dust Explosions from the Handling of Combustible	bonded. hould conform to ap uirements for areas ash hands thoroughly al to processing terr ase in the exhaust ve dard for the Preventi Manufacturing, Pro-	plicable electric handling with soap and peratures vapors entilation. See on of Fire and cessing, and
Fire-fighting class	: Polymer will burn but doe	s not easily ignite.	
Conditions for safe storage, ir	ncluding any incompatibility	ties	
Requirements for storage areas and containers	: Store in a dry location. Use good housekeeping and handling. Process er should be used to avoid o Store away from excessi oxidizing agents. Keep container closed to Take measures to preven	closures and adeque excessive dust accurve heat and away fro prevent contamination	ate ventilation mulation. om strong ion.
Specific end use(s)			
	: See Section 1.		
8. EXPOSURE CONTROLS/PERSO	VAL PROTECTION		

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

5 / 13

		hongrun	plastics.com		
SAFETY DATA	SHEET	lyonde	ellbasell		
	-				
Alathon H425	50			Gen. Variant:	SDS_US_GHS
Version 1.2	Revision Date 10	/01/2019	Print Date 01	/04/2022	SDS No.: BE29
				_	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
AFETY DATA SHEET	lyondellbase
lathon H4250	Gen. Variant: SDS_US_GH
ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/04/2022 SDS No.: BE
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL P Appearance	: Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dua varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Alathon H4250	Gen. Variant: SDS_US_GHS
/ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/04/2022 SDS No.: BE
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
). STABILITY AND REACTIVITY	/
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition products	: Not expected to decompose under normal conditions.
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
I. TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasel
Alathon H4250	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 01/04/2022 SDS No.: BE2
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	Not classified Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Alathon H4250	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 01/04/2022 SDS No.: BE29
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION Not regulated for transport	
	10 / 13

SAFETY DATA SHEET

Alathon H4250

Version 1.2

Revision Date 10/01/2019

Print Date 01/04/2022

Gen. Variant: SDS US GHS

lyondellbase

SDS No.: BE29

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

ntry/Region	Inventory	Status Description
tralia	AICS	Compliant
	11 / 1	3

SAFETY DATA SHEET Alathon H4250 Version 1.2 Revision Date 10/ Canada China Europe Japan Korea New Zealand Philippines United States of America Taiwan REACh status f the product has been purchased from	DSL IECSC REACH ENCS KECI NZIOC PICCS TSCA	Image: Solution of the second statement Compliant Compliant See REACH Compliance Statement Compliant Compliant
Version 1.2 Revision Date 10/ Canada China Europe Japan Korea New Zealand Philippines United States of America Taiwan	DSL IECSC REACH ENCS KECI NZIOC PICCS TSCA	nt Date 01/04/2022 SDS No.: Bi Compliant Compliant See REACH Compliance Statement Compliant Compliant Compliant Compliant
Version 1.2 Revision Date 10/ Canada China Europe Japan Korea New Zealand Philippines United States of America Taiwan	DSL IECSC REACH ENCS KECI NZIOC PICCS TSCA	nt Date 01/04/2022 SDS No.: Bi Compliant Compliant See REACH Compliance Statement Compliant Compliant Compliant Compliant
Canada China Europe Japan Korea New Zealand Philippines United States of America Taiwan	DSL IECSC REACH ENCS KECI NZIOC PICCS TSCA	Compliant Compliant See REACH Compliance Statement Compliant Compliant Compliant
China Europe Japan Korea New Zealand Philippines United States of America Taiwan	IECSC REACH ENCS KECI NZIOC PICCS TSCA	Compliant See REACH Compliance Statement Compliant Compliant Compliant
China Europe Japan Korea New Zealand Philippines United States of America Taiwan	IECSC REACH ENCS KECI NZIOC PICCS TSCA	Compliant See REACH Compliance Statement Compliant Compliant Compliant
China Europe Japan Korea New Zealand Philippines United States of America Taiwan	IECSC REACH ENCS KECI NZIOC PICCS TSCA	Compliant See REACH Compliance Statement Compliant Compliant Compliant
Europe Japan Korea New Zealand Philippines United States of America Taiwan	REACH ENCS KECI NZIOC PICCS TSCA	See REACH Compliance Statement Compliant Compliant Compliant
Japan Korea New Zealand Philippines United States of America Taiwan EACh status	ENCS KECI NZIOC PICCS TSCA	Compliant Compliant Compliant
Korea New Zealand Philippines United States of America Taiwan EACh status	KECI NZIoC PICCS TSCA	Compliant Compliant
New Zealand Philippines United States of America Taiwan EACh status	NZIoC PICCS TSCA	Compliant
Philippines United States of America Taiwan EACh status	PICCS TSCA	
United States of America Taiwan EACh status	TSCA	Compliant
Taiwan EACh status		Compliant
EACh status	TCSCA	Compliant
6. OTHER INFORMATION		
Material safety datasheet sectio	ons which have b	been updated:
Revised Section(s): 15 16		
F	Health Hazard: 0 Flammability: 1 Physical hazards:	0 1 0
F	Health Hazard: 0 Fire Hazard: 1 nstability: 0	
		\diamond
Further information		Ŷ
Further information HMIS rating scale (0 = minimal ha NFPA rating scale (0 = minimal ha		

(+)	188	1699	6168
hone	grun	olastic	s.com

SAFETY	DATA	SHEET

Alathon H4250

Version 1.2

Revision Date 10/01/2019

Print Date 01/04/2022

SDS No.: BE29

ondellbase

.... Gen. Variant: SDS US GHS

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234.56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet