(+) 188 1699 6168

		hongrunplastics.com	
SAFETY DATA SHEET			lyondellbasel
Alathon H5275			Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/	01/2019 Print Date 12	
. IDENTIFICATION OF THE SUB	STA	NCE/MIXTURE AND OF	THE COMPANY/UNDERTAKING
Trade name CAS Number:	:	Alathon H5275 26221-73-8	
Chemical characterization	:	Polyethylene copolymer	
Chemical name	:	1-Octene, polymer with et	
Synonyms	:	Ethylene-1-octene copoly	mer, 1-Octene-ethylene copolymer
Identified uses	:	Manufacture of plastic art or other conversion proce	icles by injection molding, extrusion ss.
Prohibited uses	:	devices; Health Canada d	manent implantation into the body;
<u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 3 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583	00	Company Tel Customer Sen product.safety	vice 888 777-0232
Emergency telephone numb EQUISTAR 800-245-4532 E-mail address		product.safety@lyb.com	
Responsible/issuing person			
HAZARDS IDENTIFICATION			
GHS Classification			
Combustible dust			
Label elements			
Signal word	:	Warning	
Hazard Statements	:		nerated during further processing, ns, may form combustible dust
Other hazards			

	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbasel
Alathon H5275		Gen. Variant: SDS_US_GHS
ersion 1.1 Revision Dat	te 10/01/2019 Print Date 12/2	1/2019 SDS No.: BE1667
No additional information	available.	
COMPOSITION/INFORMATIO	N ON INGREDIENTS	
ixtures		
Components		
Chemical name	CAS-No.	Weight %
1-Octene, polymer with ethen	e 26221-73-8	>= 99.5 %
Contains: Stabilizers		
FIRST AID MEASURES		
General advice	: Take proper precautions to before attempting rescue an	ensure your own health and safety nd providing first aid.
If inhaled	medical attention. In case of excessive inhalat during heating of this mater Obtain medical attention.	. If signs/symptoms continue, get tion of fumes that may be generate ial, move the person to fresh air. ssary give Cardio-Pulmonary
In case of skin contact	large amounts of water to c Do not attempt to peel poly skin.	the skin, immediately flush with ool the affected tissue and polyme mer from skin as this will remove t cy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discomf	water for several minutes and see ort persists.
	minutes.	molten polymer: vith cool running water for at least a attempt to remove the material
	adherent to the eye(s). Immediately seek medical a	attention.
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
	2 / 13	

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Alathon H5275	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019 Print Date 12/21/2019 SDS No.: BE1667
Notes to physician Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 13
	3/13

(+) 188 1699 6	168
hongrunplastics.	com

	hongrunp	plastics.com		
SAFETY DATA SHEET			lyon	dellbasel
Alathon H5275			Gen. Var	iant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019	Print Date 12/2	1/2019	SDS No.: BE1667
. ACCIDENTAL RELEASE MEAS	URES			
Personal precautions	Creates da surface. Equip eme equipment Avoid gene Avoid disp with comp Potential o	erating dust.	hazard on an rs with proper ne air (i.e., clea hazard.	personal protective aring dust surfaces
Environmental precautions	: Do not flus	sh into surface wa	ater or sanitary	sewer system.
Methods for containment / Methods for cleaning up	vacuum us On water, r solid. All recovere transported applicable		hich avoids ign ble; collect and d be packaged or reclaimed ons and in cor	ition risk. I contain as any I, labeled, in conformance with formance with good
. Handling and storage Precautions for safe handlin	a			
Advice on safe handling	: Material is If converted handling, o concentrati Avoid dust Use dust of dust accum Avoid gene presence o hazard. Static disch environmen explosion Electrostati Equipment	accumulation in e ollection systems nulation. erating dust; fine o of an ignition source harge (spark), or o hts may ignite the	, may form co enclosed space designed per dust suspende ce is a potenti- other ignition s dust and resu ild during conv r should be co	mbustible dust e. NFPA 654 to avoid d in air and in the al dust explosion sources, in high dust ilt in a dust eying or handling.
	grounded (,		

	nongrunplastics.com		
SAFETY DATA SHEET		lyor	ndellbasell
Alathon H5275		Gen. Va	ariant: SDS_US_GHS
Version 1.1 Revision Date 10	/01/2019 Print Date 12	2/21/2019	SDS No.: BE16675
	Metal containers involved should be grounded and I All electrical equipment sl codes and regulatory requ combustible dusts. After handling, always wa water. When bringing the materia may develop may conden section 10. Refer to NFPA 654, Stand Dust Explosions from the Handling of Combustible	bonded. hould conform t uirements for ar sh hands thoro al to processing se in the exhau dard for the Pre Manufacturing,	to applicable electric reas handling ughly with soap and g temperatures vapors ust ventilation. See vention of Fire and Processing, and
Fire-fighting class :	Polymer will burn but does		
Conditions for safe storage, inc			
		ues	
Requirements for storage : areas and containers	Store in a dry location. Use good housekeeping p and handling. Process en should be used to avoid e Store away from excessiv oxidizing agents. Keep container closed to Take measures to prevent	closures and a excessive dust a ve heat and awa prevent contam	dequate ventilation accumulation. ay from strong hination.
Specific end use(s)			
:	See Section 1.		
8. EXPOSURE CONTROLS/PERSON	AL PROTECTION		

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

5 / 13

	hongrunp	plastics.com		
SAFETY DATA SHEET			lyond	ellbasell
			1	- 111 - 11
Alathon H5275			Gen. Variant	: SDS_US_GHS
Version 1.1 Revision Date 10)/01/2019	Print Date 12	/21/2019 S	DS No.: BE16675
Materials that can	TWA	3 mg/m3	US (ACGIH)	1
be formed when	10070	respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	15 mg/m3	US (OSHA)	
be formed when		total dust	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	5 mg/m3	US (OSHA)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Alathon H5275	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	e 10/01/2019 Print Date 12/21/2019 SDS No.: BE166
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL F	: Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold Flash point	: No value available.
Lower explosion limit	 The minimum explosive concentration (MEC) for polymer durative varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Alathon H5275	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	e 10/01/2019 Print Date 12/21/2019 SDS No.: BE166
Partition coefficient: n- octanol/water Viscosity, dynamic Relative vapor density	 No Data Available. Not applicable. Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
0. STABILITY AND REACTIVITY	,
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition products	: Not expected to decompose under normal conditions.
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
1. TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Alathon H5275	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019 Print Date 12/21/2019 SDS No.: BE166
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
2. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Alathon H5275	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date 1	0/01/2019 Print Date 12/21/2019 SDS No.: BE16675
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations Waste treatment methods Product	: All recovered material should be packaged, labeled,
	transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
Not regulated for transport	
15. REGULATORY INFORMATION	
	10 / 13

SAFETY DATA SHEET

Alathon H5275

Version 1.1

Revision Date 10/01/2019

Print Date 12/21/2019

Gen. Variant: SDS_US_GHS 19 SDS No.: BE16675

lyondellbase

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
	11 / 1	3

		(+) 188	1699 6168	
		hongrun	olastics.com	
-	DATA SHEET	t		lyondellbase
Alathon				Gen. Variant: SDS_US_GH
Version 1.1	Revision D	ate 10/01/2019	Print Date 12	2/21/2019 SDS No.: BE16
Kore		KECI	Complia	
	Zealand	NZIOC	Complia	
	opines	PICCS	Complia	
	ed States of Ameri		Complia	
Taiwa	an	TCSCA	Complia	int
egistered und 907/2006)	ler REACh, in acc	ordance with the c	leadlines set for	rth in REACh. (Regulation (EU) No.
ontact produ	ct.safety@lyb.com	n for additional glo	bal inventory in	formation.
6. OTHER IN	FORMATION			
6. OTHER IN	FORMATION			
		t sections which	have been upd	lated:
Material			have been upd	lated:
Material Revised	safety datasheet		rd: 0 /: 1	lated:
Material Revised HMIS Cla	safety datasheet Section(s): 15 16	5 : Health Haza Flammability	rd: 0 /: 1 :ards: 0 rd: 0	
Material Revised HMIS Cla	safety datasheet Section(s): 15 16 Issification	5 : Health Haza Flammability Physical haz : Health Haza Fire Hazard:	rd: 0 /: 1 :ards: 0 rd: 0	0 1 0
Material Revised HMIS Cla NFPA Cla Further i HMIS rat	safety datasheed Section(s): 15 16 assification assification nformation ing scale (0 = min	5 : Health Haza Flammability Physical haz : Health Haza Fire Hazard:	rd: 0 v: 1 zards: 0 rd: 0 1 evere hazard)	0 1 0
Material Revised HMIS Cla NFPA Cla Further i HMIS rat	safety datasheed Section(s): 15 16 assification assification nformation ing scale (0 = min	 Health Haza Flammability Physical haz Health Haza Fire Hazard: Instability: 0 imal hazard; 4 = s imal hazard; 4 = s 	rd: 0 v: 1 zards: 0 rd: 0 1 evere hazard)	0 1 0
Material Revised HMIS Cla NFPA Cla Further i HMIS rat	safety datasheed Section(s): 15 16 assification assification nformation ing scale (0 = min	 Health Haza Flammability Physical haz Health Haza Fire Hazard: Instability: 0 imal hazard; 4 = s imal hazard; 4 = s 	rd: 0 2: 1 2: ards: 0 rd: 0 1 evere hazard) severe hazard)	0 1 0

SAFETY DATA SHEET

Alathon H5275

Version 1.1

Revision Date 10/01/2019

Print Date 12/21/2019

SDS No.: BE16675

Gen. Variant: SDS US GHS

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet