	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbasell
Alathon M6020SB		Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 0	01/05/2022 SDS No.: BE9920
I. IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF	THE COMPANY/UNDERTAKING
Trade name CAS Number:	: Alathon M6020SB : 9002-88-4	
Chemical characterization	: Polyethylene Homopolym	ner
Chemical name	: Polyethylene	
Synonyms	: Ethene, homopolymer, P	Έ
Identified uses	: Manufacture of plastic ar or other conversion proce	ticles by injection molding, extrusion ess.
Prohibited uses	devices; Health Canada	evices; European class III medical class IV Medical Devices; rmanent implantation into the body; applications
<u>Company Address</u> Equistar Chemicals, LP	<u>Company Te</u> Customer Se	lephone rvice 888 777-0232
LyondellBasell Tower, Suite 3 1221 McKinney St. P.O. Box 2583		
Houston Texas 77252-2583		
Emergency telephone numb EQUISTAR 800-245-4532	<u>ier</u>	
E-mail address Responsible/issuing person	: product.safety@lyb.com	
. HAZARDS IDENTIFICATION GHS Classification		
Combustible dust		
Label elements		
Signal word	: Warning	
-	-	
Hazard Statements		enerated during further processing, ans, may form combustible dust
Other hazards		
	1 / 13	

No additional information available.         COMPOSITION/INFORMATION ON INGREDIENTS         lixtures         Components <ul> <li>Chemical name</li> <li>CAS-No.</li> <li>Polyethylene</li> <li>9002-88-4</li> </ul> Contains: Additives and stabilizers         FIRST AID MEASURES         General advice       : Take proper precauti before attempting results         If inhaled       : Remove person to fmodical attention. In case of excessive during heating of this Obtain medical attention. In case of skin contact         In case of skin contact       : If molten material con large amounts of wat Do not attempt to perskin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thorough medical attention if d         In case of eye contact       : Flush eyes thorough medical attention if d         State of eye contact       : In case of eye contact         Continuously flush eyes       : In case of eye contact	lyondellbase	
Alathon M6020SB         /ersion 1.2       Revision Date 10/01/2019       Print Date 10/01/2019         No additional information available.         COMPOSITION/INFORMATION ON INGREDIENTS ixtures         Components         Chemical name       CAS-No.         Polyethylene       9002-88-4         Contains:       Additives and stabilizers         FIRST AID MEASURES       E         General advice       :         If inhaled       :         If inhaled       :         In case of skin contact       :         In case of skin contact       :         In case of eye contact       :         Seyond flushing, DO	lyondellbase	
ersion 1.2       Revision Date 10/01/2019       Print Date Date Date Date Date Date Date Dat		
No additional information available.         COMPOSITION/INFORMATION ON INGREDIENTS xtures         Components <ul> <li>Chemical name</li> <li>CAS-No.</li> <li>Polyethylene</li> <li>9002-88-4</li> </ul> Contains: Additives and stabilizers         FIRST AID MEASURES         General advice       : Take proper precauti before attempting res         If inhaled       : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical attention. In case of skin contact         In case of skin contact       : If molten material cool large amounts of wat Do not attempt to pe skin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if d : In case of eye contact         In case of eye contact       : Flush eyes thoroughl medical attention if d         : In case of eye contact       : In case of eye contact         : In case of eye contact       : In case of eye contact         : In case of eye contact       : In case of eye contact	Gen. Variant: SDS_US_GH	
<th control="" of="" second="" state="" th="" the="" the<=""><th>te 01/05/2022 SDS No.: BE9</th></th>	<th>te 01/05/2022 SDS No.: BE9</th>	te 01/05/2022 SDS No.: BE9
COMPOSITION/INFORMATION ON INGREDIENTS         ixtures       Components <ul> <li>Chemical name</li> <li>CAS-No.</li> <li>Polyethylene</li> <li>9002-88-4</li> </ul> Contains:         Additives and stabilizers           FIRST AID MEASURES             General advice         : Take proper precauti before attempting res           If inhaled         : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention (CPR)           In case of skin contact         : If molten material cool large amounts of wat Do not attempt to perskin. Obtain immediate en or extensive.           In case of eye contact         : Flush eyes thoroughl medical attention if do attention if do attention. If case of eye contact Continuously flush eye minutes. Beyond flushing, DO		
Components         Chemical name       CAS-No.         Polyethylene       9002-88-4         Contains:       Additives and stabilizers         FIRST AID MEASURES       Encode attempting restricts         General advice       :       Take proper precauti before attempting restricts         If inhaled       :       Remove person to fm medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attention. Solution medical attention for the second the secon		
Components         Chemical name       CAS-No.         Polyethylene       9002-88-4         Contains: Additives and stabilizers         FIRST AID MEASURES         General advice       : Take proper precauti before attempting res         If inhaled       : Remove person to fmedical attention. In case of excessive during heating of this Obtain medical attent Keep person warm, i Resuscitation (CPR)         In case of skin contact       : If molten material con large amounts of wat Do not attempt to perskin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if definition if definiti		
Chemical name         CAS-No.           Polyethylene         9002-88-4           Contains: Additives and stabilizers           FIRST AID MEASURES           General advice         : Take proper precauti before attempting res           If inhaled         : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical attention. In case of excessive during heating of this Obtain medical attent Keep person warm, i Resuscitation (CPR)           In case of skin contact         : If molten material con large amounts of wat Do not attempt to perskin. Obtain immediate en or extensive.           In case of eye contact         : Flush eyes thoroughl medical attention if d           In case of eye contact         : In case of eye contact		
Polyethylene       9002-88-4         Contains: Additives and stabilizers         FIRST AID MEASURES         General advice       : Take proper precauti before attempting res         If inhaled       : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical attent Keep person warm, i Resuscitation (CPR)         In case of skin contact       : If molten material con large amounts of wat Do not attempt to perskin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if d         In case of eye contact       : Flush eyes thoroughl medical attention if d         In case of eye contact       : Flush eyes thoroughl medical attention if d         Seyond flushing, DO       : In case of eye contact		
Contains: Additives and stabilizers FIRST AID MEASURES General advice If inhaled If inha	Weight %	
Contains: Additives and stabilizers FIRST AID MEASURES General advice If inhaled If inha	> 99.5 %	
FIRST AID MEASURES         General advice       : Take proper precauti before attempting res         If inhaled       : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical atten Keep person warm, i Resuscitation (CPR)         In case of skin contact       : If molten material con large amounts of wat Do not attempt to per skin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if d         In case of eye contact       : Flush eyes thoroughl medical attention if d         In case of eye contact       : In case of eye contact	2 00.0 /0	
General advice       : Take proper precauti before attempting res         If inhaled       : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical atten Keep person warm, i Resuscitation (CPR)         In case of skin contact       : If molten material con large amounts of wat Do not attempt to per skin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if d : In case of eye contact         In case of eye contact       : Substance         In case of eye contact       : Bush eyes thoroughl medical attention if d : In case of eye contact		
General advice       : Take proper precauti before attempting res         If inhaled       : Remove person to fm medical attention. In case of excessive during heating of this Obtain medical atten Keep person warm, i Resuscitation (CPR)         In case of skin contact       : If molten material con large amounts of wat Do not attempt to per skin. Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if d : In case of eye contact         In case of eye contact       : Superstance         In case of eye contact       : Bush eyes thoroughl medical attention if d : In case of eye contact         : In case of eye contact       : Superstance         : Superstance       : Superstance         : In case of eye contact       : Superstance         : Superstance       : Superstance         : Superstance       : Superstance         : Superstance       : Superstance		
If inhaled       : Remove person to fm         If inhaled       : Remove person to fm         In case of excessive       during heating of this         Obtain medical attention.       In case of excessive         In case of skin contact       : If molten material collarge amounts of wat         Do not attempt to person warm, in cestersive.         In case of eye contact       : Flush eyes thoroughl medical attention if d         in case of eye contact       : Flush eyes thoroughl medical attention if d         : In case of eye contact       : In case of eye contact         : In case of eye contact       : Beyond flushing, DO		
<ul> <li>medical attention. In case of excessive during heating of this Obtain medical atten Keep person warm, i Resuscitation (CPR)</li> <li>In case of skin contact</li> <li>If molten material col large amounts of wat Do not attempt to per skin. Obtain immediate en or extensive.</li> <li>In case of eye contact</li> <li>Flush eyes thoroughl medical attention if d</li> <li>In case of eye contact</li> <li>Seyond flushing, DO</li> </ul>	ons to ensure your own health and safe scue and providing first aid.	
Iarge amounts of wat Do not attempt to perskin.         Obtain immediate en or extensive.         In case of eye contact       : Flush eyes thoroughl medical attention if d         : In case of eye contact       : In case of eye contact Continuously flush eyes in continuously flush eyes minutes.	esh air. If signs/symptoms continue, ge inhalation of fumes that may be genera material, move the person to fresh air. tion. f necessary give Cardio-Pulmonary	
medical attention if d In case of eye contac Continuously flush e minutes. Beyond flushing, DO	ntacts the skin, immediately flush with er to cool the affected tissue and polym el polymer from skin as this will remove nergency medical attention if burn is de	
Continuously flush e minutes. Beyond flushing, DO	y with water for several minutes and se iscomfort persists.	
adherent to the eye(s Immediately seek me		
If swallowed : Adverse health effect	ts due to ingestion are not anticipated.	
2 / 13		
2710		

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasel
Alathon M6020SB	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 2	10/01/2019 Print Date 01/05/2022 SDS No.: BE992
<b>Notes to physician</b> Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzles Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk.</li> <li>Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.</li> <li>Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved in fire.</li> <li>Cool storage containers with large volumes of water even after fire is out.</li> </ul>
	3 / 13
	3713

ACCIDENTAL RELEASE MEASURES     Personal precautions     : Equip responders with proper protection.     Creates dangerous slipping hazard on any hard smooth     surface.     Equip emergency responders with proper personal protective     equipment (PPE)     Avoid dispersal of dust in the air (i.e., clearing dust surfaces     with compressed air),     Potential combustible dust hazard.     Polymer particles create slipping hazard on hard smooth     surfaces.     Environmental precautions     : Do not flush into surface water or sanitary sewer system.     Methods for containment /         : On land, sweep/shovel into suitable disposal containers or         vacuum using equipment which avoids ignition risk.         On water, material is should be packaged, labeled,         transported and disposed of or reclaimed in conformance with         applicable laws and regulations and in conformance with         applicable laws usour water means, may form combustible dust         concentrations in air.         Avid dust accumulation in enclosed space.         Use dust collection systems designed per NFPA 654 to avoid         dust accumulation.         Avoid generating dust; fine dust suspended in air and in the         presence of an ignition source is a potential dust explosion         hazard.         Static discharge (gark), or other ignition converse, in high dus         environments may ignite the dust and result in a dust         explosion         Electrostatic charge may build during conveying or handling.		hongrunp	plastics.com		
Version 1.2         Revision Date 10/01/2019         Print Date 01/05/2022         SDS No.: BE99           6. ACCIDENTAL RELEASE MEASURES         Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combusible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.           Environmental precautions         : Do not flush into surface water or sanitary sewer system.           Methods for containment / Methods for cleaning up         : On land, sweep/showel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in contommance with applicable laws and regulations and in contommance with applicable laws and regulations and in contommance with applicable laws and regulations and in contommance with applicable laws and regulations and in contommance with applicable laws and regulations and in contommance with applicable engineering practices. Reclaim where possible.           7. Handling and storage         : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NPA 654 to avoid dust accumulatin. Avoid dust accumulat	SAFETY DATA SHEET			lyo	ndellbasel
ACCIDENTAL RELEASE MEASURES     Personal precautions     : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions     : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up Con land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in conformance with applicable laws under gulations and in contormance with applicable laws consultation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition cources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.	Alathon M6020SB			Gen. V	ariant: SDS_US_GHS
Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : Do not flush into surface water or sanitary sewer system.         Methods for containment / Methods for containment / Methods for cleaning up       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with goor engineering practices. Reclaim where possible.         7. Handling and storage       : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust calcertion systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Equipment handling polymer should be conductive and grounded (earthed) and bonded.	Version 1.2 Revision Date	10/01/2019	Print Date 01	/05/2022	SDS No.: BE992
<ul> <li>Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.</li> <li>Environmental precautions : Do not flush into surface water or sanitary sever system.</li> <li>Methods for containment / Methods for cleaning up</li> <li>On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.</li> <li>7. Handling and storage</li> <li>Precautions for safe handling</li> <li>Advice on safe handling</li> <li>Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in an. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build duing conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.</li> </ul>					
<ul> <li>Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.</li> <li>Environmental precautions : Do not flush into surface water or sanitary sever system.</li> <li>Methods for containment / Methods for cleaning up</li> <li>Con land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.</li> <li>Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.</li> </ul>	6. ACCIDENTAL RELEASE MEAS	URES			
Methods for containment / Methods for cleaning up       : On land, sweep/showel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.         7. Handling and storage       Image: Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.	Personal precautions	Creates da surface. Equip eme equipment Avoid gen Avoid disp with comp Potential o Polymer p	angerous slippi ergency respon- (PPE) erating dust. bersal of dust in ressed air). combustible dus	ng hazard on ders with prop the air (i.e., c st hazard.	any hard smooth er personal protective learing dust surfaces
Methods for cleaning up       vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.         All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.         7. Handling and storage         Precautions for safe handling         Advice on safe handling         :       Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.	Environmental precautions	: Do not flus	sh into surface	water or sanita	ary sewer system.
Precautions for safe handling         Advice on safe handling         Advice on safe handling         :       Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.		vacuum us On water, i solid. All recovere transported applicable	ing equipment material is insol ed material sho and disposed laws and regula	which avoids i uble; collect a ould be packag of or reclaime ations and in c	ignition risk. Ind contain as any ged, labeled, d in conformance with conformance with good
<ul> <li>Advice on safe handling</li> <li>Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.</li> </ul>					
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.	Precautions for safe handling	g			
	Advice on safe handling	If converted handling, co concentrati Avoid dust Use dust c dust accun Avoid gene presence co hazard. Static discl environmen explosion Electrostat Equipment	d to small partic or by other mean ons in air. accumulation i ollection syster nulation. erating dust; fine of an ignition so harge (spark), o harge (spark), o ts may ignite t ic charge may l	cles during furt ns, may form of n enclosed sp ns designed p e dust suspen urce is a poter or other ignition he dust and re puild during co ner should be	combustible dust ace. er NFPA 654 to avoid ded in air and in the ntial dust explosion n sources, in high dust esult in a dust
4 / 13					

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Alathon M6020SB	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 10	0/01/2019 Print Date 01/05/2022 SDS No.: BE9920
	Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Fire-fighting class :	Polymer will burn but does not easily ignite.
Conditions for safe storage, in	
Requirements for storage : areas and containers	Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	See Section 1.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **Control parameters**

### Ingredients with workplace control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

		hongrun	plastics.com		
SAFETY DATA	SHEET	-		Ivond	ellbasell
				iy on a	
Alathon M60	20SB			Gen. Variant	: SDS_US_GHS
Version 1.2	Revision Date 10	01/01/2010	Print Date 01/		SDS No.: BE9920
VEISION 1.2	Revision Date R	5/01/2019		03/2022	505 NO DL992(
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	15 mg/m3	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

#### **Exposure controls**

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Alathon M6020SB	Gen. Variant: SDS_US_GHS
/ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE99
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>
PHYSICAL AND CHEMICAL P Appearance	ROPERTIES : Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer due varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hen any male attender and	
AFETY DATA SHEET	hongrunplastics.com	
AFEIT DATA SHEET	lyondellbase	
lathon M6020SB	Gen. Variant: SDS_US_GH	
ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BES	
Partition coefficient: n- octanol/water	: No Data Available.	
Viscosity, dynamic	: Not applicable.	
Relative vapor density	: Not applicable.	
Evaporation rate	: Not applicable.	
Explosive properties	: No Data Available.	
Other Information	: No additional information available.	
STABILITY AND REACTIVITY	, ,	
Reactivity	: No known reactivity hazards.	
Chemical stability	: Stable under normal conditions.	
Hazardous reactions	: Will not occur.	
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.	
Materials to avoid	: Material may be softened by some hydrocarbons.	
Hazardous decomposition products	: Not expected to decompose under normal conditions.	
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.	
TOXICOLOGICAL INFORMAT	ΓΙΟΝ	
Acute toxicity		
Acute oral toxicity	: Not classified	
Acute inhalation toxicity	: Not classified	
Acute dermal toxicity	: Not classified	
Skin corrosion/irritation	: Not a skin irritant.	
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.	
	8 / 13	

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Alathon M6020SB	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 7	10/01/2019 Print Date 01/05/2022 SDS No.: BE9920
Respiratory or skin sensitization Chronic toxicity	: Not classified
Carcinogenicity	: Not classified
	Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Alathon M6020SB	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 1	0/01/2019 Print Date 01/05/2022 SDS No.: BE9920
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	<ul> <li>Ecotoxicity is expected to be minimal based on the low water solubility of polymers.</li> <li>No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.</li> </ul>
13. Disposal considerations Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
Not regulated for transport	
15. REGULATORY INFORMATION	
	10 / 13

## SAFETY DATA SHEET

## Alathon M6020SB

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE9920

lyondellbase

### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

### Combustible dust

#### **SARA 313**

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

557-05-1 Zinc Stearate

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Inventory	Status Description	
AICS	Compliant	
DSL	Compliant	
IECSC	Compliant	
11 / 1	3	
11/1	5	
	AICS DSL IECSC	AICS Compliant DSL Compliant

SAFETY DATA SHEET	nongranpia	stics.com			
	-		lyondellbasel		
			Gen. Variant: SDS_US_GHS		
Alathon M6020SB	D-1- 40/04/0040	Duint Data 04			
Version 1.2 Revision	Date 10/01/2019	Print Date 01	/05/2022 SDS No.: BE992		
Europe	REACH	See REA	ACH Compliance Statement		
Japan	ENCS	Complia			
Korea	KECI	Complia	Compliant		
New Zealand	NZIoC	Complia	Compliant		
Philippines	PICCS		Compliant		
United States of Ame			Compliant		
Taiwan	TCSCA	Complia	nt		
EACh status					
907/2006) *This product contains Safety for additional in Contact product.safety@lyb.co	nformation.	-	lume restrictions. Contact Product		
6. OTHER INFORMATION		ve been und	ated.		
Material safety datashed		ve been upd	ated:		
		0	ated:		
Material safety datashed Revised Section(s): 15	16 : Health Hazard: Flammability: 1	0 ds: 0			
Material safety datashed Revised Section(s): 15 HMIS Classification	<ul> <li>16</li> <li>Health Hazard: Flammability: 1 Physical hazard</li> <li>Health Hazard: Fire Hazard: 1</li> </ul>	0 ds: 0	0 1 0		
Material safety datashed Revised Section(s): 15 HMIS Classification NFPA Classification	<ul> <li>Health Hazard: Flammability: 1 Physical hazard</li> <li>Health Hazard: Fire Hazard: 1 Instability: 0</li> </ul>	0 ds: 0 0	0 1 0		

(+)	188	1699	6168
hon	arunı	olastic	s.com

# SAFETY DATA SHEET

## Alathon M6020SB

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE9920

ondellbase

NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

### Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

### End of Material Safety Data Sheet