	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET according to Regulation (EC) No.	1907/2006	lyondellbasell
Hostalen CRP 100 RES	SIST S ORANGE-YELLOW	Gen. Variant: SDS_AT
	e 05/31/2020 Print Date 01/05/2	
1. Identification of the substance	/mixture and of the company/under	aking
1.1 Product identifier		
Trade name Synonyms Substance name Substance No. Chemical characterization	 Hostalen CRP 100 RESIST S OR Ethylene, polymer with 1-butene, 1-Butene, polymer with ethene 25087-34-7 Polyethylene copolymer 	
1.2 Relevant identified uses of th	ne substance or mixture and uses ac	lvised against
Identified uses	: Manufacture of plastic articles by i or other conversion process.	njection molding, extrusion
Prohibited uses	: FDA Class III medical devices; Eu devices; Health Canada class IV M Applications involving permanent Life-sustaining medical application	Nedical Devices; implantation into the body;
1.3 Details of the supplier of the	safety data sheet	
Company Basell Sales & Marketing Compa	ny B.V. NA	Telephone 31 (0) 10 275 55 00
Delftseplein 27E 3013 AA Rotterdam Netherlands		
3013 AA Rotterdam	: product.safety@lyb.com	
3013 AA Rotterdam Netherlands E-mail address		
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person	er	+32 3 575 1235
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe	er	
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe Basell Sales & Marketing Compa <u>Poison Center:</u> Gesundheid Österreich GMBH AT: +43 1 406 43 43	er	
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe Basell Sales & Marketing Compa <u>Poison Center:</u> Gesundheid Österreich GMBH AT: +43 1 406 43 43	er	
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe Basell Sales & Marketing Compa <u>Poison Center:</u> Gesundheid Österreich GMBH AT: +43 1 406 43 43	er	
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe Basell Sales & Marketing Compa <u>Poison Center:</u> Gesundheid Österreich GMBH AT: +43 1 406 43 43	er Ing B.V.	
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe Basell Sales & Marketing Compa <u>Poison Center:</u> Gesundheid Österreich GMBH AT: +43 1 406 43 43	er Ing B.V.	
3013 AA Rotterdam Netherlands E-mail address Responsible/issuing person 1.4 Emergency telephone numbe Basell Sales & Marketing Compa <u>Poison Center:</u> Gesundheid Österreich GMBH AT: +43 1 406 43 43	er Ing B.V.	

	(+) 18	8 1699 6168	
	hongru	nplastics.com	
SAFETY DATA SHEE according to Regulation (EC			yondellbasell
Hostalen CRP 100	RESIST S ORA	NGE-YELLOW	Gen. Variant: SDS_AT
Version 1.4 Revisio	on Date 05/31/2020	Print Date 01/05/202	22 SDS No.: BE7784
2. Hazards identification			
2.1 Classification of the su	bstance or mixture		
Classification (REGUL	ATION (EC) No 1272	/2008)	
Not a hazardous substa	nce or mixture accord	ing to Regulation (EC) No	o 1272/2008.
2.2 Label elements			
Labeling (REGULATIO	N (EC) No 1272/2008)	
Not a hazardous substa	ince or mixture accord	ng to Regulation (EC) N	o 1272/2008.
2.3 Other hazards			
combustible dust conce	ntrations in air. contains no componer	nts considered to be eithe	by other means, may form er persistent, bioaccumulative
3. Composition/information	on ingredients		
3.2 Mixtures			
Components			
Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	<u>Weight %</u>
1-Butene, polymer with ethene	25087-34-7	Not Classified	98.0 - 100.0 %
Contains: Additives and	d stabilizers		
4. First aid measures			
4.1 Description of first-aid	measures		
General advice		r precautions to ensure y mpting rescue and provid	your own health and safety ing first aid.
If inhaled			/symptoms continue, get
		2 / 16	

Hostalen CRP 100 RESIST S ORANGE-YELLOW Gen. Variant: SDS.AT Version 1.4 Revision Date 05/31/2020 Print Date 01/05/2022 SDS No.: BET medical attention. In case of excessive inhalation of furmes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Do not attempt to peel polymer from skin as this will remove the skin. In case of eye contact I case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed A deverse health effects due to ingestion are not anticipated. 42 Most important symptoms and effects, both acute and delayed Symptoms Symptoms Inhalation of process furmes and vapors may cause soreness in the nose and threat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment immediate condition of t		(+) 188 1699 6168
according to Regulation (EC) No. 1907/2006 Gen. Variant: SDS_AT Version 1.4 Revision Date 05/31/2020 Print Date 01/05/2022 SDS No.: BET medical attention. In case of excessive inhalation of furmes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention. It case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention. It case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention. It swallowed Adverse health effects due to ingestion are not anticipated. 42 Most important symptoms and effects, both acute and delayed Symptoms Inhalation of process furmes and vapors may cause soreness in the nose and throat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal b		hongrunplastics.com
Version 1.4 Revision Date 05/31/2020 Print Date 01/05/2022 SDS No.: BE7 medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm. if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention. If discomfort persists. In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 42 Most important symptoms and effects, both acute and delayed Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention a	•••••••••••••••••••••••••••••••••••••••	1907/2006 Iyondellbasel
medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 42 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms		
In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	Version 1.4 Revision Dat	e 05/31/2020 Print Date 01/05/2022 SDS No.: BE778
In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.		
large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media		In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary
In case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed Adverse health effects due to ingestion are not anticipated. A2 Most important symptoms and effects, both acute and delayed Symptoms Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. A.3 Indication of any immediate medical attention and special treatment needed Treatment Treatment Fire-fighting measures 5.1 Extinguishing media	In case of skin contact	large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep
Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media	In case of eye contact	: Flush eyes thoroughly with water for several minutes and seek
4.2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media		Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).
Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Indication of any immediate medical attention and special treatment needed Treatment Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Fire-fighting measures 5. Fire-fighting measures	If swallowed	: Adverse health effects due to ingestion are not anticipated.
 in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Fire-fighting measures 5. Fire-fighting media 	l.2 Most important symptoms a	nd effects, both acute and delayed
Molten polymer may cause thermal burns. I.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media	Symptoms	
Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media	Hazards	
symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media	I.3 Indication of any immediate	medical attention and special treatment needed
5.1 Extinguishing media	Treatment	
	5. Fire-fighting measures	
3 / 16	5.1 Extinguishing media	
		3 / 16

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to Regulation (EC) No. 1	907/2006 lyondellbasell
	ST S ORANGE-YELLOW Gen. Variant: SDS_AT
Version 1.4 Revision Date	05/31/2020 Print Date 01/05/2022 SDS No.: BE7784
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising from t	he substance or mixture
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
5.3 Advice for firefighters	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
6. Accidental release measures	
6.1 Personal precautions, protect	ve equipment and emergency procedures
Personal precautions	: Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface.
	4 / 16

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to Regulation (EC) No. 19	07/2006 Iyondellbasell
Hostalen CRP 100 RESIS	ST S ORANGE-YELLOW Gen. Variant: SDS_AT
Version 1.4 Revision Date (05/31/2020 Print Date 01/05/2022 SDS No.: BE7784
	Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
6.2 Environmental precautions	
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
6.3 Methods and materials for cont	ainment and cleaning up
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
7. Handling and storage	
7.1 Precautions for safe handling	
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material
	5 / 16

		(+) 18	8 1699 6168		
		hongru	nplastics.com		
SAFETY DATA SH according to Regulation		2006		lyond	ellbasell
Hostalen CRP 1	00 RESIST	SORA	NGE-YELL	OW Gen. Variant	t: SDS_AT
	vision Date 05/		Print Date 01		SDS No.: BE7784
	s / c / v v v r	should be g All electrical codes and r combustible After handlir vater. When bringi	rounded and bon equipment shou egulatory requirer dusts. ng, always wash ng the material to		cable electric ndling vith soap and eratures vapors
Fire-fighting class	: F	Polymer will	burn but does no	ot easily ignite.	
7.2 Conditions for safe	storage, inclu	ding any ir	ncompatibilities		
 Requirements for storage areas and containers Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. 7.3 Specific end use(s) 					e ventilation llation. strong
		See Section	1.2.		
8. Exposure controls/pe 8.1 Control parameters Ingredients with w Occupational Expo	orkplace contr		ters		
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
				Trevision Date	mormation
		6	6 / 16		

(+) 188 1699 6168 hongrunplastics.com lyondellbasell SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Hostalen CRP 100 RESIST S ORANGE-YELLOW Gen. Variant: SDS_AT Version 1.4 Revision Date 05/31/2020 Print Date 01/05/2022 SDS No.: BE7784 Materials that can TWA 10 mg/m3 US (ACGIH) be formed when inhalable 2005 handling this product: Nonspecified (inert or nuisance) dust Materials that can TWA 3 mg/m3 US (ACGIH) be formed when respirable 2005 handling this product: Nonspecified (inert or nuisance) dust Consult local authorities for acceptable exposure limits. 8.2 Exposure controls **Engineering measures** Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product. Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Personal protective equipment : Use process enclosures, local exhaust ventilation, or other Respiratory protection engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.

 Hand protection
 : Wear gloves that provide thermal protection where there is a potential for contact with heated material.

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to Regulation (EC) No.	1907/2006 Iyondellbasell
	SIST S ORANGE-YELLOW Gen. Variant: SDS_AT
Version 1.4 Revision Da	te 05/31/2020 Print Date 01/05/2022 SDS No.: BE7784
Eye and face protection	: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which
	may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
Environmental exposure co	ontrols
General advice	: See section 6.
9. Physical and chemical proper 9.1 Information on basic physica	
Appearance	: Pellets.
Color	: yellow-orange
Odor	: Slight.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
	8 / 16

SAFETY DATA SHEET according to Regulation (EC) No. 7 Hostalen CRP 100 RES Version 1.4 Revision Date Decomposition temperature	SIST S ORANGE-YELLOW Gen. Variant: SDS_AT
according to Regulation (EC) No. 7 Hostalen CRP 100 RES Version 1.4 Revision Date	Gen. Variant: SDS_AT
Version 1.4 Revision Date	
	e 05/31/2020 Print Date 01/05/2022 SDS No.: BE778
Decomposition temperature	
Decomposition temperature	
Decomposition temperature	
	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
9.2 Other information Other information	: No additional information available.
	. No additional mormation available.
10. Stability and reactivity	
10.1 Reactivity	
No known reactivity hazards.	
10.2 Chemical stability	
Stable under normal conditions	S.
10.3 Possibility of hazardous rea	ictions
Hazardous reactions	: Will not occur.
10.4 Conditions to avoid	
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
	9 / 16

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to Regulation (EC) No.	
	SIST S ORANGE-YELLOW Gen. Variant: SDS_AT
Version 1.4 Revision Da	te 05/31/2020 Print Date 01/05/2022 SDS No.: BE7784
10.5 Incompatible materials Materials to avoid	: Material may be softened by some hydrocarbons.
10.6 Hazardous decomposition	
Hazardous decomposition	: Not expected to decompose under normal conditions.
products	
Thermal decomposition	: Note: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
11. Toxicological information	
11.1 Information on toxicologica	al effects
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	10 / 16

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to Regulation (EC) N	
	ESIST S ORANGE-YELLOW Gen. Variant: SDS_AT
Version 1.4 Revision D	Date 05/31/2020 Print Date 01/05/2022 SDS No.: BE7784
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility /	: Not classified
Effects on or via lactation Effects on Development	: Not classified
Target Organ Systemic To	oxicant - Single exposure
	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic To	oxicant - Repeated exposure
	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
12.1 Ecotoxicology Assessmer	nt
Short-term (acute) aquatio	c : Not classified
hazard Long-term (chronic) aquatic hazard	: Not classified
12.2 Persistence and degrada	bility
Biodegradability	: Not expected to be biodegradable.
12.3 Bioaccumulative potentia	il de la constant de
Bioaccumulation	: This material is not expected to bioaccumulate.
	11 / 16

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to Regulation (EC) No.	1907/2006 Iyondellbasell
	SIST S ORANGE-YELLOW Gen. Variant: SDS_AT
Version 1.4 Revision Da	te 05/31/2020 Print Date 01/05/2022 SDS No.: BE7784
12.4 Mobility in soil	
Mobility	: no data available
12.5 Results of PBT and vPvB a	ssessment
Result	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).
12.6 Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
12.7 Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
13.1 Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
14. Transport information	
	12 / 16

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

lyondellbasell

Hostalen CRP 100 RESIST S ORANGE-YELLOW Gen. Variant: SDS_AT

Version 1.4

Revision Date 05/31/2020

Print Date 01/05/2022

SDS No.: BE7784

Not regulated for transport

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

Contact product.safety@lyb.com for additional global inventory information.

15.2 Chemical safety assessment

No information available.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

lyondellbasell

Hostalen CRP 100 RESIST S ORANGE-YELLOW Gen. Variant: SDS_AT

Version 1.4

Revision Date 05/31/2020

Print Date 01/05/2022

SDS No.: BE7784

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists ACGIH BEIs - American Conference of Governmental Industrial Hygienists Biological Exposure Indices ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances ASTM - American Society for Testing and Materials **BEL - Biological Exposure Limits** BTEX - Benzene, Toluene, Ethylbenzene, Xylenes CAS - Chemical Abstracts Service **CEFIC - European Chemical Industry Council** CLP - Classification Packaging and Labelling COC - Cleveland Open-Cup CS - Consumer Scenario DIN - Deutsches Institut für Normung DN(M)EL - Derived No (Minimal) Effect Level DSL - Canada Domestic Substance List EC - European Commission EC50 - Median Effective Concentration ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals ECHA - European Chemicals Agency EL50 - Effective Loading fifty ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods **IECSC** - Chinese Chemicals Inventory **IOELV - Indicative Occupational Exposure Limit Values** IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI - Korea Existing Chemicals Inventory Koc - Organic Carbon/Water Partition Coefficient

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

lyondellbasell

Hostalen CRP 100 RESIST S ORANGE-YELLOW Gen. Variant: SDS_AT

Version 1.4

Revision Date 05/31/2020

Print Date 01/05/2022

SDS No.: BE7784

LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level NZIoC - New Zealand Inventory of Chemicals OE_HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration PPE - Personal Protective Equipment PROC - Process Category QSAR - Quantitative Structure-Activity Relationship REACh - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average UN - United Nations vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Hostalen CRP 100 RESIST S ORANGE-YELLOW Gen. Variant: SDS_AT

Version 1.4

Revision Date 05/31/2020

Print Date 01/05/2022

SDS No.: BE7784

lyondellbasell

Disclaimer

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet