(+) 188 1699 6168

	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbasell
Hostalen GF 9045 F		Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date	04/08/2021 Print Date 0	1/05/2022 SDS No.: BE7820
1. IDENTIFICATION OF THE SUBS	STANCE/MIXTURE AND OF	THE COMPANY/UNDERTAKING
Trade name CAS Number:	: Hostalen GF 9045 F : 25087-34-7	
Chemical characterization	: Polyethylene copolymer	
Chemical name	: 1-Butene, polymer with e	
Synonyms	: Ethylene, polymer with 1	-butene, Ethene-Butene copolymer
Identified uses	: Manufacture of plastic an or other conversion proce	ticles by injection molding, extrusion ess.
Prohibited uses	devices; Health Canada	rmanent implantation into the body;
<u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 30 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583		vice 888 777-0232
Emergency telephone number EQUISTAR 800-245-4532 E-mail address Responsible/issuing person	er : product.safety@lyb.com	
2. HAZARDS IDENTIFICATION		
GHS Classification		
Combustible dust		
Label elements		
Signal word	: Warning	
Hazard Statements		nerated during further processing, ns, may form combustible dust
Other hazards		
	1 / 13	

	(+) 188 1699 6168	
	hongrunplastics.com	
AFETY DATA SHEET		lyondellbasell
ostalen GF 9045 F		Gen. Variant: SDS_US_GHS
ersion 1.0 Revision Date (04/08/2021 Print Date 01/0	05/2022 SDS No.: BE7820
No additional information ava	ailable.	
COMPOSITION/INFORMATION	ON INGREDIENTS	
xtures		
Components		<u> </u>
Chemical name	CAS-No.	<u>Weight %</u>
1-Butene, polymer with ethene	25087-34-7	98.0 - 100.0 %
Contains: Stabilizers		
FIRST AID MEASURES		
General advice	: Take proper precautions to before attempting rescue a	ensure your own health and safety nd providing first aid.
If inhaled	medical attention. In case of excessive inhala during heating of this mate Obtain medical attention.	r. If signs/symptoms continue, get tion of fumes that may be generated rial, move the person to fresh air. ssary give Cardio-Pulmonary
In case of skin contact	large amounts of water to o Do not attempt to peel poly skin.	the skin, immediately flush with cool the affected tissue and polymer. mer from skin as this will remove the cy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discomination di d	water for several minutes and seek fort persists.
	minutes.	vith cool running water for at least 15 attempt to remove the material
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
	2 / 13	

Hostalen GF 9045 F Gen. Variant: SDS_US_G Version 1.0 Revision Date 04/08/2021 Print Date 01/05/2022 SDS No.: BE Notes to physician Symptoms : Inhalation of process fumes and vapors may cause sorene the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. Suitable extinguishing media : SMALL FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : Nore known. Specific hazards during fire fighting : Noee known. Special protective equipment for fire-fighters : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocard (smote). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose ounder fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire area if it		hongrunplastics.com
Version 1.0 Revision Date 04/08/2021 Print Date 01/05/2022 SDS No.: EE Notes to physician Symptoms : Inhalation of process fumes and vapors may cause sorene the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the contrasymptoms and the clinical condition of the patient. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. Suitable extinguishing media : SMALL FIRE: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : None known. Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarl (smoke). Further information : Wear approved positive pressure self-contained breathing aparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calonfic Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat firammable vapors. Move containers from fire area if it can be done without fis Evacuate immediately in the event of opening of storage container pressure rel	SAFETY DATA SHEET	lyondellbase
Notes to physician Symptoms : Inhalation of process fumes and vapors may cause sorene the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the contr symptoms and the clinical condition of the patient. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. Unsuitable extinguishing media : SMALL FIRE: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing aparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompase polymer, and generat framable vapors. Move containers from fire area if it can be done without fis Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contai Always stay away from t	Hostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Symptoms : Inhalation of process fumes and vapors may cause sorene the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the contresymptoms and the clinical condition of the patient. FIRE-FIGHTING MEASURES : Treatment of overexposure should be directed at the contresymptoms and the clinical condition of the patient. Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. Unsuitable extinguishing media : SMALL FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocard (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without fis Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contai Always stay away from tanks engulfed in fire. Do	Version 1.0 Revision Date (04/08/2021 Print Date 01/05/2022 SDS No.: BE78
Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the contrisymptoms and the clinical condition of the patient. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. Suitable extinguishing media : SMALL FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : None known. Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat fammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage containers pressure relief devices or discoloration of contail Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even		: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing media : None known. Specific hazards during fire fighting : Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Special protective equipment for fire-fighters : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information : Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat fammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contai Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire.	Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Suitable extinguishing media: SMALL FIRE: Use dry chemical, CO2, or water spray.Unsuitable extinguishing media Specific hazards during fire fighting: None known.:None known.:: Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke).:Special protective equipment for fire-fighters::: <td>Treatment</td> <td>: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.</td>	Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
 Unsuitable extinguishing media Specific hazards during fire fighting Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Special protective equipment for fire-fighters Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Further information Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contait Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even 		Use dry chemical, CO2, or water spray. : LARGE FIRES:
 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Special protective equipment for fire-fighters Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. 	• •	
for fire-fightersapparatus and firefighter protective clothing.Further information: Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even	Specific hazards during fire	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbon
conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. Cool storage containers with large volumes of water even		
	Further information	 conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after the storage container of the storage containers with large volumes of the storage container of the storage containers with large volumes of the storage container of the storage container of the storage containers with large volumes of the storage container of the storage container of the storage containers with large volumes of the storage container of the storage container of the storage containers with large volumes of the storage container of the storage container of the storage container of the storage containers with large volumes of the storage container of the storage c
3 / 13		3/13

Hostalen GF 9045 F Gen. Variant: SDS_US_I Version 1.0 Revision Date 04/08/2021 Print Date 01/05/2022 SDS No.: B 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protec equipment (PE) Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sever system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On vater, material shouldbe; collect and contain as any solid. All recovered material shouldbe packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with g engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid generating just; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion		hongrunplastics.com
Version 1.0 Revision Date 04/08/2021 Print Date 01/05/2022 SDS No.: B S. ACCIDENTAL RELEASE MEASURES Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid degenerating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfac with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with g engineering practices. Reclaim where possible. 7. Handling and storage : Methods for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in t presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion	SAFETY DATA SHEET	lyondellbase
3. ACCIDENTAL RELEASE MEASURES Personal precautions Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protec equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfac with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions Comparison of the surface water or sanitary sewer system. Methods for containment / Methods for containment / Methods for cleaning up Comparison of the surface water or sanitary sewer system. Methods for cleaning up Comparison of the surface water or sanitary sewer system. Methods for cleaning up Comparison of the surface water of the surface water or sanitary sewer system. Methods for cleaning up Comparison of the surface water of the surface water or sanitary sewer system. Methods for cleaning up Comparison of the surface water of the surface water or cleaning the surface water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance applicable laws and regulations and in conformance applicable laws and regulations and in conformance use dust accumutation. Avoid dust accumutation in enclosed space. Use dust colection systems designed per NFPA 64 to av dust accumutation. Avoid generating dust; fine dust suspended in air and in t presence of an ignition source is a potential dust explosion Electrostatic charge (spark), or other ignition sources, in high - environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlin	Hostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Personal precautions 2 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid denerating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions 2 Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up 2 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with g engineering practices. Reclaim where possible. 7. Handling and storage 2 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid dust fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling	Version 1.0 Revision Date 04	I/08/2021 Print Date 01/05/2022 SDS No.: BE78
Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid denerating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfac with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with g engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid gust fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling		
Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protec equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed or reclaimed in conformance with gengineering practices. Reclaim where possible. 7. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling	6. ACCIDENTAL RELEASE MEASUR	RES
Methods for containment / : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with gengineering practices. Reclaim where possible. 7. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion	Personal precautions	 Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
 Methods for cleaning up vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance or engineering practices. Reclaim where possible. 7. Handling and storage Precautions for safe handling Advice on safe handling Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlir 	Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlir		vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlir		
grounded (earthed) and bonded.	Advice on safe handling :	If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and
4 / 13		//13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Hostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04	/08/2021 Print Date 01/05/2022 SDS No.: BE7820
	Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Fire-fighting class :	Polymer will burn but does not easily ignite.
Conditions for safe storage, in	sluding any incompatibilities
Requirements for storage : areas and containers	Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	See Section 1.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

CAS-No.	Туре	Limit Value	Basis	Additional
			Revision Date	Information
	TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
	CAS-No.		TWA 10 mg/m3	TWA 10 mg/m3 US (ACGIH)

		hongrun	plastics.com		
SAFETY DATA	SHEET			lyond	ellbasell
Hostalen GF	9045 F			Gen. Variant	:: SDS_US_GHS
Version 1.0	Revision Date 04	1/08/2021	Print Date 01	/05/2022	SDS No.: BE7820
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when handling this			respirable	2005	
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	15 mg/m3	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non-					
specified (inert or nuisance) dust					
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
lostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date	e 04/08/2021 Print Date 01/05/2022 SDS No.: BE78
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL P	
Appearance Color	: Pellets. : Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dua varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Hostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date	e 04/08/2021 Print Date 01/05/2022 SDS No.: BE78
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
0. STABILITY AND REACTIVITY	,
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition products	: Not expected to decompose under normal conditions.
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
1. TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Hostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 0	4/08/2021 Print Date 01/05/2022 SDS No.: BE7820
Respiratory or skin sensitization Chronic toxicity	: Not classified
Carcinogenicity	: Not classified
	Not listed by IARC, NTP, OSHA or EPA.
	······································
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Hostalen GF 9045 F	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04	V08/2021 Print Date 01/05/2022 SDS No.: BE7820
Bioaccumulative potential	
Bioaccumulation	This material is not expected to bioaccumulate.
Mobility in soil	
Mobility :	no data available
Other adverse effects	
Environmental fate and : pathways	This material is not volatile and insoluble in water.
Other information	
Additional ecological : information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations Waste treatment methods	
Product :	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
:	This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
Not regulated for transport	
15. REGULATORY INFORMATION	
	10 / 13

SAFETY DATA SHEET

Hostalen GF 9045 F

Version 1.0

Revision Date 04/08/2021 Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE7820

lyondellbase

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description				
Australia	AICS	Compliant				
Canada	DSL	Compliant				
China	IECSC	Compliant				
Europe	REACH	See REACH Compliance Statement				
Japan	ENCS	Compliant				
11 / 13						

		(+) 188 1699	9 6168					
		hongrunplasti	cs.com					
SAFE	TY DATA SHEET						hac	
••••				IY	ond	IGII	Daz	EII
					n. Variar			
	talen GF 9045 F				n. variar			
Versior	n 1.0 Revision Date 0	4/08/2021 Prii	nt Date 01	/05/2022		SDS	No.: BI	= 7820
	Korea	KECI	Compliant					
	New Zealand	NZIOC	Compliant					
	Philippines United States of America	PICCS TSCA	Complia Complia					
	Taiwan	TCSCA	Complia					
			Compila]
REACh	status							
	oduct has been purchased fro							
	ed in the European Union, we ed under REACh, in accordar							
1907/20			163 361 101			julatio	(ĽO) I	NU.
Contact	product.safety@lyb.com for a	additional global in	entory inf	formation				
Contact	product.salety eryb.com for a		vernory in	ormation.				
16 OTH	HER INFORMATION							
10. 011								
Ma	aterial safety datasheet sect	ions which have	been upd	ated:				
Fir	rst Edition							
HM	IIS Classification	Health Hazard: 0						
		Flammability: 1	_		0 1	0		
		Physical hazards:	0					
NF	PA Classification	Health Hazard: 0						
		Fire Hazard: 1						
		Instability: 0						
								<u> </u>
						' /	$\langle 0 \rangle$	/
						\mathbf{i}		
						$\overline{\}$	/	
_								
Fu	urther information							
нл	/IS rating scale (0 = minimal	nazard: 4 = severe	hazard)					
	PA rating scale (0 = minimal							
	3	,	,					
		Disclai	mer					
		12 / 13						
		12,10						
1								

SAFETY DATA SHEET

Hostalen GF 9045 F

Version 1.0

Revision Date 04/08/2021

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE7820

iyondellbase

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet