(+) 188 1699 6168

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasel
Hyperzone HY55430SX	
Version 1.1 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE1685
. IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name CAS Number: Chemical characterization Chemical name Synonyms	 Hyperzone HY55430SX01 25213-02-9 Polyethylene copolymer 1-Hexene,polymer with ethene Ethylene-1-hexene copolymer, Ethylene-Hexene Copolymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications
<u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 3 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583	Customer Service 888 777-0232 00 product.safety@lyb.com
Emergency telephone numb EQUISTAR 800-245-4532	<u>er</u>
E-mail address Responsible/issuing person	: product.safety@lyb.com
HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 13

		(+) 188 1699 6168	
		hongrunplastics.com	
SAFETY DATA	SHEET		lyondellbasell
Hyperzone H	IY55430SX0)1	Gen. Variant: SDS_US_GHS
Version 1.1	Revision Date 1		/05/2022 SDS No.: BE16859
No additiona	al information avai	ilable.	
3. COMPOSITION/I	NEORMATION C		
Mixtures			
Components			
	al name	CAS-No.	Weight %
			······································
1-Hexene,polym	er with ethene	25213-02-9	<=99.5 %
Contains: Addi	tives and stabilize	ers	
4. FIRST AID MEAS	SURES		
General advice		: Take proper precautions to before attempting rescue	to ensure your own health and safety and providing first aid.
If inhaled		medical attention. In case of excessive inhal during heating of this mat Obtain medical attention.	air. If signs/symptoms continue, get lation of fumes that may be generated erial, move the person to fresh air. ressary give Cardio-Pulmonary
In case of skin	contact	large amounts of water to Do not attempt to peel po skin.	s the skin, immediately flush with cool the affected tissue and polymer. lymer from skin as this will remove the ency medical attention if burn is deep
In case of eye	contact	: Flush eyes thoroughly wit medical attention if discor	h water for several minutes and seek nfort persists.
		minutes.	with cool running water for at least 15 attempt to remove the material
If swallowed		: Adverse health effects du	e to ingestion are not anticipated.
		2 / 13	
		2,10	

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Hyperzone HY55430SX	01 Gen. Variant: SDS_US_GHS
/ersion 1.1 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE168
Notes to physician Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES Suitable extinguishing media	 SMALL FIRE: Use dry chemical, CO2, or water spray. LARGE FIRES:
Unsuitable extinguishing	Use water spray hose nozzles from a safe location. : None known.
media Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasel
Hyperzone HY55430SX	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	
. ACCIDENTAL RELEASE MEAS	URES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
. Handling and storage Precautions for safe handlin	g
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.
	4 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Hyperzone HY55430SX	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	
	Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Fire-fighting class	: Polymer will burn but does not easily ignite.
	ncluding any incompatibilities
Requirements for storage areas and containers	 Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	: See Section 1.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	

SAFETY DATA SHEET

SAFEIT DATA	SHEET			Iyona	elidaseli
Hyperzone H	V55/30SY01			Gen. Varian	t: SDS_US_GHS
	Revision Date 10/0	1/2010	Print Date 01/0		SDS No.: BE16859
		1/2013		JJ/2022	505 NO DE 10033
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	15 mg/m3	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust			- / 0		
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

lyon dellerer

	hongrunplastics.com	
AFETY DATA SHEET	lyondellbase	
lyperzone HY55430SX		
ersion 1.1 Revision Date 1	0/01/2019 Print Date 01/05/2022 SDS No.: BE16	
	injury or other irritation to eyes due to airborne particles which may result from handling this product.	
Skin and body protection	: Wear suitable protective clothing.	
Hygiene measures	 Wear suitable protective clothing. Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. 	
PHYSICAL AND CHEMICAL PRO Appearance Color	: Pellets.	
	: Pellets. : Translucent to white	
Appearance Color	: Pellets.	
Appearance Color Odor	Pellets.Translucent to whiteSlight.	
Appearance Color Odor Odor Threshold	 Pellets. Translucent to white Slight. No value available. 	
Appearance Color Odor Odor Threshold Flash point	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer due 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer durvaries according to particle size distribution. 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 Pellets. Translucent to white Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer durvaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable. 	

(+) 188 1699 6168

hongrunplastics.com SAFETY DATA SHEET lyondellbasel Gen. Variant: SDS_US_GHS Hyperzone HY55430SX01 Version 1.1 Revision Date 10/01/2019 Print Date 01/05/2022 SDS No.: BE16859 : No Data Available. Partition coefficient: noctanol/water Viscosity, dynamic : Not applicable. Relative vapor density : Not applicable. Evaporation rate : Not applicable. Explosive properties : No Data Available. Other Information : No additional information available. **10. STABILITY AND REACTIVITY** Reactivity : No known reactivity hazards. : Stable under normal conditions. Chemical stability Hazardous reactions : Will not occur. Conditions to avoid : Avoid contact with strong oxidizers, excessive heat, sparks or open flame. Materials to avoid : Material may be softened by some hydrocarbons. Hazardous decomposition : Not expected to decompose under normal conditions. products Thermal decomposition Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed. **11. TOXICOLOGICAL INFORMATION** Acute toxicity Acute oral toxicity : Not classified Acute inhalation toxicity : Not classified Acute dermal toxicity : Not classified Skin corrosion/irritation : Not a skin irritant. Serious eye damage/eye : Not an eye irritant. irritation Mechanical irritation is possible.

8 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Hyperzone HY55430SX	Gen. Variant: SDS_US_GHS
/ersion 1.1 Revision Date	
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
2. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Hyperzone HY55430SX0	1 Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date 10	01/2019 Print Date 01/05/2022 SDS No.: BE16859
Bioaccumulative potential	
Bioaccumulation :	This material is not expected to bioaccumulate.
Mobility in soil	
Mobility :	no data available
Other adverse effects	
Environmental fate and : pathways	This material is not volatile and insoluble in water.
Other information	
Additional ecological : information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product :	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
:	This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
Not regulated for transport	
15. REGULATORY INFORMATION	
	10 / 13

SAFETY DATA SHEET

Hyperzone HY55430SX01

Version 1.1

1 Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE16859

lyondellbase

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description	
Australia	AICS	Compliant	
Canada	DSL	Compliant	
China	IECSC	Compliant	
Europe	REACH	See REACH Compliance Statement	
Japan	ENCS	Not Determined	
11 / 13			

(+) 188 1699 6168

hongrunplastics.com

SAFETY DATA SHEET

Hyperzone HY55430SX01 Revision Date 10/01/2019

Version 1.1

Print Date 01/05/2022

Gen. Variant: SDS US GHS SDS No.: BE16859

lyondellbase

0

0

0

Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification : Health Hazard: 0 Flammability: 1 Physical hazards: 0

NFPA Classification : Health Hazard: 0

Fire Hazard: 1 Instability: 0

Further information

HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

 Disclaimer	
12 / 13	

SAFETY DATA SHEET

Hyperzone HY55430SX01

Version 1.1

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS

lvondellbase

SDS No.: BE16859

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet