(+) 188 1699 6168

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LB560201	Gen. Variant: SDS_US_GF
ersion 1.2 Revision Date	
IDENTIFICATION OF THE SUB	TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name CAS Number:	: Petrothene LB560201 : 25213-02-9
Chemical characterization	: Polyethylene copolymer
Chemical name	: 1-Hexene, polymer with ethene
Synonyms	: Ethylene-1-hexene copolymer, Ethylene-Hexene Copolymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	 FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications
<u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 30 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583	Customer Service 888 777-0232 product.safety@lyb.com
<u>Emergency telephone numb</u> EQUISTAR 800-245-4532	<u>er</u>
E-mail address Responsible/issuing person	: product.safety@lyb.com
HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	

Petrothene LB560201 Gen. Variant: SDS_US_GH Version 1.2 Revision Date 10/01/2019 Print Date 01/05/2022 SDS No.: BE11 No additional information available. Image: SDS No.: BE11 SDS No.: BE11 No additional information available. Image: SDS No.: BE11 SDS No.: BE11 S. COMPOSITION/INFORMATION ON INGREDIENTS Image: SDS No.: BE11 Image: SDS No.: BE11 Mixtures Components Image: SDS No.: SDS NO		(+) 188 1699 6168		
Petrothene LB560201 Gen. Variant: SDS_US_GH Version 1.2 Revision Date 10/01/2019 Print Date 01/05/2022 SDS No.: BET No additional information available. 3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Contains: Stabilizers Contains: Stabilizers A FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. Nease of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immedical attention if burn is decore xetensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with water fo		hongrunplastics.com		
Version 1.2 Revision Date 10/01/2019 Print Date 01/05/2022 SDS No.: BE1 No additional information available. 3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Components Version 1.2 Version 1.2 Version 1.2 SDS No.: BE1 Image: Additional information available. Components Version 1.2 Version 1.2 Version 1.2 Chemical name CAS-No. Weight % Version 1.2 Version 1.2 Image: Additional information available. Components Version 1.2 Version 1.2 Version 1.2 Contains: Stabilizers Contains: Stabilizers Version 1.2 Version 1.2 Version 2.2 Stabilizers If inhaled : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attemption. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. No detain medical attention. In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly	SAFETY DATA SHEET		lyondellbasell	
No additional information available. 3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Chemical name CAS-No. Weight % 1-Hexene,polymer with ethene 25213-02-9 99.5 % Contains: Stabilizers FIRST AID MEASURES General advice Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. <th></th> <th></th> <th></th>				
3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Chemical name CAS-No. Weight % 1-Hexene.polymer with ethene 25213-02-9 99.5 % Contains: Stabilizers A FIRST AID MEASURES General advice Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention. If discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention. If discomfort persists. : In ca	Version 1.2 Revision Date	10/01/2019 Print Date 01	/05/2022 SDS No.: BE1736	
3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Chemical name CAS-No. Weight % 1-Hexene.polymer with ethene 25213-02-9 99.5 % Contains: Stabilizers A FIRST AID MEASURES General advice Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention. If discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention. If discomfort persists. : In ca				
Mixtures Components Chemical name CAS-No. Weight % 1-Hexene,polymer with ethene 25213-02-9 99.5 % Contains: Stabilizers FIRST AID MEASURES General advice Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If mothen material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is deal or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	No additional information a	vailable.		
Components Chemical name CAS-No. Weight % 1-Hexene,polymer with ethene 25213-02-9 > 99.5 % Contains: Stabilizers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is deal or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.		ON INGREDIENTS		
Chemical name CAS-No. Weight % 1-Hexene,polymer with ethene 25213-02-9 > 99.5 % Contains: Stabilizers Contains: Stabilizers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is deer or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and see medical attention if dushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.				
1-Hexene, polymer with ethene 25213-02-9 > 99.5 % Contains: Stabilizers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	-			
Contains: Stabilizers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	Chemical name	CAS-No.	<u>Weight %</u>	
4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is deel or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	1-Hexene,polymer with ethene	25213-02-9	> 99.5 %	
General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	Contains: Stabilizers			
General advice : Take proper precautions to ensure your own health and safe before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.				
If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be general during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is dee or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	4. FIRST AID MEASURES			
 In case of skin contact If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polym Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is deel or extensive. In case of eye contact Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. 	General advice			
 In case of eye contact In case of eye contact Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. 	If inhaled	In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary		
 medical attention if discomfort persists. In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. 	In case of skin contact	large amounts of water to Do not attempt to peel po skin. Obtain immediate emerge	o cool the affected tissue and polymer. Iymer from skin as this will remove the	
Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	In case of eye contact			
If swallowed : Adverse health effects due to ingestion are not anticipated.		Continuously flush eye(s) minutes. Beyond flushing, DO NOT adherent to the eye(s).	with cool running water for at least 15	
	If swallowed	: Adverse health effects du	e to ingestion are not anticipated.	
2 / 13		2 / 13		
2710		2710		

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LB560201	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE17:
Notes to physician Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbor (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 13

hongrunplastics.com
lyondellbase
Gen. Variant: SDS_US_GH
10/01/2019 Print Date 01/05/2022 SDS No.: BE1
URES
: Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth
surface.
Equip emergency responders with proper personal protective
equipment (PPE) Avoid generating dust.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces
with compressed air). Potential combustible dust hazard.
Polymer particles create slipping hazard on hard smooth
surfaces.
: Do not flush into surface water or sanitary sewer system.
: On land, sweep/shovel into suitable disposal containers or
vacuum using equipment which avoids ignition risk.
On water, material is insoluble; collect and contain as any solid.
All recovered material should be packaged, labeled,
transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
engineering practices. Reclaim where possible.
9
: Material is in a pellet form. If converted to small particles during further processing,
handling, or by other means, may form combustible dust
concentrations in air. Avoid dust accumulation in enclosed space.
Use dust collection systems designed per NFPA 654 to avoid
dust accumulation.
Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion
hazard.
Static discharge (spark), or other ignition sources, in high dua environments may ignite the dust and result in a dust
explosion
Electrostatic charge may build during conveying or handling.
Faunment handling polymer should be conductive and
Equipment handling polymer should be conductive and grounded (earthed) and bonded.

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Petrothene LB560201	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Dat	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE1736
Fire-fighting class Conditions for safe storage	Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
-	
Requirements for storage areas and containers	 Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	: See Section 1.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	

		hongrun	plastics.com		
SAFETY DATA	SHEET	<u>.</u>		lyond	ellbasell
Petrothene LE	3560201			Gen. Variant	: SDS_US_GHS
Version 1.2 R	evision Date 10	/01/2019	Print Date 01/	/05/2022	SDS No.: BE1736
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LB560201	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE173
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
. PHYSICAL AND CHEMICAL P Appearance	: Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hongrunplastics.com			
AFETY DATA SHEET	lyondellbase			
etrothene LB560201	Gen. Variant: SDS_US_G			
ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE			
Partition coefficient: n- octanol/water Viscosity, dynamic Relative vapor density	 No Data Available. Not applicable. Not applicable. 			
Evaporation rate	: Not applicable.			
Explosive properties	: No Data Available.			
Other Information	: No additional information available.			
STABILITY AND REACTIVITY	<i>,</i>			
Reactivity	: No known reactivity hazards.			
Chemical stability	: Stable under normal conditions.			
Hazardous reactions	: Will not occur.			
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks open flame.			
Materials to avoid	: Material may be softened by some hydrocarbons.			
Hazardous decomposition	: Not expected to decompose under normal conditions.			
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.			
TOXICOLOGICAL INFORMAT	ΓΙΟΝ			
Acute oral toxicity	: Not classified			
Acute inhalation toxicity	: Not classified			
Acute dermal toxicity	: Not classified			
Skin corrosion/irritation	: Not a skin irritant.			
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.			
	8 / 13			

	hongrunplas	tics.com		
SAFETY DATA SHEET			lyonde	llbasell
Petrothene LB560201			Gen. Variant:	SDS_US_GHS
Version 1.2 Revision Date 1	0/01/2019 Pr	int Date 01/05/20	22 S	DS No.: BE1736
Respiratory or skin sensitization	: Not classified			
Chronic toxicity				
Carcinogenicity	: Not classified			
	Not classified Not listed by IA	RC, NTP, OSHA	or EPA.	
Germ cell mutagenicity	: Not classified			
Reproductive toxicity				
Effects on fertility / Effects on or via lactation	: Not classified			
Effects on Development	: Not classified			
Target Organ Systemic Toxicant - Single exposure	: The substance organ toxicant,	or mixture is not a single exposure.	classified as sp	becific target
Target Organ Systemic Toxicant - Repeated exposure		or mixture is not repeated exposu		becific target
Aspiration hazard	: Not applicable.			
12. Ecological information				
Ecotoxicology Assessment				
Short-term (acute) aquatic hazard	: Not classified			
Long-term (chronic) aquatic hazard	: Not classified			
Persistence and degradability				
Biodegradability	: Not expected to		е.	
	9 / 13			

	hongrunplastics.com			
SAFETY DATA SHEET	lyondellbasell			
Petrothene LB560201	Gen. Variant: SDS_US_GHS			
Version 1.2 Revision Date 10	0/01/2019 Print Date 01/05/2022 SDS No.: BE1736			
Bioaccumulative potential				
	: This material is not expected to bioaccumulate.			
Mobility in soil				
	: no data available			
Other adverse effects				
Environmental fate and pathways	: This material is not volatile and insoluble in water.			
Other information				
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 			
13. Disposal considerations Waste treatment methods				
Product	 All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible. This material is classified as a Non-hazardous Material by RCRA. 			
14. TRANSPORT INFORMATION				
Not regulated for transport				
	10 / 13			

SAFETY DATA SHEET

Petrothene LB560201

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS US GHS

lyondellbase

SDS No.: BE1736

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

Know Act.

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Inventory	Status Description
AICS	Compliant
•	· ·
11 / 1	3
	-

SAFETY DATA SHEET

Petrothene LB560201

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1736

lyondellbasel

Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification	: Health Hazard: 0 Flammability: 1 Physical hazards: 0	0 1 0				
NFPA Classification	: Health Hazard: 0 Fire Hazard: 1 Instability: 0					
Further information						
HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)						
	12 / 13					

(+)	188 '	1699	6168
hon	grunp	lastic	s.com

SAFETY DATA SHEET

Petrothene LB560201

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1736

ondellbase

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet