# (+) 188 1699 6168

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LR732001	Gen. Variant: SDS_US_GH
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE7
IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name CAS Number: Chemical characterization Chemical name Synonyms	<ul> <li>Petrothene LR732001</li> <li>25213-02-9</li> <li>Polyethylene copolymer</li> <li>1-Hexene,polymer with ethene</li> <li>Ethylene-1-hexene copolymer, Ethylene-Hexene Copolymer</li> </ul>
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 3 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583	Customer Service 888 777-0232 product.safety@lyb.com
Emergency telephone numb EQUISTAR 800-245-4532	
E-mail address Responsible/issuing person	: product.safety@lyb.com
HAZARDS IDENTIFICATION	
<b>GHS Classification</b>	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	

	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbasell
Petrothene LR732001		Gen. Variant: SDS_US_GHS
/ersion 1.2 Revision Date	10/01/2019 Print Date 01/	05/2022 SDS No.: BE759
No additional information av	ailable.	
COMPOSITION/INFORMATION	ON INGREDIENTS	
ixtures		
Components		
Chemical name	CAS-No.	<u>Weight %</u>
1-Hexene,polymer with ethene	25213-02-9	> 99.5 %
Contains: Stabilizers		
FIRST AID MEASURES		
General advice	: Take proper precautions t before attempting rescue	o ensure your own health and safety and providing first aid.
If inhaled	-	ir. If signs/symptoms continue, get
	medical attention. In case of excessive inhal	ation of fumes that may be generated
		erial, move the person to fresh air.
	Keep person warm, if nec	essary give Cardio-Pulmonary
	Resuscitation (CPR)	
In case of skin contact	: If molten material contacts	s the skin, immediately flush with
	large amounts of water to	cool the affected tissue and polymer.
	skin.	ymer from skin as this will remove the
	Obtain immediate emerge or extensive.	ncy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with	n water for several minutes and seek
	medical attention if discon	nfort persists.
	: In case of eye contact with	
	Continuously flush eye(s) minutes.	with cool running water for at least 15
	Beyond flushing, DO NOT adherent to the eye(s).	attempt to remove the material
	Immediately seek medical	attention.
If swallowed	· Adverse health effects du	e to ingestion are not anticipated.
ii Swallowed		
	2 / 13	
	2710	

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LR732001	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE7
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE:
	Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbor (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> </ul>
	Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved ir fire.
	fire. Cool storage containers with large volumes of water even aft fire is out.
	3 / 13

	hongrunplastics.com
AFETY DATA SHEET	lyondellbase
Petrothene LR732001	Gen. Variant: SDS_US_GH
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE
ACCIDENTAL RELEASE MEAS	URES
Personal precautions	<ul> <li>Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface.</li> <li>Equip emergency responders with proper personal protective equipment (PPE)</li> <li>Avoid generating dust.</li> <li>Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).</li> <li>Potential combustible dust hazard.</li> <li>Polymer particles create slipping hazard on hard smooth surfaces.</li> </ul>
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	<ul> <li>On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.</li> <li>All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.</li> </ul>
Handling and storage Precautions for safe handlin Advice on safe handling	<ul> <li>g</li> <li>Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion</li> </ul>
	hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.
	4 / 13

		lyondellbase
		1 <sup>°</sup> 1 111
		Gen. Variant: SDS_US_G
/01/2019	Print Date 01	1/05/2022 SDS No.: BE
should be g All electrica codes and combustible After handli water. When bring may develop section 10. Refer to NF Dust Explos	rounded and to a equipment sh regulatory requ e dusts. ng, always was ing the materia o may condens PA 654, Stand sions from the	in the transfer of this material bonded. hould conform to applicable electric uirements for areas handling ash hands thoroughly with soap and al to processing temperatures vapous in the exhaust ventilation. See dard for the Prevention of Fire and Manufacturing, Processing, and Particulate Solids, for safe handling
Polymer wil	l burn but does	s not easily ignite.
cluding any	incompatibili	ties
Use good h and handlin should be u Store away oxidizing ag Keep conta	ousekeeping p g. Process end ised to avoid e from excessiv gents. iner closed to	practices during storage, transferrin aclosures and adequate ventilation excessive dust accumulation. we heat and away from strong prevent contamination. t the build up of electrostatic charg
	Metal conta should be g All electrica codes and combustible After handli water. When bring may develop section 10. Refer to NF Dust Explos Handling of Polymer will <b>cluding any</b> Store in a d Use good h and handlin should be u Store away oxidizing ag Keep conta Take measu	Metal containers involved should be grounded and All electrical equipment s codes and regulatory req combustible dusts. After handling, always wa water. When bringing the materi may develop may conder section 10. Refer to NFPA 654, Stan Dust Explosions from the Handling of Combustible Polymer will burn but doe <b>cluding any incompatibili</b> Store in a dry location. Use good housekeeping and handling. Process er should be used to avoid of Store away from excessiv oxidizing agents. Keep container closed to

## Control parameters

#### Ingredients with workplace control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

5 / 13

		hongrun	plastics.com		
SAFETY DATA	SHEET	<u>.</u>	———————————————————————————————————————	lvond	ellbasell
<b>Petrothene</b>	.R732001			Gen. Variant	: SDS_US_GHS
Version 1.2	Revision Date 10	)/01/2019	Print Date 01	/05/2022	SDS No.: BE759
Materials that can	1	TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	15 mg/m3	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust			- / -		
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

#### Exposure controls

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
AFETY DATA SHEET	lyondellbase
etrothene LR732001	Gen. Variant: SDS_US_GHS
ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE7
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>
PHYSICAL AND CHEMICAL P	ROPERTIES : Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dua varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hongrunplastics.com
AFETY DATA SHEET	lyondellbase
etrothene LR732001	Gen. Variant: SDS_US_G
ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	,
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Petrothene LR732001	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 1	0/01/2019 Print Date 01/05/2022 SDS No.: BE759
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	Not classified Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
Ecotoxicology Assessment	
hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Petrothene LR732001	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 10	D/01/2019 Print Date 01/05/2022 SDS No.: BE759
Bioaccumulative potential	
	This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	no data available
Other adverse effects	
Environmental fate and pathways	This material is not volatile and insoluble in water.
Other information	
Additional ecological information	<ul> <li>Ecotoxicity is expected to be minimal based on the low water solubility of polymers.</li> <li>No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.</li> </ul>
13. Disposal considerations Waste treatment methods	
Product	<ul> <li>All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.</li> <li>This material is classified as a Non-hazardous Material by RCRA.</li> </ul>
14. TRANSPORT INFORMATION	
Not regulated for transport	
	10 / 13

## SAFETY DATA SHEET

## Petrothene LR732001

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS US GHS

....

lyondellbase

SDS No.: BE759

#### **15. REGULATORY INFORMATION**

#### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

#### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

#### **SARA 313**

Know Act.

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description	
Australia	AICS	Compliant	
	•	· ·	
	11 / 1	3	

## SAFETY DATA SHEET

## Petrothene LR732001

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE759

lyondellbasel

Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

#### 16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification	: Health Hazard: 0 Flammability: 1 Physical hazards: 0	0 1 0				
NFPA Classification	: Health Hazard: 0 Fire Hazard: 1 Instability: 0					
Further information						
HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)						
	12 / 13					

## SAFETY DATA SHEET

## Petrothene LR732001

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE759

ш

lyondellbase

....

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

#### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

#### Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

#### End of Material Safety Data Sheet