(+) 188 1699 6168

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbas
Petrothene LR734046	Gen. Variant: SDS_US_G
Version 1.1 Revision Date	
	10/01/2019 Fillt Date 01/03/2022 3D3 No BET
1. IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name CAS Number:	: Petrothene LR734046 : 25213-02-9
Chemical characterization	: Polyethylene copolymer
Chemical name	: 1-Hexene,polymer with ethene
Synonyms	: Ethylene-1-hexene copolymer, Ethylene-Hexene Copolyme
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body
	Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP	Customer Service 888 777-0232
LyondellBasell Tower, Suite 3	
1221 McKinney St.	
P.O. Box 2583	
Houston Texas 77252-2583	
Emergency telephone numb EQUISTAR 800-245-4532	<u>er</u>
E-mail address Responsible/issuing person	: product.safety@lyb.com
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
Hazaru Statements	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 13

	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbasell
Petrothene LR734046		Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019 Print Date 01/	/05/2022 SDS No.: BE16422
No additional information av	ailable.	
3. COMPOSITION/INFORMATION	ON INGREDIENTS	
Mixtures		
Components	212.1	
Chemical name	CAS-No.	<u>Weight %</u>
1-Hexene, polymer with ethene	25213-02-9	98.0 - 100.0 %
Contains: Stabilizers		
4. FIRST AID MEASURES		
General advice	: Take proper precautions t before attempting rescue	o ensure your own health and safety and providing first aid.
If inhaled	medical attention. In case of excessive inhal during heating of this mate Obtain medical attention.	ir. If signs/symptoms continue, get ation of fumes that may be generated erial, move the person to fresh air. essary give Cardio-Pulmonary
In case of skin contact	 If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. 	
In case of eye contact	: Flush eyes thoroughly with medical attention if discon	h water for several minutes and seek nfort persists.
	minutes.	with cool running water for at least 15 attempt to remove the material
If swallowed	: Adverse health effects due	e to ingestion are not anticipated.
	2 / 13	
	2710	

	hongrunplastics.com	
SAFETY DATA SHEET	lyondellbase	
Petrothene LR734046	Gen. Variant: SDS_US_GHS	
Version 1.1 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE1642	
Notes to physician Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.	
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.	
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.	
5. FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.	
	: LARGE FIRES: Use water spray hose nozzles from a safe location.	
Unsuitable extinguishing media	: None known.	
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke). 	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.	
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out. 	
	3 / 13	

hongrunplastics.com
IYUIUEIIDASE
Gen. Variant: SDS US GH
10/01/2019 Print Date 01/05/2022 SDS No.: BE16
URES
: Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth
surface.
Equip emergency responders with proper personal protective
equipment (PPE) Avoid generating dust.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces
with compressed air). Potential combustible dust hazard.
Polymer particles create slipping hazard on hard smooth
surfaces.
: Do not flush into surface water or sanitary sewer system.
. Do not nush into sunace water of samilary sewer system.
: On land, sweep/shovel into suitable disposal containers or
vacuum using equipment which avoids ignition risk.
On water, material is insoluble; collect and contain as any solid.
All recovered material should be packaged, labeled,
transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
engineering practices. Reclaim where possible.
g
: Material is in a pellet form.
If converted to small particles during further processing,
handling, or by other means, may form combustible dust concentrations in air.
Avoid dust accumulation in enclosed space.
Use dust collection systems designed per NFPA 654 to avoid dust accumulation.
Avoid generating dust; fine dust suspended in air and in the
presence of an ignition source is a potential dust explosion
hazard. Static discharge (spark), or other ignition sources, in high du
environments may ignite the dust and result in a dust
explosion Electrostatic charge may build during conveying or handling.
Equipment handling polymer should be conductive and
grounded (earthed) and bonded.
4 / 13

	hongrunplastics.com	
SAFETY DATA SHEET		lyondellbasell
Petrothene LR734046		Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date 10	/01/2019 Print Date 0	1/05/2022 SDS No.: BE16422
	should be grounded and All electrical equipment s codes and regulatory required combustible dusts. After handling, always wat water. When bringing the materi may develop may condent section 10. Refer to NFPA 654, Stand Dust Explosions from the	in the transfer of this material bonded. hould conform to applicable electric uirements for areas handling ash hands thoroughly with soap and al to processing temperatures vapors use in the exhaust ventilation. See dard for the Prevention of Fire and Manufacturing, Processing, and Particulate Solids, for safe handling.
Fire-fighting class :	Polymer will burn but doe	s not easily ignite.
Conditions for safe storage, inc	cluding any incompatibili	ties
Requirements for storage : areas and containers	and handling. Process en should be used to avoid e Store away from excessiv oxidizing agents. Keep container closed to	practices during storage, transferring iclosures and adequate ventilation excessive dust accumulation. We heat and away from strong prevent contamination. t the build up of electrostatic charge.
Specific end use(s)	See Section 1.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
·	•				

5 / 13

	hongrun	plastics.com		
SAFETY DATA SHEET			lyond	ellbasell
Petrothene LR734046				: SDS_US_GHS
Version 1.1 Revision Date 1	0/01/2019	Print Date 01	/05/2022 S	DS No.: BE16422
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust Materials that can	TWA	3 mg/m3 respirable 15 mg/m3	US (ACGIH) 2005 US (OSHA)	
be formed when handling this product: Non- specified (inert or nuisance) dust		total dust	2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasel
Petrothene LR734046	
Version 1.1 Revision Dat	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE1642
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL F	rOPERTIES : Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hongrunplastics.com		
AFETY DATA SHEET	lyondellbasi		
etrothene LR734046	Gen. Variant: SDS_US_GI		
rsion 1.1 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE16		
Partition coefficient: n- octanol/water Viscosity, dynamic Relative vapor density Evaporation rate Explosive properties Other Information	 No Data Available. Not applicable. Not applicable. Not applicable. No Data Available. No additional information available. 		
Other Information	: No additional information available.		
STABILITY AND REACTIVITY			
Reactivity	: No known reactivity hazards.		
Chemical stability	: Stable under normal conditions.		
Hazardous reactions	: Will not occur.		
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.		
Materials to avoid	: Material may be softened by some hydrocarbons.		
Hazardous decomposition	: Not expected to decompose under normal conditions.		
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.		
TOXICOLOGICAL INFORMAT	ΓΙΟΝ		
Acute oral toxicity	: Not classified		
Acute inhalation toxicity	: Not classified		
Acute dermal toxicity	: Not classified		
Skin corrosion/irritation	: Not a skin irritant.		
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.		
	8 / 13		

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LR734046	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE164
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
2. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	hongrunplastics.com		
SAFETY DATA SHEET		lyondellbasell	
Petrothene LR734046		Gen. Variant: SDS_US_GHS	
Version 1.1 Revision Date 10	0/01/2019 Print Date 01/05	5/2022 SDS No.: BE16422	
Bioaccumulative potential			
Bioaccumulation	This material is not expected	to bioaccumulate.	
Mobility in soil			
Mobility	no data available		
Other adverse effects			
Environmental fate and pathways	This material is not volatile ar	nd insoluble in water.	
Other information			
Additional ecological information	: Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.		
13. Disposal considerations Waste treatment methods			
Product		or reclaimed in conformance with ns and in conformance with good	
	This material is classified as a RCRA.	a Non-hazardous Material by	
14. TRANSPORT INFORMATION			
Not regulated for transport			
15. REGULATORY INFORMATION			
	10 / 13		
	107 10		

SAFETY DATA SHEET

Petrothene LR734046

Version 1.1

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE16422

Iyondellbase

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

557-05-1 Zinc Stearate

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description		
Australia	AICS	Compliant		
Canada	DSL	Compliant		
China	IECSC	Compliant		
11 / 13				

SAFETY DATA SHEET

Petrothene LR734046

Version 1.1 Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE16422

	Europe	REACH	See REACH Compliance Statement			
	Japan	ENCS	Compliant			
-	Korea	KECI	Compliant			
-	New Zealand	NZIOC	Compliant			
-	Philippines	PICCS	Compliant			
-	United States of America	TSCA	Compliant			
-	Taiwan	TCSCA	Compliant			
REACh status If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006) Contact product.safety@lyb.com for additional global inventory information.						
16. OTHER INFORMATION Material safety datasheet sections which have been updated: Revised Section(s): 15 16						
ым	IS Classification	Health Hazard: 0				
	I	Flammability: 1 Physical hazards:	0 1 0			
NFF	I	Health Hazard: 0 Fire Hazard: 1 Instability: 0				
Further information						
HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)						
	12 / 13					

SAFETY DATA SHEET

Petrothene LR734046

Version 1.1

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE16422

iyondellbase

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet