<section-header><ul> <li>SAFETY DATA SHEET</li> <li>Pertorthene LT606932</li> <li>Varsion 1.2 Revision Date 10/01/2019 Print Date 01/05/202</li> <li>SDS No: BE1888</li> <li>CLENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING</li> <li>Trade name : Petrothene LT606932</li> <li>CAS Number: : 9002-884</li> <li>Chemical name : Petrothene LT606932</li> <li>Chemical name : Polyethylene : Other conversion process.</li> <li>Prohibited uses : FDA Class III medical devices; European class III medical devices: Health Canada class IV Medical Devices: Userstaining medical applications: Nothing Str. Users Str. Str. Str. Str. Str. Str. Str. Str.</li></ul></section-header>		hongrunplastics.com
Version 1.2       Revision Date 10/01/2019       Print Date 01/05/2022       SDS No.: BE1892         1. JDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING       Trade name       : 9002-88-4         CAS Number:       : 9002-88-4       Othermical characterization       : 9002-88-4         Chemical characterization       : 9002-88-4       Othermical characterization       : 9002-88-4         Chemical name       :: 9002-88-4       Othermical characterization       :: 9002-88-4         Identified uses       :: Ethene, homopolymer, PE       Identified uses       :: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications         VonodelBasell Tower, Suite 300       :: FDA Class III medical devices; Buropean class III medical devices; Applications involving permanent implantation into the body; Life-sustaining medical applications         P.O. Box 2653       Company Address         Houston Texas 77252-2583       :: Product.safety@lyb.com         P.AZARDS IDENTIFICATION       GHS Classification         Combustible dust       :: Maranig         Label elements       : If small particles are generated during further processing, handling or by other means, may form combustible dust         Label elements       : If small particles are generated during further processing, concentrations in air.	SAFETY DATA SHEET	lyondellbasel
Version 1.2       Revision Date 10/01/2019       Print Date 01/05/2022       SDS No.: BE1889         IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING       Trade name       : 9002-88-4         Characterization       : 9002-88-4       Company Address         Chemical characterization       : Polyethylene       Synonyms         Synonyms       :: Ethene, homopolymer       Chemical characterization         Or other conversion process.       : Ethene, homopolymer       Chemical characterization         Prohibited uses       :: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications         Lyondellibasell Tower, Suite 300 1221 McKinney St.       Company Telephone         P.O. Box 2683       Customer Service 888 777-0232         Houston Texas 77252-2583       product.safety@lyb.com         Emergency telephone number       Eou/STAR 800-245-4532         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : fmail particles are generated during further processing, handling or by other means, may form combustible dust         Label elements       : ff smail particles are generated during further processing, handling or by other means, may form combustible dust         Label elements       : ff smail particles are generated during further	Petrothene LT606932	Gen. Variant: SDS_US_GHS
Trade name       Hertorial characterization       9002-88-4         Chemical name       Polyethylene Homopolymer         Synonyms       Hertorial aname         Synonyms       Hertorial characterization         Synonyms       Hertorial aname         Synonyms       Hertorial aname         Synonyms       Hertorial aname         Synonyms       Hertorial aname         Generation       Hertorial aname         Hentorial aname       Hertorial aname         Synonyms       Hertorial aname         Generation       Manufacture of plastic articles by injection molding, extrusion         Generation       Harufacture of plastic articles by injection molding, extrusion         Generation       Hordical Devices; European class III medical         Generation       Hertorial aname         Bayer       European class IV Medical Devices;         Eropany Address       Company Telephone         Equistar Chemicals, LP       LyondellBasell Tower, Suite 300         L221 McKinney St.       P.O. Box 2583         Houston Texas 77252-2583       Company Telephone         Energency telephone number       EQUISTAR 800-245-4532         E-mail address       ir product.safety@lyb.com         Cherophyscience       Herophysciente		10/01/2019 Print Date 01/05/2022 SDS No.: BE1898
Trade name       Herbitane Polysthylene Homopolymer         CAS Number:       9002-88-4         Chemical characterization       Polysthylene Homopolymer         Synonyms       Herbitane Homopolymer, PE         Identified uses       Hanufacture of plastic articles by injection molding, extrusion         Manufacture of plastic articles solving permanent implantation into the body;         Hieronal Mathematical Structure       FDA Class III medical devices; European class III medical         Applications involving permanent implantation into the body;       Life-sustaining medical applications         Mathematical Structure       Company Address         Equistar Chemicals, LP       Customer Service 888 777-0232         LyondellBasell Tower, Suite 300       Product.safety@lyb.com         1221 McKinney St.       Product.safety@lyb.com         Energency telephone number       EQUISTAR 800-245-4532         E-mail address       : product.safety@lyb.com         Responsible/issuing person       :         2. HAZARDS IDENTIFICATION       Combustible dust         Label elements       : fi small particles are generated during further processing, handling or by other means, may form combustible dust         Label elements       : fi small particles are generated during further processing, handling or by other means, may form combustible dust         Hazard Statements       : fi	I. IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
CAS Number: :: 9002-88-4 Chemical characterization :: Polyethylene Homopolymer Chemical name :: Polyethylene Homopolymer, PE Identified uses :: Manufacture of plastic articles by injection molding, extrusion or other conversion process. Prohibited uses :: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications <b>Company Address</b> Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2563 Houston Texas 77252-2583 <b>Emergency telephone number</b> EQUISTAR 800-246-44532 E-mail address :: product.safety@lyb.com Responsible/issuing person <b>2. HAZARDS IDENTIFICATION</b> <b>GHS Classification</b> Combustible dust <b>Label elements</b> Signal word :: Warning Hazard Statements Comcentrations in air.		
Chemical characterization       Polyethylene Homopolymer         Chemical name       Polyethylene         Synonyms       ::         Identified uses       ::         Manufacture of plastic articles by injection molding, extrusion or other conversion process.         Prohibited uses       ::         Company Address       ::         Equistar Chemicals, LP       ::         LyondellBasell Tower, Suite 300       ::         1221 McKinney St.       :         P.O. Box 2583       ::         Houston Texas 77252-2583       ::         Product.safety@lyb.com <td< th=""><th></th><th></th></td<>		
Synonyms       Ethene, homopolymer, PE         Identified uses       Manufacture of plastic articles by injection molding, extrusion or other conversion process.         Prohibited uses       FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications         Company Address       Equistar Chemicals, LP         LyondellBasell Tower, Suite 300       The Company Telephone         Customer Service 888 777-0232       product.safety@lyb.com         P.O. Box 2583       Energency telephone number         EQUISTAR 800-245-4532       Energency telephone number         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         Chassification       Combustible dust         Label elements       : gignal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handing or by other means, may form combustible dust concentrations in air.         Other hazards       : Mazards		: Polyethylene Homopolymer
Identified uses <ul> <li>Manufacture of plastic articles by injection molding, extrusion or other conversion process.</li> </ul> <li>Prohibited uses</li> <li>FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications</li> <li>Company Address</li> <li>Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583</li> <li>Houston Texas 77252-2583</li> <li>Emergency telephone number EQUISTAR 800-245-4532</li> <li>E-mail address : product.safety@lyb.com</li> <li>Responsible/issuing person</li> <li>Product.safety@lyb.com</li> <li>Combustible dust</li> <li>Label elements</li> <li>Signal word : Warning</li> <li>Hazard Statements : f small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.</li> <li>Other hazards</li>		
r other conversion process. The second secon	Synonyms	: Ethene, nomopolymer, PE
devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person E-HAZARDS IDENTIFICATION GHS Classification Combustible dust Label elements Signal word : Warning Hazard Statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.	Identified uses	
Applications involving permanent implantation into the body; Life-sustaining medical applications          Company Address       Company Telephone         Equistar Chemicals, LP       Development         LyondellBasell Tower, Suite 300       Development         1221 McKinney St.       P.O. Box 2583         Houston Texas 77252-2583       Company Telephone         Equistar Chemicals, LP       Development         LyondellBasell Tower, Suite 300       Development         1221 McKinney St.       P.O. Box 2583         Houston Texas 77252-2583       Company Telephone         Equistar Anamoter       Customer Service 888 777-0232         product.safety@lyb.com       Product.safety@lyb.com         Responsible/issuing person       product.safety@lyb.com         P. HAZARDS IDENTIFICATION       GHS Classification         Combustible dust       Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       Development	Prohibited uses	
Life-sustaining medical applications         Company Address         Equistar Chemicals, LP         LyondellBasell Tower, Suite 300         121 McKinney St.         P.O. Box 2583         Houston Texas 77252-2583         Email address         Enail address         Enail address         Equisitive Value         PAZARDS IDENTIFICATION         GHS Classification         Combustible dust         Label elements         Signal word       Warning         Hazard Statements       If small particles are generated during further processing. handling or by other means, may form combustible dust         Concentrations in air.         Other hazards		
Equistar Chemicals, LP       Customer Service 888 777-0232         LyondellBasell Tower, Suite 300       product.safety@lyb.com         1221 McKinney St.       p.O. Box 2583         Houston Texas 77252-2583       Emergency telephone number         EQUISTAR 800-245-4532       Ermail address         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         Responsible/issuing person       : fismall particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : If small particles are generated during further processing, handling or by other means, may form combustible dust		
Equistar Chemicals, LP       Customer Service 888 777-0232         LyondellBasell Tower, Suite 300       product.safety@lyb.com         1221 McKinney St.       p.O. Box 2583         Houston Texas 77252-2583       Emergency telephone number         EQUISTAR 800-245-4532       Ermail address         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         BHS Classification       Combustible dust         Label elements       : if small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : If small particles are generated during further processing, handling or by other means, may form combustible dust		
Equistar Chemicals, LP       Customer Service 888 777-0232         LyondellBasell Tower, Suite 300       product.safety@lyb.com         1221 McKinney St.       P.O. Box 2583         Houston Texas 77252-2583       Emergency telephone number         EQUISTAR 800-245-4532       Ermail address         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         Responsible/issuing person       : final particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : If small particles are generated during further processing, handling or by other means, may form combustible dust		
LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification Combustible dust Label elements Signal word : Warning Hazard Statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.		
1221 McKinney St.         P.O. Box 2583         Houston Texas 77252-2583         Emergency telephone number         EQUISTAR 800-245-4532         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         HAZARDS IDENTIFICATION         GHS Classification         Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards	•	
P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person : HAZARDS IDENTIFICATION GHS Classification Combustible dust Label elements Signal word : Warning Hazard Statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.		bo product.salety@tyb.com
Emergency telephone number         EQUISTAR 800-245-4532         E-mail address       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         HAZARDS IDENTIFICATION         GHS Classification         Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.		
EQUISTAR 800-245-4532         E-mail address Responsible/issuing person       : product.safety@lyb.com         Responsible/issuing person       : product.safety@lyb.com         GHS Classification       : Combustible dust         Label elements       : Varning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : Varning	Houston Texas 77252-2583	
EQUISTAR 800-245-4532         E-mail address Responsible/issuing person       : product.safety@lyb.com         . HAZARDS IDENTIFICATION         GHS Classification         Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards		
Responsible/issuing person         HAZARDS IDENTIFICATION         GHS Classification         Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards		<u>er</u>
HAZARDS IDENTIFICATION     GHS Classification     Combustible dust     Label elements     Signal word : Warning     Hazard Statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.     Other hazards	E-mail address	: product.safety@lyb.com
GHS Classification         Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.	Responsible/issuing person	
GHS Classification         Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.		
Combustible dust         Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards	. HAZARDS IDENTIFICATION	
Label elements         Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards	GHS Classification	
Signal word       : Warning         Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards       : Varning	Combustible dust	
Hazard Statements       : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.         Other hazards	Label elements	
handling or by other means, may form combustible dust concentrations in air.	Signal word	: Warning
	Hazard Statements	handling or by other means, may form combustible dust
1 / 13	Other hazards	
		1 / 13

		(+) 188 1699 6168	
Petrothene LT606932         Gen. Variant: SDS_US_GHS           Version 1.2         Revision Date 10/01/2019         Print Date 01/05/2022         SDS No.: BE188           No additional information available.		hongrunplastics.com	
Version 1.2         Revision Date 10/01/2019         Print Date 01/05/2022         SDS No.: BE188           No additional information available.	SAFETY DATA SHEET	·····	lyondellbasell
No additional information available.         3. COMPOSITION/INFORMATION ON INGREDIENTS         Mixtures         Components <ul> <li>Chemical name</li> <li>CAS-No.</li> <li>Weight %</li> <li>Polyethylene</li> <li>9002-88-4</li> <li>99.5 %</li> </ul> Contains: Stabilizers <ul> <li>FIRST AID MEASURES</li> <li>General advice</li> <li>Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.</li> </ul> If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. In case of skin contact         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and see medical attention discomfort persists.         In case of eye contact       : Flush eyes thoroughly with cool running water for at least to minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.			Gen. Variant: SDS_US_GHS
3. COMPOSITION/INFORMATION ON INGREDIENTS         Mixtures         Components <ul> <li></li></ul>	Version 1.2 Revision Date	10/01/2019 Print Date 01/	/05/2022 SDS No.: BE1898
3. COMPOSITION/INFORMATION ON INGREDIENTS         Mixtures         Components <ul> <li></li></ul>			
Mixtures         Components <ul> <li>Chemical name</li> <li>CAS-No.</li> <li>Weight 36</li> <li>Polyethylene</li> <li>9002-88-4</li> <li>99.5 %</li> </ul> Contains: Stabilizers         A FIRST AID MEASURES         General advice       : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material. move the person to fresh air. Obtain medical attention. In case of skin contact         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove t skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists.         In case of eye contact       : Flush eyes contact with molten polymer: Continuously flush eye(s) with cool running water for at least to minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	No additional information a	vailable.	
Components <ul> <li>Chemical name</li> <li>CAS-No.</li> <li>Weight %</li> <li>90.5 %</li> </ul> <li>Contains: Stabilizers</li> <li> <ul> <li>AFRST AID MEASURES</li> <li>General advice</li> <li>Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.</li> <li>If inhaled</li> <li>Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)</li> </ul> </li> <li>In case of skin contact         <ul> <li>If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove th skin. Obtain incidecal attention if discomfort persists.</li> </ul> </li> <li>In case of eye contact         <ul> <li>Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.</li> <li>In case of eye contact with molten polymer:</li></ul></li>	3. COMPOSITION/INFORMATION	ON INGREDIENTS	
Chemical name         CAS-No.         Weight %           Polyethylene         9002-88-4         > 99.5 %           Contains: Stabilizers         Contains: Stabilizers           4. FIRST AID MEASURES         General advice         : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.           If inhaled         : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)           In case of skin contact         : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove t skin. Obtain immediate emergency medical attention if burn is deep or extensive.           In case of eye contact         : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists.           In case of eye contact         : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.           If swallowed         : Adverse health effects due to ingestion are not anticipated.	Mixtures		
Polyethylene       9002-88-4       > 99.5 %         Contains:       Stabilizers         A. FIRST AID MEASURES       General advice       : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove t skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists.         : In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	-		
Contains: Stabilizers         4. FIRST AID MEASURES         General advice       : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove t skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	Chemical name	CAS-No.	<u>Weight %</u>
4. FIRST AID MEASURES         General advice       : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         In case of eye contact       : Flush eyes thoroughly with cool running water for at least immutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	Polyethylene	9002-88-4	> 99.5 %
4. FIRST AID MEASURES         General advice       : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove t skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         In case of eye contact       : Flush eyes thoroughly with cool running water for at least is minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	Contains: Stabilizers		
General advice       : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove to skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.			
If inhaled       : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generate during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove to skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least to minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	4. FIRST AID MEASURES		
In case of skin contact       If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       :         In case of eye contact with molten polymer:       :         Continuously flush eye(s) with cool running water for at least the minutes.         Beyond flushing, DO NOT attempt to remove the material adheren	General advice		
In case of eye contact       Iarge amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove the skin.         In case of eye contact       Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         In case of eye contact       In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes.         Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.	If inhaled	medical attention. In case of excessive inhal during heating of this mate Obtain medical attention. Keep person warm, if nec	ation of fumes that may be generated erial, move the person to fresh air.
<ul> <li>medical attention if discomfort persists.</li> <li>In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.</li> <li>If swallowed : Adverse health effects due to ingestion are not anticipated.</li> </ul>	In case of skin contact	large amounts of water to Do not attempt to peel pol skin. Obtain immediate emerge	cool the affected tissue and polymer. ymer from skin as this will remove the
Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of eye contact		
		Continuously flush eye(s) minutes. Beyond flushing, DO NOT adherent to the eye(s).	with cool running water for at least 15 attempt to remove the material
2 / 13	If swallowed	: Adverse health effects due	e to ingestion are not anticipated.
		2 / 13	
		2710	

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LT606932	Gen. Variant: SDS_US_GHS
/ersion 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE18
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness
e y nipienie	the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbor (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved ir fire.</li> <li>Cool storage containers with large volumes of water even aft fire is out.</li> </ul>
	3 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LT606932	Gen. Variant: SDS_US_GF
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE1
ACCIDENTAL RELEASE MEAS	BURES
Personal precautions	<ul> <li>Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface.</li> <li>Equip emergency responders with proper personal protective equipment (PPE)</li> <li>Avoid generating dust.</li> <li>Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).</li> <li>Potential combustible dust hazard.</li> <li>Polymer particles create slipping hazard on hard smooth surfaces.</li> </ul>
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	<ul> <li>On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.</li> <li>All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wit applicable laws and regulations and in conformance with goo engineering practices. Reclaim where possible.</li> </ul>
Handling and storage Precautions for safe handlin Advice on safe handling	: Material is in a pellet form.
	<ul> <li>If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air.</li> <li>Avoid dust accumulation in enclosed space.</li> <li>Use dust collection systems designed per NFPA 654 to avoid dust accumulation.</li> <li>Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard.</li> <li>Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion</li> <li>Electrostatic charge may build during conveying or handling.</li> <li>Equipment handling polymer should be conductive and grounded (earthed) and bonded.</li> </ul>
	gioanada (dannea) ana benada

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbasell
Petrothene LT606932	Gen. Variant: SDS_US_GHS
	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE1898
	Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Fire-fighting class	: Polymer will burn but does not easily ignite.
Conditions for safe storage	, including any incompatibilities
Requirements for storage areas and containers	<ul> <li>Store in a dry location.</li> <li>Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation.</li> <li>Store away from excessive heat and away from strong oxidizing agents.</li> <li>Keep container closed to prevent contamination.</li> <li>Take measures to prevent the build up of electrostatic charge.</li> </ul>
Specific end use(s)	
	: See Section 1.
B. EXPOSURE CONTROLS/PERS	SONAL PROTECTION

# Control parameters

### Ingredients with workplace control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

5 / 13

		hongrun	plastics.com		
SAFETY DATA	SHEET			lyond	ellbasel
<b>Petrothene L</b>	T606932			Gen. Variant	: SDS_US_GHS
Version 1.2	Revision Date 10	)/01/2019	Print Date 01	/05/2022	SDS No.: BE1898
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust Materials that can		TWA	45 m m/m 2		
		IVVA	15 mg/m3 total dust	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non- specified (inert or					
nuisance) dust					
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when		IVVA	respirable	2005	
handling this			respirable	2000	
product: Non-					
specified (inert or					
nuisance) dust					
			1	1	1

Consult local authorities for acceptable exposure limits.

#### **Exposure controls**

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	hongrunplastics.com
SAFETY DATA SHEET	lyondellbase
Petrothene LT606932	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Dat	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE189
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>
. PHYSICAL AND CHEMICAL F Appearance	: Pellets.
Color	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	hongrunplastics.com
AFETY DATA SHEET	lyondellbase
etrothene LT606932	Gen. Variant: SDS_US_GH
ersion 1.2 Revision Date	e 10/01/2019 Print Date 01/05/2022 SDS No.: BE1
Partition coefficient: n- octanol/water Viscosity, dynamic Relative vapor density Evaporation rate	<ul> <li>No Data Available.</li> <li>Not applicable.</li> <li>Not applicable.</li> <li>Not applicable.</li> </ul>
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	r
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	hongrunp	lastics.com
SAFETY DATA SHEET		lyondellbasell
Petrothene LT606932		Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019	Print Date 01/05/2022 SDS No.: BE1898
Respiratory or skin sensitization	: Not classifie	ed
Chronic toxicity		
Carcinogenicity	: Not classifie	ed
	Not classifie Not listed b	ed y IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classifie	ed
Reproductive toxicity		
Effects on fertility / Effects on or via lactation	: Not classifie	ed
Effects on Development	: Not classifie	ed
Target Organ Systemic Toxicant - Single exposure		nce or mixture is not classified as specific target ant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure		ance or mixture is not classified as specific target cant, repeated exposure.
Aspiration hazard	: Not applical	ble.
12. Ecological information		
Ecotoxicology Assessment		
Short-term (acute) aquatic hazard	: Not classifie	
Long-term (chronic) aquatic hazard	: Not classifie	əd
Persistence and degradability		
Biodegradability		ed to be biodegradable.
	9	/ 13

	hongrunplastics.com		
SAFETY DATA SHEET	lyondellbasell		
Petrothene LT606932	Gen. Variant: SDS_US_GHS		
Version 1.2 Revision Date 1	0/01/2019 Print Date 01/05/2022 SDS No.: BE1898		
Bioaccumulative potential			
Bioaccumulation	: This material is not expected to bioaccumulate.		
Mobility in soil			
Mobility	: no data available		
Other adverse effects			
Environmental fate and pathways	: This material is not volatile and insoluble in water.		
Other information			
Additional ecological information	<ul> <li>Ecotoxicity is expected to be minimal based on the low water solubility of polymers.</li> <li>No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.</li> </ul>		
13. Disposal considerations Waste treatment methods			
Product	<ul> <li>All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.</li> <li>This material is classified as a Non-hazardous Material by RCRA.</li> </ul>		
14. TRANSPORT INFORMATION			
Not regulated for transport			
	10 / 13		

# SAFETY DATA SHEET

### Petrothene LT606932

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS US GHS

lyondellbase 

# SDS No.: BE1898

### **15. REGULATORY INFORMATION**

### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

#### **SARA 313**

Know Act.

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

557-05-1 Zinc Stearate

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

11 / 13

# SAFETY DATA SHEET

# Petrothene LT606932

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

lyondellbasel

Gen. Variant: SDS US GHS

SDS No.: BE1898

**Country/Region** Inventory Status Description AICS Australia Compliant Canada DSL Compliant China **IECSC** Compliant REACH Europe See REACH Compliance Statement ENCS Japan Compliant KECI Compliant Korea New Zealand NZIoC Compliant PICCS Compliant Philippines United States of America TSCA Compliant Taiwan TCSCA Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

\*This product contains one or more substances having volume restrictions. Contact Product Safety for additional information.

Contact product.safety@lyb.com for additional global inventory information.

### **16. OTHER INFORMATION**

#### Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification	: Health Hazard: 0 Flammability: 1 Physical hazards: 0	0 1 0
NFPA Classification	: Health Hazard: 0 Fire Hazard: 1 Instability: 0	
	12 / 13	

# SAFETY DATA SHEET

### Petrothene LT606932

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE1898

lyondellbase

### **Further information**

HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

#### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

#### Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

### End of Material Safety Data Sheet