	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET according to GB/T 16483-2008, GB/	T 17519-2013	lyondellbasell
Metocene HM2015		Gen. Variant: SDS_CN
Version 1.1 Revision Date 2	019-09-28 Print Date 20	022-01-04 SDS No.: BE8357
1. IDENTIFICATION OF THE SUBST	ANCE/MIXTURE AND OF TH	E COMPANY/UNDERTAKING
Trade name:CAS Number::Chemical characterization:Chemical name:Synonyms:	Metocene HM2015 9003-07-0 Polypropylene Homopolyme Polypropylene 1-Propene, homopolymer, F	
Identified uses :	Manufacture of plastic article or other conversion process	es by injection molding, extrusion
Prohibited uses :	devices; Health Canada clas	anent implantation into the body;
<u>Company Address</u> Basell Asia Pacific Ltd. 32/F, Dorset House Taikoo Place 979 King's Road Quarry Bay, Hong Kong	<u>Company</u> Product S Switchboa	
E-mail address Responsible/issuing person	product.safety@lyb.com	
2. HAZARDS IDENTIFICATION		
Emergency Overview		
If small particles are generate combustible dust concentration At process temperatures irrita Molten polymer may cause th Slipping hazard if spilled on h The material can accumulate	ns in air. ting fumes may be produced. ermal burns. ard smooth walking surface.	andling or by other means, may form a source of ignition.
GHS-Classification		
Not a hazardous substance o	r mixture according to the Glo	bally Harmonized System (GHS).
GHS-Labeling		
Not a hazardous substance o	r mixture according to the Glo	bally Harmonized System (GHS).

	hongrunplastics.c			
FETY DATA SHEET cording to GB/T 16483-200	8, GB/T 17519-2013		ndellbase	
etocene HM2015			ariant: SDS_CN	
rsion 1.1 Revision	Date 2019-09-28 Print Da	te 2022-01-04	SDS No.: BE8	
Physical-chemical, Heal	th, Environmental Hazard Des	cription		
Health hazards				
Eyes:	Mechanical irritation	is possible.		
Ingestion:	Ingestion not a likely	route of exposure.		
Inhalation:	in the nose and throa polymer dust typicall they are reasonably	Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. "Nuisance dust" such as polymer dust typically exhibit no significant health effect when they are reasonably controlled. Exposure to high concentrations of dust may cause slight irritation by mechanical action.		
Skin:	Molten polymer may	cause thermal burns		
Other hazards No additional informatio				
No additional information				
No additional information COMPOSITION/INFORMATIon Estances	ION ON INGREDIENTS	Weight %	Component	
No additional information COMPOSITION/INFORMAT Distances Components	ION ON INGREDIENTS	<u>Weight %</u> > 99.5 %	Component Type A	
No additional information COMPOSITION/INFORMATION Estances Components Chemical name	ION ON INGREDIENTS CAS-No. EC-No.		Туре	
No additional information COMPOSITION/INFORMATION Stances Components Chemical name Polypropylene Contains: Stabilizers	ION ON INGREDIENTS CAS-No. EC-No.		Туре	
No additional information COMPOSITION/INFORMATION Estances Components Chemical name Polypropylene	ION ON INGREDIENTS CAS-No. EC-No.		Туре	
No additional information COMPOSITION/INFORMATION Stances Components Chemical name Polypropylene Contains: Stabilizers Key:	ION ON INGREDIENTS CAS-No. EC-No.		Туре	
No additional information COMPOSITION/INFORMATION Stances Components Chemical name Polypropylene Contains: Stabilizers Key:	ION ON INGREDIENTS CAS-No. EC-No.		Туре	
No additional information COMPOSITION/INFORMATION Estances Components Chemical name Polypropylene Contains: Stabilizers Key: (A) Substance	ION ON INGREDIENTS CAS-No. EC-No.	> 99.5 %	n health and safety	

	(+) 188 1699 6168	
	hongrunplastics.com	
SAFETY DATA SHEET according to GB/T 16483-2008, GE	B/T 17519-2013	lyondellbasell
Metocene HM2015		Gen. Variant: SDS_CN
Version 1.1 Revision Date	2019-09-28 Print Date 20	022-01-04 SDS No.: BE8357
	Keep person warm, if neces Resuscitation (CPR)	ssary give Cardio-Pulmonary
In case of skin contact	large amounts of water to c Do not attempt to peel poly skin.	the skin, immediately flush with cool the affected tissue and polymer. mer from skin as this will remove the cy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discomf	water for several minutes and seek ort persists.
	minutes.	vith cool running water for at least 15 attempt to remove the material
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
Notes to physician		
Symptoms	: Inhalation of process fumes the nose and throat and co	and vapors may cause soreness in ughing.
Hazards	: Dust contact with the eyes Molten polymer may cause	can lead to mechanical irritation. thermal burns.
Treatment	: Treatment of overexposure symptoms and the clinical c	should be directed at the control of condition of the patient.
5. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or	water spray.
	: LARGE FIRES: Use water spray hose nozz	les from a safe location.
Unsuitable extinguishing media	: None known.	

(+) 188 1699 6168 hongrunplastics.com

SAFETY DATA SHEET

according to GB/T 16483-2008, GB/T 17519-2013

lyondellbasell

· · · · · · · · ·	Gen. Variant: SDS_CN
ersion 1.1 Revision Date	2019-09-28 Print Date 2022-01-04 SDS No.: BE8
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
	: The formation of hydrocarbons and aldehydes are possible in the initial stages of a fire (especially in between 400 C and 700 C)
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
CCIDENTAL RELEASE MEAS	URES
ACCIDENTAL RELEASE MEAS	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth

	(+) 188 1699 6168
	hongrunplastics.com
SAFETY DATA SHEET according to GB/T 16483-2008, G	B/T 17519-2013 Iyondelibase
Metocene HM2015	Gen. Variant: SDS_CN
Version 1.1 Revision Date	2019-09-28 Print Date 2022-01-04 SDS No.: BE835'
	transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
7. Handling and storage	
Precautions for safe handlin	g
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Conditions for safe storage.	including any incompatibilities
Requirements for storage areas and containers	 Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	

		(+) 188	1699 616	8		
		hongrun	plastics.coi	n		
SAFETY DA' according to GB	TA SHEET /T 16483-2008, GB/	Г 17519-2013		lyo	ndellba	asell
Metocene H	M2015			Gen. V	Variant: SDS	_CN
Version 1.1	Revision Date 2	019-09-28	Print Date	2022-01-04	SDS No.	: BE8357
	:	See Section	1.			
8. EXPOSURE C	CONTROLS/PERSON	AL PROTEC	TION			

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	3 mg/m3 respirable	US (ACGIH) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection

: Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below

(+) 188 1699 6168 hongrunplastics.com

SAFETY DATA SHEET

according to GB/T 16483-2008, GB/T 17519-2013



Metocene HM2015		Ger	n. Variant: SDS_CN
Version 1.1 Revision	Date 2019-09-28	Print Date 2022-01-04	SDS No.: BE8357
	When worke limit they mu Use appropri exceeds rec Where work	ed exposure limits. ers are facing concentration ust use appropriate certified riate respiratory protection commended limits. kers could be exposed to du exposure limit they must use	d respirators. where atmosphere ust concentrations
Hand protection		s that provide thermal prote contact with heated materi	
Eye and face protection	injury or oth	e goggles should be worn to per irritation to eyes due to a from handling this product.	
Skin and body protection	: Wear suitab	ble protective clothing.	
Hygiene measures	be based or of the protect performed, hazards and during use. Use good p Wash hands facilities.	f appropriate personal prote n an evaluation of the perfor ctive equipment relative to conditions present, duration d/or potential hazards that r ersonal hygiene practices. s before eating, drinking, sr ntaminated clothing and wa	mance characteristics the task(s) to be n of use, and the may be encountered moking, or using toilet

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color	: Pellets. : Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.

SAFETY DATA SHEET ccording to GB/T 16483-2008,	GB/T 17519-2013 Iyondellbase		
Metocene HM2015	Gen. Variant: SDS_CN		
Version 1.1 Revision Da	te 2019-09-28 Print Date 2022-01-04 SDS No.: BE82		
Autoignition temperature	: > 300 °C		
Decomposition temperature	: not determined		
Melting point/range	: 50 - 170 °C		
Boiling point/boiling range	: Not applicable.		
Vapor pressure	: Not applicable.		
Density	: < 1 g/cm3		
Water solubility	: Insoluble.		
Partition coefficient: n-	: No Data Available.		
octanol/water Viscosity, dynamic	: Not applicable.		
Relative vapor density	: Not applicable.		
Evaporation rate	: Not applicable.		
Explosive properties	: No Data Available.		
Other Information	: No additional information available.		
D. STABILITY AND REACTIVIT	Y : No known reactivity hazards.		
Chemical stability	: Stable under normal conditions.		
Hazardous reactions	: Will not occur.		
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.		
Materials to avoid	: Material may be softened by some hydrocarbons.		
Hazardous decomposition	: Not expected to decompose under normal conditions.		
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.		
I. TOXICOLOGICAL INFORMA	TION		
Acute toxicity			

	(+) 188 1699 6168			
	hongrunplastics.com			
SAFETY DATA SHEET according to GB/T 16483-2008, G	BB/T 17519-2013			
Metocene HM2015	Gen. Variant: SDS_CN			
Version 1.1 Revision Date	e 2019-09-28 Print Date 2022-01-04 SDS No.: BE8357			
Acute oral toxicity	: Not classified			
Acute inhalation toxicity	: Not classified			
Acute dermal toxicity	: Not classified			
Skin corrosion/irritation	: Not a skin irritant.			
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.			
Respiratory or skin sensitization	: Not classified			
Chronic toxicity				
Carcinogenicity	: Not classified			
Germ cell mutagenicity	Not classified			
Reproductive toxicity				
Effects on fertility /	: Not classified			
Effects on or via lactation Effects on Development	: Not classified			
Target Organ Systemic Toxicant - Single exposure	The substance or mixture is not classified as specific target organ toxicant, single exposure.			
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.			
Aspiration hazard	: Not applicable.			
12. Ecological information				
Ecotoxicology Assessment				
Short-term (acute) aquatic hazard	: Not classified			
Long-term (chronic) aquatic hazard	: Not classified			

	(+)	188 1699 6168		
	hon	grunplastics.com	1 1 111	
SAFETY DATA SHEET according to GB/T 16483-2008, (GB/T 17519	9-2013	lyondellbase	
Metocene HM2015			Gen. Variant: SDS_CN	
Version 1.1 Revision Dat	te 2019-09	P-28 Print Date 20	022-01-04 SDS No.: BE835	
Persistence and degradability	,			
Biodegradability	: Not ex	Not expected to be biodegradable.		
Bioaccumulative potential				
Bioaccumulation	: This m	naterial is not expected	to bioaccumulate.	
Mobility in soil				
Mobility	: no dat	ta available		
Other adverse effects				
Environmental fate and pathways	: This n	naterial is not volatile a	and insoluble in water.	
Other information				
Additional ecological information	solubil No da other	lity of polymers. ta available on this pro	e minimal based on the low water oduct. However, birds, fish and which may obstruct their	
3. Disposal considerations				
Waste treatment methods				
Product	transp applica engine	orted and disposed of	d be packaged, labeled, or reclaimed in conformance with ons and in conformance with good im where possible.	
4. TRANSPORT INFORMATION				
lot regulated for transport				

(+) 188 1699 6168

hongrunplastics.com

SAFETY DATA SHEET

according to GB/T 16483-2008, GB/T 17519-2013

Metocene HM2015

Revision Date 2019-09-28 Version 1.1

Gen. Variant: SDS CN Print Date 2022-01-04

SDS No.: BE8357

lyondellbasell

15. REGULATORY INFORMATION

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further

(+) 188 1699 6168

hongrunplastics.com

SAFETY DATA SHEET

according to GB/T 16483-2008, GB/T 17519-2013

Metocene HM2015

Version 1.1 Revision Date 2019-09-28

Gen. Variant: SDS CN Print Date 2022-01-04

SDS No.: BE8357

lyondellbasell

Disclaimer

information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet