

Technical Data Sheet

Clyrell RC6049



Polypropylene, Specialty Products

Product Description

Clyrell RC6049 is a polypropylene terpolymer containing anti-blocking agent, with low seaming temperature, good optical properties, and good stiffness impact balance. Typical customer applications are for skin layer of coextruded CPP, BOPP films.

Regulatory Status

For regulatory compliance information, see *Clyrell* RC6049 [Product Stewardship Bulletin \(PSB\) and Safety Data Sheet \(SDS\)](#).

Status	Commercial: Active
Availability	Africa-Middle East; Asia-Pacific; Australia and New Zealand
Application	Food Packaging Film; Lamination Film
Market	Flexible Packaging
Processing Method	BOPP; Cast Film; Double Bubble
Attribute	Medium Temperature Heat Sealability; Superior Optical Properties

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	7	g/10 min	ASTM D1238
Density	0.90	g/cm ³	ASTM D792
Mechanical			
Flexural Modulus	850	MPa	ASTM D790
Tensile Strength at Yield	25	MPa	ASTM D638
Tensile Elongation at Yield	13	%	ASTM D638
Impact			
Notched Izod Impact Strength, (23 °C)	47	J/m	ASTM D256
Thermal			
Deflection Temperature Under Load	80	°C	ASTM D648