

Technical Data Sheet

Hostacom BB 1161 F/M D72703



Polypropylene Compounds

Product Description

Hostacom BB 1161 F M D72703 is a 12% talc filled PP copolymer, with high melt flow rate, and UV resistance, excellent processability and high stiffness. The product reflects the latest advancements in resin synthesis and compounding technology. The product is also available as a customized color matched, pellet form. This grade is delivered in D72703 color version.

Regulatory Status

For regulatory compliance information, see Hostacom BB 1161 F/M D72703 [Product Stewardship Bulletin \(PSB\)](#) and [Safety Data Sheet \(SDS\)](#).

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

Status	Commercial: Active
Availability	Europe
Application	Interior Trims
Market	Automotive
Processing Method	Injection Molding
Attribute	Good Color Stability; Good Processability; High Flow; Medium Impact Resistance; UV Resistant

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	28	g/10 min	ISO 1133-1
Density, (23 °C)	1	g/cm ³	ISO 1183-1/A
Mechanical			
Flexural Modulus, (23 °C, Tech. A)	2000	MPa	ISO 178/A1
Impact			
Charpy Impact Strength - Notched, (23 °C)	4	kJ/m ²	ISO 179-1/1eA

Notes

These are typical property values not to be construed as specification limits.