

## Technical Data Sheet

### Moplen EP549N



Polypropylene, Impact Copolymer

#### Product Description

Moplen EP549N is a medium melt flow polypropylene impact copolymer resin, with low warpage, good impact stiffness balance, good flowability, low stress whitening, good UV stability, and good thermal resistance. Typical customer applications are battery casing with good sealing properties in low fiber generation, industrial containers, and motorcycle parts.

<b>Application</b>	Battery Cases; Industrial Packaging
<b>Market</b>	Consumer Products
<b>Processing Method</b>	Injection Molding
<b>Attribute</b>	Good Impact Resistance; Good Stiffness; Impact Copolymer

Typical Properties	Nominal Value	Units	Test Method
<b>Physical</b>			
Melt Flow Rate, (230 °C/2.16 kg)	12	g/10 min	ASTM D1238
Density	0.90	g/cm <sup>3</sup>	ASTM D792
<b>Mechanical</b>			
Flexural Modulus	1350	MPa	ASTM D790
Tensile Strength at Yield	26	MPa	ASTM D638
Tensile Elongation at Yield	6	%	ASTM D638
<b>Impact</b>			
Notched Izod Impact Strength, (23 °C)	100	J/m	ASTM D256
<b>Thermal</b>			
Deflection Temperature Under Load	100	°C	ASTM D648