



## Moplen EP2596

### Polypropylene, Impact Copolymer

#### Product Description

Moplen EP2596 is a nucleated polypropylene impact copolymer, suitable for injection moulding applications and contains antistatic agent. This grade exhibits good stiffness with medium fluidity.

Potential applications include houseware, furniture, pails, cylindrical containers and crates.

#### Product Characteristics

Status	Development
Test Method used	ISO
Availability	Europe, Asia-Pacific, Africa-Middle East
Processing Methods	Injection Molding
Features	Antistatic, Medium Flow, Nucleated, Good Stiffness
Typical Customer Applications	Crates, Furniture, Housewares, Opaque Containers

Typical Properties	Method	Value	Unit
<b>Physical</b>			
Density	ISO 1183	0.9	g/cm <sup>3</sup>
Melt flow rate (MFR) (230°C/2.16kg)	ISO 1133	20	g/10 min
<b>Mechanical</b>			
Tensile Stress at Yield	ISO 527-1, -2	28	MPa
Flexural modulus	ISO 178	1450	MPa
Elongation at yield	ISO 527	5	%
<b>Impact</b>			
Charpy notched impact strength (23°C)	ISO 179	9	kJ/m <sup>2</sup>

#### Notes

Typical properties; not to be construed as specifications.