(+) 188 1699 6168 hongrunplastics.com



# Pro-fax SE012

### Polypropylene, Impact Copolymer

#### **Product Description**

*Pro-fax* SE012 low melt flow, electrical grade polypropylene copolymer resin has outstanding toughness, flex-life and abrasion resistance. This resin demonstrates good processing behavior and is tailored for production of heavy- and thin-walled constructions. Other features include excellent electrical and physical properties, resistance to stress-cracking, solvent and chemical resistance, good colorability, high yields due to low specific gravity, and proven life in the presence of copper.

All ingredients of *Pro-fax* SE012 meet the chemical registration requirements of TSCA (U.S.) and DSL (Canada).

Typical applications include oil well logging cables, data cables and heavier wall insulation.

#### **Product Characteristics**

Status Commercial: Active

Test Method used ISO

**Availability** North America

**Features** Good Abrasion Resistance , Good Chemical Resistance,

Good Colorability, Copolymer, Good Dimensional Stability, Good Electrical Properties, High ESCR (Environmental Stress Cracking Resistance), Fatigue Resistant, Low Flow, Good Heat Aging Resistance, Machinable, Good

Processability, Solvent Resistant, Good Toughness, Low to

No Water Absorption

**Typical Customer Applications** Other Industrial, Wire & Cable

Method	Value	Unit
ISO 1183	0.90	g/cm³
ISO 1133	1.5	g/10 min
ISO 527-1, -2	25	MPa
ISO 527-1, -2	10	%
ISO 178	1000	MPa
ISO 180	34	kJ/m²
ISO 75B-1, -2	78	°C
	ISO 1183 ISO 1133 ISO 527-1, -2 ISO 527-1, -2 ISO 178	ISO 1183 0.90 ISO 1133 1.5  ISO 527-1, -2 25 ISO 527-1, -2 10 ISO 178 1000  ISO 180 34

## **Additional Properties**

Environmental Stress-Cracking Resistance, REA PE-210: >1,000 hrs Thermal Stress-Cracking Resistance, REA PE-210: > 1,000 hrs Drop Weight Impact Strength, Basell Test Method, -20°F: 23 ft-lbs

#### Notes

Typical properties; not to be construed as specifications.