



Hostacom T 60 T4 NERO

Compounded Polyolefin

IMDS Number:

19524193

Product Description

Hostacom T 60 T4 NERO is a 40% talc filled PP homopolymer, with medium melt flow, high impact/stiffness balance and excellent thermal resistance. This grade is delivered in black color version.

This grade is not intended for medical, pharmaceutical, food, drinking water and all applications not listed in the supported list. For more information please contact our sales representatives.

Product Characteristics

Status	Commercial	
Availability	Europe	(1)
Processing Method	Injection molding	
Features	Impact/stiffness balance, thermal resistance.	
Typical Customer Applications	Designed for automotive instrument panel.	

Typical Properties	Method	Value	Unit
Physical			
Melt Flow Rate (230 °C, 2.16 kg)	ISO 1133	5	g/10 min
Density (23 °C)	ISO 1183-1/A	1.25	g/cm ³
Mechanical			
Tensile Stress at Yield (23 °C)	ISO 527-1, -2	29	MPa
Flexural Modulus (23 °C) Tech. A	ISO 178/A1	3500	MPa
Impact			
Izod Impact strength, notched (23 °C)	ISO 180/1A	2.5	kJ/m ²

Product Storage and Handling

- Product should be stored in dry conditions at temperatures below 50°C and protected from UV-light.
- Improper storage may bring damage to the packaging and can negatively affects on the quality of this product
- Keep material completely dry for good processing.

Notes

Typical properties; not to be construed as specifications.

(1) : Here is indicated the region where the material is produced. For importation or demand of a local equivalent grade, please contact our Sales Representatives.