

Safety Data Sheet

ULTRAMID® 8260 POLYAMIDE

Revision date : 2011/02/21

Version: 1.0

Page: 1/6

(30216558/SDS_GEN_US/EN)

1. Product and Company Identification

Use: Polymer

Company

BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Synonyms:

POLYAMIDE RESIN

2. Hazards Identification

Emergency overview

CAUTION:

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear safety glasses with side-shields.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

State of matter: solid

Colour: opaque

Odour: odourless

Potential health effects**Primary routes of exposure:**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Irritation / corrosion:

Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes.

Sensitization:

The substance is inert.

Chronic toxicity:

Safety Data Sheet

ULTRAMID® 8260 POLYAMIDE

Revision date : 2011/02/21
Version: 1.0

Page: 2/6
(30216558/SDS_GEN_US/EN)

Repeated dose toxicity: No adverse effects have been reported in the processing and use of the product. No known chronic effects.

Genotoxicity: The substance is inert.

Medical conditions aggravated by overexposure:

Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product. See MSDS section 11 - Toxicological information.

Potential environmental effects

Aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Degradation / environmental fate:

Experience shows this product to be inert and non-degradable.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25038-54-4	> 50.0 - < 70.0 %	polyamide (PA 6)
13983-17-0	> 30.0 - < 50.0 %	Wollastonite (Ca(SiO ₃))

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-Fighting Measures

Flash point:	> 400 °C	(closed cup)
Autoignition:		No data available.
Self-ignition temperature:		not self-igniting

Suitable extinguishing media:

water spray, dry powder, carbon dioxide, foam

Hazards during fire-fighting:

No particular hazards known.



Safety Data Sheet

ULTRAMID® 8260 POLYAMIDE

Revision date : 2011/02/21
Version: 1.0

Page: 3/6
(30216558/SDS_GEN_US/EN)

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

Reclaim for processing if possible. Sweep/shovel up. Place into suitable containers for reuse or disposal in a licensed facility.

7. Handling and Storage

Handling

Protection against fire and explosion:

No explosion proofing necessary.

Storage

General advice:

Keep container tightly closed. Avoid deposition of dust.

Storage stability:

Protect against moisture.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

caprolactam

ACGIH TWA value 5 mg/m3 Inhalable fraction and vapor ;

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Safety glasses with side-shields.

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	pellets
Odour:	odourless
Colour:	opaque



Safety Data Sheet

ULTRAMID® 8260 POLYAMIDE

Revision date : 2011/02/21
Version: 1.0

Page: 4/6
(30216558/SDS_GEN_US/EN)

pH value:		not applicable
softening point:	215 - 225 °C	
Relative density:	1.05 - 1.25	
Bulk density:	500 - 800 kg/m ³	
Solubility in water:		insoluble

10. Stability and Reactivity

Conditions to avoid:

Avoid prolonged exposure to extreme heat.

Substances to avoid:

strong oxidizing agents, acids, bases

Hazardous reactions:

The product is chemically stable.

Decomposition products:

Possible thermal decomposition products:
hydrogen cyanide, carbon monoxide, ammonia

Thermal decomposition:

> 300 °C
May decompose if overheated and/or subjected to prolonged heating.

Corrosion to metals:

No corrosive effect on metal.

11. Toxicological information

Acute toxicity

Information on: caprolactam

Assessment of acute toxicity:

Of moderate toxicity after short-term inhalation. Of moderate toxicity after single ingestion. Virtually nontoxic after a single skin contact.

Irritation / corrosion

Information on: caprolactam

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Repeated dose toxicity

Information on: caprolactam

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation. The substance may cause damage to the upper respiratory tract even after repeated inhalation, as shown in animal studies.

Other Information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.



Safety Data Sheet

ULTRAMID® 8260 POLYAMIDE

Revision date : 2011/02/21
Version: 1.0

Page: 5/6
(30216558/SDS_GEN_US/EN)

12. Ecological Information

Bioaccumulation

The product will not be readily bioavailable due to its consistency and insolubility in water.

13. Disposal considerations

Waste disposal of substance:

Incinerate in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories):

Not hazardous;

16. Other Information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0



Safety Data Sheet

ULTRAMID® 8260 POLYAMIDE

Revision date : 2011/02/21

Page: 6/6

Version: 1.0

(30216558/SDS_GEN_US/EN)

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations

msds@basf.com

MSDS Prepared on: 2011/02/21

ULTRAMID® 8260 POLYAMIDE is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET

