



The Chemical Company

HELPING MAKE PRODUCTS BETTER™

## Safety data sheet

### ULTRAMID® B3GK24 BLACK 00564 POLYAMIDE

Revision date : 2005/03/09

Page: 1/4

Version: 1.0

(30045365/MDS\_GEN\_US/EN)

#### 1. Substance/preparation and company identification

Company  
BASF CORPORATION  
100 Campus Drive  
Florham Park, NJ 07932

24 Hour Emergency Response Information  
CHEMTREC: (800) 424-9300  
BASF HOTLINE: (800) 832-HELP

Chemical family: polyamide

#### 2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25038-54-4	>= 55.0 %	polyamide (PA 6)

#### 3. Hazard identification

##### Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

##### Potential health effects

##### Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

##### Acute toxicity:

Contact with molten product may cause thermal burns.

#### 4. First-aid measures

##### General advice:

Remove contaminated clothing.

##### If inhaled:

Assist in breathing if necessary. Keep patient calm, remove to fresh air. Consult a physician.

##### If on skin:

Burns caused by molten material require hospital treatment.

##### If in eyes:

If irritation develops, seek medical attention. In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

##### If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.





The Chemical Company

HELPING MAKE PRODUCTS BETTER™

## Safety data sheet

### ULTRAMID® B3GK24 BLACK 00564 POLYAMIDE

Revision date : 2005/03/09

Page: 2/4

Version: 1.0

(30045365/MDS\_GEN\_US/EN)

#### 5. Fire-fighting measures

Autoignition: > 400 °C (ASTM D1929)

**Suitable extinguishing media:**

water, foam, dry extinguishing media

**Hazards during fire-fighting:**

carbon monoxide, hydrogen cyanide, can be emitted at > 300 °C

Formation of further decomposition and oxidation products depends upon the fire conditions. Under special fire conditions traces of other toxic substances are possible.

**Further information:**

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### 6. Accidental release measures

**Cleanup:**

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

**Further information:**

High risk of slipping due to leakage/spillage of product.

#### 7. Handling and storage

**Handling**

**Protection against fire and explosion:**

Take precautionary measures against static discharges.

**Storage**

**General advice:**

Keep container tightly closed. Avoid deposition of dust.

**Storage stability:**

Protect against moisture.

#### 8. Exposure controls and personal protection

**Advice on system design:**

Ensure adequate ventilation.

**Personal protective equipment**

**Respiratory protection:**

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.



# Safety data sheet

## ULTRAMID® B3GK24 BLACK 00564 POLYAMIDE

Revision date : 2005/03/09

Page: 3/4

Version: 1.0

(30045365/MDS\_GEN\_US/EN)

**Hand protection:**

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

**Eye protection:**

Tightly fitting safety goggles (splash goggles) (EN 166)

**Body protection:**

Body protection must be chosen based on level of activity and exposure.

### 9. Physical and chemical properties

Form:	granules
Odour:	odourless
Colour:	various, depending on the colourant
Melting temperature:	approx. 220 °C (DIN 53736)
Density:	1.10 - 1.60 g/cm <sup>3</sup> (20 °C) (EN/ISO 1183-1)
Bulk density:	500 - 800 kg/m <sup>3</sup>
Solubility in water:	insoluble

### 10. Stability and reactivity

**Decomposition products:**

Hazardous decomposition products: carbon monoxide, hydrogen cyanide

**Thermal decomposition:**

&gt; 300 °C

### 11. Toxicological information

**Chronic toxicity****Other information:**

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### 12. Ecological information

**Environmental fate and transport****Biodegradation:**

Evaluation: Experience shows this product to be inert and non-degradable.

**Bioaccumulation:**



The Chemical Company

HELPING MAKE PRODUCTS BETTER™

## Safety data sheet

### ULTRAMID® B3GK24 BLACK 00564 POLYAMIDE

Revision date : 2005/03/09

Page: 4/4

Version: 1.0

(30045365/MDS\_GEN\_US/EN)

The product will not be readily bioavailable due to its consistency and insolubility in water..  
Due to the consistency of the product, dispersion into the environment is impossible. Therefore no negative effects on the environment may be anticipated based on the present state of knowledge.

## 13. Disposal considerations

### Waste disposal of substance:

Check for possible recycling.

May be disposed of or combusted with domestic refuse according to local regulations.

### Contaminated packaging:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

## 14. Transport information

Reference Bill of Lading

## 15. Regulatory information

### Federal Regulations

#### Registration status:

TSCA, US

released / listed

## 16. Other information

### Local contact information

Tech Desk

1-800-527-8324

ULTRAMID® B3GK24 BLACK 00564 POLYAMIDE is a registered trademark of BASF Corporation or BASF AG

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET

