



The Chemical Company

Safety data sheet

ULTRAMID® B3S BLACK 00464 POLYAMIDE

Revision date : 2006/08/02

Version: 1.0

Page: 1/5

(30045493/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. Composition/information on ingredients

| CAS Number | Content (W/W) | Chemical name |
|------------|---------------------|------------------|
| 25038-54-4 | = 90.0 - <= 100.0 % | polyamide (PA 6) |
| 1333-86-4 | <= 1.0 % | carbon black |

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Repeated dose toxicity:

No known chronic effects.

Information on: Carbon black

*Prolonged inhalation exposures may produce cough, phlegm, tiredness, chest pain and headache.
Chronic exposures have been known to produce pneumoconiosis (chronic inflammatory and fibrotic lung disease).*



Safety data sheet

ULTRAMID® B3S BLACK 00464 POLYAMIDE

Revision date : 2006/08/02

Version: 1.0

Page: 2/5

(30045493/MDS_GEN_US/EN)

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Assist in breathing if necessary. Keep patient calm, remove to fresh air. Consult a physician.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

If irritation develops, seek medical attention. In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Autoignition:

> 400 °C

(ASTM D1929)

Suitable extinguishing media:

water, foam, dry extinguishing media

Hazards during fire-fighting:

carbon monoxide, hydrogen cyanide, can be emitted at > 300 °C

Formation of further decomposition and oxidation products depends upon the fire conditions. Under special fire conditions traces of other toxic substances are possible.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

General advice:

Keep container tightly closed. Avoid deposition of dust.



Safety data sheet

ULTRAMID® B3S BLACK 00464 POLYAMIDE

Revision date : 2006/08/02

Page: 3/5

Version: 1.0

(30045493/MDS_GEN_US/EN)

Storage stability:
Protect against moisture.

8. Exposure controls and personal protection

Components with workplace control parameters

| | | |
|--------------|-------|-----------------------------------|
| carbon black | OSHA | PEL 3.5 mg/m ³ ; |
| | ACGIH | TWA value 3.5 mg/m ³ ; |

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

9. Physical and chemical properties

| | |
|----------------------|---|
| Form: | granules |
| Odour: | odourless |
| Colour: | various, depending on the colourant |
| Melting temperature: | approx. 220 °C (DIN 53736) |
| Density: | 1.00 - 1.20 g/cm ³ (20 °C) (EN/ISO 1183-1) |
| Bulk density: | 500 - 800 kg/m ³ |
| Solubility in water: | insoluble |

10. Stability and reactivity

Decomposition products:

Hazardous decomposition products: carbon monoxide, hydrogen cyanide

Thermal decomposition:

> 300 °C

11. Toxicological information

Chronic toxicity

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport



Safety data sheet

ULTRAMID® B3S BLACK 00464 POLYAMIDE

Revision date : 2006/08/02

Version: 1.0

Page: 4/5

(30045493/MDS_GEN_US/EN)

Biodegradation:

Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation:

The product will not be readily bioavailable due to its consistency and insolubility in water..

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling.

May be disposed of or combusted with domestic refuse according to local regulations.

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

State regulations

State RTK

CAS Number
1333-86-4

Chemical name
carbon black

State RTK
MA, NJ, PA



Safety data sheet

ULTRAMID® B3S BLACK 00464 POLYAMIDE

Revision date : 2006/08/02

Version: 1.0

Page: 5/5

(30045493/MDS_GEN_US/EN)

16. Other information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

Tech Desk
1-800-527-8324

ULTRAMID® B3S BLACK 00464 POLYAMIDE is a registered trademark of BASF Corporation or BASF AG
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN
ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR
GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE,
WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR
YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER
EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A
PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR
INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE
USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE
SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A
PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND
AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF
HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE
DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH
BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

