

Ultramid® T KR 4350 BK00564

Polyamide 6/6T Copolymer



PHYSICAL	ASTM Test Method	Property Value	
Moisture, %	D-570		
MECHANICAL	ASTM Test Method	Dry	Conditioned
Tensile Strength, Yield, MPa (psi)	D-638		
Tensile Strength, Break, MPa (psi)	D-638		
Elongation, Yield, %	D-638		
Elongation, Break, %	D-638		
Flexural Modulus, MPa (psi)	D-790		
Flexural Strength, MPa (psi)	D-790		
IMPACT	ASTM Test Method	Dry	Conditioned
Notched Izod Impact, J/M (ft-lbs/in)	D-256		
THERMAL	ASTM Test Method	Dry	Conditioned
Coef. of Linear Thermal Expansion, mm/mm C (in/in F)	E-831	X10-4	X10-4
ELECTRICAL	ASTM Test Method	Dry	Conditioned

Note

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required.

