

# Ultramid® T KR 4350 BK00564

## Polyamide 6/6T Copolymer



PHYSICAL		ISO Test Method	Property Value
Moisture, %		62	
RHEOLOGICAL	ISO Test Method	Dry	Conditioned
MECHANICAL	ISO Test Method	Dry	Conditioned
Tensile Modulus, MPa	527		
Tensile stress at yield, MPa	527		
Tensile stress at break, MPa	527		
Tensile strain at yield, %	527		
Nominal strain at break, %	527		
Flexural Strength, MPa	178		
Flexural Modulus, MPa	178		
IMPACT	ISO Test Method	Dry	Conditioned
Izod Notched Impact, kJ/m <sup>2</sup>	180		
Charpy Notched, kJ/m <sup>2</sup>	179		
Charpy Unnotched, kJ/m <sup>2</sup>	179		
THERMAL	ISO Test Method	Dry	Conditioned
Coef. of Linear Thermal Expansion, Parallel, mm/mm C	X10-4		X10-4
Coef. of Linear Thermal Expansion, Normal, mm/mm C	X10-4		X10-4
ELECTRICAL	ISO Test Method	Dry	Conditioned

### Note

Although all statements and information in this publication are believed to be accurate and reliable, they are presented gratis and for guidance only, and risks and liability for results obtained by use of the products or application of the suggestions described are assumed by the user. NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH. Statements or suggestions concerning possible use of the products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that toxicity data and safety measures are indicated or that other measures may not be required.



BASF Corporation  
Engineering Plastics  
609 Biddle Avenue  
Ypsilanti, MI 48192

