

Safety Data Sheet

NYPEL RC6024 BK

Revision date : 2013/07/09
Version: 2.0

Page: 1/7
(30486111/SDS_GEN_US/EN)

1. Product and Company Identification

Company
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTRIC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Chemical family: polyamide

2. Hazards Identification

Emergency overview

CAUTION:
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.
CONTAINS MATERIAL WHICH MAY CAUSE LUNG DAMAGE BASED ON ANIMAL DATA.
Use with local exhaust ventilation.
Wear a NIOSH-certified (or equivalent) particulate respirator.
Wear protective clothing.
Eye wash fountains and safety showers must be easily accessible.

State of matter: solid
Colour: black
Odour: odourless

Potential health effects

Primary routes of exposure:

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Irritation / corrosion:

Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes. Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Chronic toxicity:



Safety Data Sheet

NYPEL RC6024 BK

Revision date : 2013/07/09

Version: 2.0

Page: 2/7

(30486111/SDS_GEN_US/EN)

Carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Repeated dose toxicity: No adverse effects have been reported in the processing and use of the product.

Genotoxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Signs and symptoms of overexposure:

No significant reaction of the human body to the product known.

Potential environmental effects

Aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Degradation / environmental fate:

Experience shows this product to be inert and non-degradable.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25038-54-4	>= 50.0 - <= 70.0 %	polyamide (PA 6)
12001-26-2	>= 15.0 - <= 30.0 %	Mica-group minerals
65997-17-3	>= 7.0 - <= 15.0 %	Glass, oxide, chemicals
471-34-1	>= 1.0 - <= 5.0 %	Calcium carbonate
9003-07-0	>= 0.5 - <= 1.5 %	polypropylene
9003-55-8	>= 0.5 - <= 1.5 %	Polystyrene with 1,3-butadiene polymer
1333-86-4	>= 0.1 - <= 1.0 %	carbon black

4. First-Aid Measures

General advice:

Remove contaminated clothing. Burns caused by molten material require hospital treatment.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention. Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-Fighting Measures

Flash point: > 300 °C

Self-ignition temperature: not self-igniting



Safety Data Sheet

NYPEL RC6024 BK

Revision date : 2013/07/09

Version: 2.0

Page: 3/7

(30486111/SDS_GEN_US/EN)

Suitable extinguishing media:
water spray, dry powder, foam

Hazards during fire-fighting:

carbon monoxide, hydrogen cyanide, can be emitted at > 300 °C

Formation of further decomposition and oxidation products depends upon the fire conditions. Under special fire conditions traces of other toxic substances are possible.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Do not allow to enter drains or waterways. Notify proper authorities.

6. Accidental release measures

Cleanup:

Reclaim for processing if possible. Sweep/shovel up. Place into suitable containers for reuse or disposal in a licensed facility.

For large amounts: Pick up with suitable appliance and dispose of.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and Storage

Handling

Protection against fire and explosion:

No explosion proofing necessary.

Storage

General advice:

Keep container tightly closed. Avoid deposition of dust.

Storage stability:

Protect against moisture.

8. Exposure Controls and Personal Protection

Components with occupational exposure limits

caprolactam	ACGIH TLV	TWA value 5 mg/m ³ Inhalable fraction and vapor ;
carbon black	OSHA PEL	PEL 3.5 mg/m ³ ;
Mica-group minerals	ACGIH TLV	TWA value 3.5 mg/m ³ ;
Calcium carbonate	OSHA PEL	TWA value 20 millions of particles per cubic foot of air ;
	ACGIH TLV	TWA value 3 mg/m ³ Respirable fraction ;
	OSHA PEL	PEL 5 mg/m ³ Respirable fraction ; PEL 15 mg/m ³ Total dust ;

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.



Safety Data Sheet

NYPEL RC6024 BK

Revision date : 2013/07/09

Version: 2.0

Page: 4/7

(30486111/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	pellets
Odour:	odourless
Colour:	black
pH value:	not applicable
Melting point:	not applicable
Boiling point:	not applicable
Vapour pressure:	not applicable
Density:	not applicable
Relative density:	No data available.
Bulk density:	500 - 800 kg/m ³
Vapour density:	not applicable
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Solubility in water:	insoluble

10. Stability and Reactivity

Conditions to avoid:

Avoid prolonged exposure to extreme heat.

Substances to avoid:

strong oxidizing agents, acids, bases

Hazardous reactions:

The product is chemically stable.
No hazardous reactions known.

Decomposition products:

Possible thermal decomposition products:
hydrogen cyanide, carbon monoxide, ammonia

Thermal decomposition:

> 300 °C

May decompose if overheated and/or subjected to prolonged heating.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Not an oxidizer.



Safety Data Sheet

NYPEL RC6024 BK

Revision date : 2013/07/09

Version: 2.0

Page: 5/7

(30486111/SDS_GEN_US/EN)

11. Toxicological information

Acute toxicity

Information on: caprolactam

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of moderate toxicity after short-term inhalation. Of low toxicity after short-term skin contact.

Irritation / corrosion

Information on: caprolactam

Assessment of irritating effects:

May cause slight irritation to the skin. May cause slight irritation to the eyes.

Information on: Glass, oxide, chemicals

Assessment of irritating effects:

Skin contact causes irritation. EU-classification

Repeated dose toxicity

Information on: caprolactam

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation. The substance may cause damage to the upper respiratory tract after repeated inhalation, as shown in animal studies.

Information on: Mica-group minerals

Assessment of repeated dose toxicity:

Chronic exposures have been known to produce pneumoconiosis (chronic inflammatory and fibrotic lung disease).

Carcinogenicity

Information on: Glass, oxide, chemicals

IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Information on: carbon black

IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.

Aspiration Hazard:

No aspiration hazard expected.

Other Information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Aquatic toxicity

Information on: Glass, oxide, chemicals



Safety Data Sheet

NYPEL RC6024 BK

Revision date : 2013/07/09

Version: 2.0

Page: 7/7

(30486111/SDS_GEN_US/EN)

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

16. Other Information

Recommended use: Polymer for industrial processing only
Suitable for use in industrial sector: Polymers industry;

NFPA Hazard codes:

Health : 1 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

SDS Prepared by:

BASF NA Product Regulations

msds@basf.com

SDS Prepared on: 2013/07/09

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

