

Safety data sheet

ULTRAMID® A3EG6 BLACK 00564 POLYAMIDE

Revision date : 2006/04/28

Version: 1.0

Page: 1/5

(30043073/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company

BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Molecular formula: (C12 H22 N2 O2)N
Chemical family: polyamide
Synonyms: Poly(hexamethylene adipamide)

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
32131-17-2	>= 50.0 - <= 80.0 %	polyamide (PA 66)
65997-17-3	>= 20.0 - <= 40.0 %	Glass, oxide, chemicals
1333-86-4	<= 1.0 %	carbon black

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear NIOSH-certified chemical goggles.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

Potential health effectsPrimary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns.

Repeated dose toxicity:

No known chronic effects.

Information on: Carbon black

Prolonged inhalation exposures may produce cough, phlegm, tiredness, chest pain and headache.



Safety data sheet

ULTRAMID® A3EG6 BLACK 00564 POLYAMIDE

Revision date : 2006/04/28

Page: 2/5

Version: 1.0

(30043073/MDS_GEN_US/EN)

Chronic exposures have been known to produce pneumoconiosis (chronic inflammatory and fibrotic lung disease).

Information on: Fiberglass

This product contains glass fibers which are compounded into the polymer matrix and thus are not expected to present the same hazards as fiberglass wool.

Information on: Fiberglass

Animal implantation studies have indicated that fiberglass wool is an animal carcinogen. A small study of Canadian glass wool workers reported a statistically significant increase in deaths due to lung cancer; however, animal inhalation studies and several large-scale studies of U.S. and European fiberglass wool workers have shown no statistically significant increases in lung cancer. The International Agency for Research on Cancer (IARC) has classified this material in Category 2B.

Information on: Fiberglass

These findings are based on glass wool, which has a smaller diameter than continuous glass filament or glass fiber chopped strands or rovings. Fiberglass wool is not used in this product.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Flash point:	> 400 °C	(Unspecified)
Autoignition:	> 400 °C	(ASTM D1929)

Suitable extinguishing media:

water, foam, dry extinguishing media

Hazards during fire-fighting:

carbon monoxide, hydrogen cyanide, can be emitted at > 310 °C

Formation of further decomposition and oxidation products depends upon the fire conditions. Under special fire conditions traces of other toxic substances are possible.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.



Safety data sheet

ULTRAMID® A3EG6 BLACK 00564 POLYAMIDE

Revision date : 2006/04/28

Version: 1.0

Page: 3/5

(30043073/MDS_GEN_US/EN)

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

General advice:

Keep container tightly closed.

8. Exposure controls and personal protection

Components with workplace control parameters

Glass, oxide, chemicals

ACGIH	TWA value 5 mg/m3 Inhalable fraction ; TWA value 1 fibers/cm ³ Fiber ; TWA value 1 fibers/cm ³ Fiber ; TWA value 0.2 fibers/cm ³ Fiber ;
carbon black	OSHA PEL 3.5 mg/m3 ;
ACGIH	TWA value 3.5 mg/m3 ;

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

General safety and hygiene measures:

Wash soiled clothing immediately.

9. Physical and chemical properties

Form:

granules

Odour:

odourless



Safety data sheet

ULTRAMID® A3EG6 BLACK 00564 POLYAMIDE

Revision date : 2006/04/28

Page: 4/5

Version: 1.0

(30043073/MDS_GEN_US/EN)

Colour:	various, depending on the colourant	
pH value:		No data available.
Melting temperature:	approx. 260 °C	(DIN 53736)
Density:	1.15 - 1.60 g/cm ³	(20 °C) (EN/ISO 1183-1)
Bulk density:	500 - 800 kg/m ³	
Solubility in water:		insoluble

10. Stability and reactivity

Decomposition products:

Hazardous decomposition products: carbon monoxide, hydrogen cyanide

Thermal decomposition:

> 310 °C

11. Toxicological information

Chronic toxicity

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation:

Because of the product's consistency and low water solubility, bioavailability is improbable.

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling.

Dispose of in accordance with national, state and local regulations.

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations



Safety data sheet

ULTRAMID® A3EG6 BLACK 00564 POLYAMIDE

Revision date : 2006/04/28

Version: 1.0

Page: 5/5

(30043073/MDS_GEN_US/EN)

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

State regulations

State RTK

CAS Number

65997-17-3

1333-86-4

Chemical name

Glass, oxide, chemicals

carbon black

State RTK

MA, NJ, PA

MA, NJ, PA

16. Other information

Local contact information

Tech Desk

1-800-527-8324

ULTRAMID® A3EG6 BLACK 00564 POLYAMIDE is a registered trademark of BASF Corporation or BASF AG

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

