

Safety data sheet

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE

Revision date : 2007/03/09

Version: 2.0

Page: 1/6

(30055645/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Molecular formula: (C12 H22 N2 O2)N
Synonyms: Nylon 66

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
32131-17-2	30.0 - 60.0 %	polyamide (PA 66)
65997-17-3	10.0 - 30.0 %	Glass, oxide, chemicals
7723-14-0	<= 6.0 %	phosphorus

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

INGESTION MAY CAUSE GASTRIC DISTURBANCES.

CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE.

CAN CAUSE CARDIAC OR CARDIOVASCULAR DAMAGE.

CAN CAUSE LIVER DAMAGE.

CAN CAUSE KIDNEY DAMAGE.

CONTAINS MATERIAL WHICH CAN CAUSE CANCER.

Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts/mists/vapours.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear safety glasses with side-shields.

Wear protective clothing.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns.



Safety data sheet

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE

Revision date : 2007/03/09

Version: 2.0

Page: 2/6

(30055645/MDS_GEN_US/EN)

Information on: Phosphine

Thermal decomposition of red phosphorous may emit phosphine. The PEL/TLV for phosphine is 0.3 ppm ACGIH, OSHA (Final); 1 ppm STEL ACGIH, OSHA (Final).

Inhalation of phosphine may result in severe pulmonary irritation, cough, headache, chest tightness, dizziness, lethargy and stupor. Delayed pulmonary edema may result. Inhalation also results in CNS effects including nausea, dizziness, fatigue, ataxia, seizures and possibly coma. Cardiac arrhythmias may also be noted. Gastric disturbances including nausea, vomiting, abdominal pain and diarrhea may also be noted. Liver and kidney damage may also be noted. Exposure to 8 ppm concentrations at 1 or 2 hrs/day were found to be fatal to humans.

Information on: Phosphorous, red

Inhalation of vapors or smoke from products containing red phosphorus may result in respiratory tract irritation, lung injury or systemic effects. In animal studies, red phosphorus was reported to cause adverse lung and kidney effects.

Irritation:

Contact with the eyes or skin may cause mechanical irritation.

Repeated dose toxicity:

Information on: Fiberglass

This product contains glass fibers which are compounded into the polymer matrix and thus are not expected to present the same hazards as fiberglass wool.

Information on: Fiberglass

Animal implantation studies have indicated that fiberglass wool is an animal carcinogen. A small study of Canadian glass wool workers reported a statistically significant increase in deaths due to lung cancer; however, animal inhalation studies and several large-scale studies of U.S. and European fiberglass wool workers have shown no statistically significant increases in lung cancer. The International Agency for Research on Cancer (IARC) has classified this material in Category 2B.

Information on: Fiberglass

These findings are based on glass wool, which has a smaller diameter than continuous glass filament or glass fiber chopped strands or rovings. Fiberglass wool is not used in this product.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required if there are visible signs of phosphine exposure.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Flash point:

> 400 °C

(Unspecified)

Autoignition:

> 350 °C

(ASTM D1929)

Suitable extinguishing media:

water, foam, dry extinguishing media



Safety data sheet

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE

Revision date : 2007/03/09

Page: 3/6

Version: 2.0

(30055645/MDS_GEN_US/EN)

Hazards during fire-fighting:

carbon monoxide, hydrogen cyanide, Phosphine, can be emitted at > 310 °C
Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of.
For large amounts: Pick up with suitable appliance and dispose of.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

General advice:

Provide suitable exhaust ventilation at drying process and in the surrounding of the melt outlet of processing machines. Closed containers should only be opened in well-ventilated areas. Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Handling of hot melt may produce small flame-up conditions. Hot melt should be placed in cool water immediately if flame-up occurs.

Storage

General advice:

Keep container tightly closed. Protect against moisture.

8. Exposure controls and personal protection

Components with workplace control parameters

Glass, oxide, chemicals

	ACGIH	TWA value 5 mg/m ³ Inhalable fraction ; TWA value 1 fibers/cm ³ Fiber ; TWA value 1 fibers/cm ³ Fiber ; TWA value 0.2 fibers/cm ³ Fiber ;
phosphorus	OSHA	PEL 0.1 mg/m ³ ;

Advice on system design:

Ensure adequate ventilation. Local exhaust ventilation preferred.



Safety data sheet

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE

Revision date : 2007/03/09

Version: 2.0

Page: 4/6

(30055645/MDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. Wear the following respiratory protection if exposure limit for phosphine may be exceeded: Wear a NIOSH-certified (or equivalent) supplied-air respirator.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Apron

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Wash soiled clothing immediately.

9. Physical and chemical properties

Form:	granules
Odour:	odourless
Colour:	various, depending on the colourant
pH value:	No data available.
melting range:	260 °C (DIN 53736)
Density:	1.30 - 1.60 g/cm3 (20 °C) (EN ISO 1183-1)
Bulk density:	500 - 800 kg/m3
Solubility in water:	insoluble

10. Stability and reactivity

Decomposition products:

Hazardous decomposition products: carbon monoxide, hydrogen cyanide, Phosphine

Thermal decomposition:

> 310 °C

To avoid thermal decomposition, do not overheat.

11. Toxicological information

Chronic toxicity

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation: Experience shows this product to be inert and non-degradable.



Safety data sheet

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE

Revision date : 2007/03/09

Version: 2.0

Page: 5/6

(30055645/MDS_GEN_US/EN)

Bioaccumulation:

The product will not be readily bioavailable due to its consistency and insolubility in water.

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling.

Dispose of in accordance with national, state and local regulations.

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

SARA 313:

CAS Number
7723-14-0

Chemical name
phosphorus

State regulations

State RTK

CAS Number
65997-17-3
7723-14-0

Chemical name
Glass, oxide, chemicals
phosphorus

State RTK
MA, NJ, PA
MA, NJ, PA

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.



Safety data sheet

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE

Revision date : 2007/03/09
Version: 2.0

Page: 6/6
(30055645/MDS_GEN_US/EN)

16. Other information

HMIS III rating

Health: 3 Flammability: 1 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

Tech Desk
1-800-527-8324

ULTRAMID® A3XZG5 UNCOLORED POLYAMIDE is a registered trademark of BASF Corporation or BASF AG

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

