

## Safety data sheet

Page: 1/9

---

BASF Safety data sheet

Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

### 1. Substance/preparation and manufacturer/supplier identification

**Product name:**

**ULTRADUR® B 4300 G4 UNCOLORED Q100  
POLYBUTYLENE TEREPHTHALATE**

Use: Polymer

Recommended use: Polymer, for industrial processing only

**Manufacturer/supplier:**

BASF South East Asia Pte Ltd.

128 Beach Road #18-01

Guoco Midtown, 189773, Singapore

Telephone: +65 6 337-0330

Telefax number: +65 6 334-0330

E-mail address: xinhui.khaw@basf.com

**Emergency information:**

Singapore Emergency Toll-Free Number:

Telephone: 1800-723-1361

International emergency number:

Telephone: +49 180 2273-112

---

### 2. Hazard identification

**Classification of the substance and mixture:**

No need for classification according to GHS criteria for this product.

**Label elements and precautionary statement:**

The product does not require a hazard warning label in accordance with GHS criteria.



BASF Safety data sheet  
Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

Other hazards which do not result in classification:

No specific dangers known, if the regulations/notes for storage and handling are considered.

### 3. Composition/information on ingredients

#### Chemical nature

Substance nature: mixture

Preparation based on:

| polybutylene terephthalate (PBT)

additives, fillers

### 4. First-Aid Measures

General advice:

Avoid contact with the skin, eyes and clothing.

If inhaled:

| If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

On skin contact:

Wash thoroughly with soap and water Burns caused by molten material require hospital treatment.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Rinse mouth and then drink 200-300 ml of water. If difficulties occur: Seek medical attention.

Note to physician:

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

### 5. Fire-Fighting Measures

Suitable extinguishing media:  
water spray, foam, dry powder

Specific hazards:

At temperatures of > 290 °C can be emitted: carbon monoxide, tetrahydrofuran

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Special protective equipment:

Wear a self-contained breathing apparatus.



BASF Safety data sheet

Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental Release Measures

Personal precautions:

No special precautions necessary.

Environmental precautions:

No special precautions necessary.

Methods for cleaning up or taking up:

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

For residues: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations.

Additional information: High risk of slipping due to leakage/spillage of product.

---

## 7. Handling and Storage

Handling

Avoid inhalation of dusts/mists/vapours. Exhaust ventilation at processing machines is required during thermal processing and/or machining.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

Segregate from foods and animal feeds.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:

Protect against moisture.

---

## 8. Exposure controls and personal protection

Components with occupational exposure limits

The limit values will not be achieved if the product is processed proper and suitable ventilation is provided.



Personal protective equipment

## Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. (Particle filter EN 143 P2 or FFP2)

## Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

## Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

## Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

## General safety and hygiene measures:

No special precautions necessary. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. After use of gloves apply skin-cleaning agents and skin cosmetics.

**9. Physical and Chemical Properties**

Form:	granules	
Colour:	various, depending on the colourant	
Odour:	odourless	
Odour threshold:	not applicable	
pH value:	not applicable	
melting range:	220 - 230 °C (1,013 hPa)	(DIN 53736)
Boiling range:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable	
Evaporation rate:	The product is a non-volatile solid.	
Flammability (solid/gas):	not self-igniting	(derived from flash point)
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	



Ignition temperature:	350 °C	(ASTM D1929)
Thermal decomposition:	> 290 °C	(TGA)
Self ignition:	Thermal decomposition above the indicated temperature is possible. not self-igniting	Test type: Spontaneous self-ignition at room-temperature.
Self heating ability:	It is not a substance capable of spontaneous heating according to UN transport regulations class 4.2.	(VDI 2263, sheet 1, 1.4.1)
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:	not applicable	
Density:	1.3 - 1.8 g/cm <sup>3</sup> (20 °C, 1,013 hPa)	(EN ISO 1183-1)
Relative density:	Study does not need to be conducted.	
Bulk density:	600 - 900 kg/m <sup>3</sup> (20 °C, 1,013 hPa)	(DIN 53466)
Relative vapour density (air):	not applicable	
Solubility in water:	insoluble (20 °C, 1,013 hPa)	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	

## 10. Stability and Reactivity

Conditions to avoid:

Temperature: > 290 °C

See SDS section 7 - Handling and storage.

Thermal decomposition:

> 290 °C (TGA)

Thermal decomposition above the indicated temperature is possible.

Substances to avoid:

No substances known that should be avoided.



BASF Safety data sheet

Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

| Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

No hazardous reactions known.  
The product is chemically stable.

| Possible decomposition products:

carbon monoxide, tetrahydrofuran, terephthalic acid, carbon dioxide, water

| Gaseous products of degradation can be given off if the product is greatly overheated.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

| The product is chemically stable.

Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

## 11. Toxicological Information

### Routes of exposure

### Assessment of acute toxicity

Contact with molten product may cause thermal burns.

### Symptoms

(Further) symptoms and / or effects are not known so far

### Irritation

Assessment of irritating effects:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Experimental/calculated data:

Serious eye damage/irritation: May cause mechanical irritation.

### Respiratory/Skin sensitization

Assessment of sensitization:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Germ cell mutagenicity

Assessment of mutagenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Carcinogenicity

Assessment of carcinogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.



BASF Safety data sheet

Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

## Reproductive toxicity

Assessment of reproduction toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

## Developmental toxicity

Assessment of teratogenicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

## Specific target organ toxicity (single exposure)

not applicable

## Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

## Aspiration hazard

No aspiration hazard expected.

## Other relevant toxicity information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

---

## 12. Ecological Information

### Ecotoxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

### Mobility

Assessment transport between environmental compartments:

Adsorption to solid soil phase is not expected.

### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.



BASF Safety data sheet

Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

Elimination information:

| Poorly biodegradable.

Assessment of stability in water:

| According to structural properties, hydrolysis is not expected/probable.

### Bioaccumulation potential

Assessment bioaccumulation potential:

| Does not significantly accumulate in organisms.

Bioaccumulation potential:

The product will not be readily bioavailable due to its consistency and insolubility in water.

### Other adverse effects

Adsorbable organically-bound halogen (AOX):

| This product contains no organically-bound halogen.

## 13. Disposal Considerations

Check for possible recycling.

Incinerate in suitable incineration plant, observing local authority regulations.

Contaminated packaging:

Packs must be completely emptied.

Completely emptied packagings can be given for recycling.

## 14. Transport Information

### Domestic transport:

UN number or ID number	Not applicable	Not classified as a dangerous good under transport regulations
UN proper shipping name:	Not applicable	
Transport hazard class(es):	Not applicable	
Packing group:	Not applicable	
Environmental hazards:	Not applicable	
Special precautions for user	None known	

### Sea transport

IMDG

UN number or ID number:	Not applicable	Not classified as a dangerous good under transport regulations
UN proper shipping name:	Not applicable	
Transport hazard class(es):	Not applicable	
Packing group:	Not applicable	
Environmental hazards:	Not applicable	
Special precautions for user	None known	



BASF Safety data sheet

Date / Revised: 27.03.2023

Version: 7.0

Product: **ULTRADUR® B 4300 G4 UNCOLORED Q100 POLYBUTYLENE TEREPHTHALATE**

(30036552/SDS\_GEN SG/EN)

Date of print: 20.08.2023

**Air transport**

IATA/ICAO

UN number or ID number	Not classified as a dangerous good under transport regulations
Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

---

**15. Regulatory Information****Other regulations**

---

**16. Other Information**

---

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

