

Safety Data Sheet

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE

Revision date : 2009/10/09

Version: 1.0

Page: 1/6

(30073368/SDS_GEN_US/EN)

1. Product and Company Identification

Company

BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Synonyms:

POLY(BUTYLENE TEREPHTHALATE)

2. Hazards Identification

Emergency overview

CAUTION:

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear NIOSH-certified chemical goggles.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

State of matter: solid

Colour: various, depending on the colourant

Odour: odourless

Potential health effects**Primary routes of exposure:**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Irritation / corrosion:

Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization:

The substance is inert.

Chronic toxicity:**Repeated dose toxicity:** No known chronic effects.Potential environmental effects

Safety Data Sheet

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE

Revision date : 2009/10/09
Version: 1.0

Page: 2/6
(30073368/SDS_GEN_US/EN)

Aquatic toxicity:

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Degradation / environmental fate:

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
30965-26-5	> 40.0 - < 60.0 %	polybutylene terephthalate (PBT)
26062-94-2	> 40.0 - < 60.0 %	polybutylene terephthalate (PBT)

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-Fighting Measures

Flash point:

No data available.

Autoignition:

350 °C

(ASTM D1929)

Self-ignition temperature:

not self-igniting

Suitable extinguishing media:

water, foam, dry extinguishing media

Hazards during fire-fighting:

carbon monoxide, tetrahydrofuran, can be emitted at > 290 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.



Safety Data Sheet

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE

Revision date : 2009/10/09
Version: 1.0

Page: 3/6
(30073368/SDS_GEN_US/EN)

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of.
For large amounts: Pick up with suitable appliance and dispose of.

Further information:

High risk of slipping due to leakage/spillage of product.

7. Handling and Storage

Handling

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

General advice:

Keep container tightly closed.

Storage stability:

Protect against moisture.

8. Exposure Controls and Personal Protection

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

none Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	pellets
Odour:	odourless
Colour:	various, depending on the colourant



Safety Data Sheet

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE

Revision date : 2009/10/09

Page: 4/6

Version: 1.0

(30073368/SDS_GEN_US/EN)

pH value:		not applicable
melting range:	220 - 230 °C	(DIN 53736)
Boiling range:		The substance / product decomposes therefore not determined.
Vapour pressure:		not applicable
Density:	1.2 - 1.35 g/cm3	(20 °C) (EN ISO 1183-1)
Bulk density:	600 - 900 kg/m3	
Solubility in water:		insoluble

10. Stability and Reactivity

Conditions to avoid:
> 290 degrees Celsius

Decomposition products:
Hazardous decomposition products: carbon monoxide, tetrahydrofuran

Thermal decomposition:
298 - 400 °C

11. Toxicological information

Other Information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Degradability / Persistence
Biological / Abiological Degradation

Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation

The product will not be readily bioavailable due to its consistency and insolubility in water.

13. Disposal considerations

Waste disposal of substance:
Check for possible recycling. Dispose of in accordance with national, state and local regulations.

Container disposal:
Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport Information



Safety Data Sheet

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE

Revision date : 2009/10/09
Version: 1.0

Page: 5/6
(30073368/SDS_GEN_US/EN)

Land transport USDOT

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories):

Not hazardous;

16. Other Information

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

BASF supports worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Local Contact Information

Tech Desk
+1 800 5278324

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR



Safety Data Sheet

ULTRADUR® B 6550 L NATURAL POLYBUTYLENE TEREPHTHALATE

Revision date : 2009/10/09

Page: 6/6

Version: 1.0

(30073368/SDS_GEN_US/EN)

PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

