

Safety data sheet

ULTRADUR® S 4090 G4 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2007/01/04
Version: 1.0

Page: 1/5
(30035786/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
30965-26-5	>= 10.0 - <= 30.0 %	polybutylene terephthalate (PBT)
65997-17-3	>= 10.0 - < 30.0 %	Glass, oxide, chemicals
26062-94-2	>= 10.0 - <= 30.0 %	polybutylene terephthalate (PBT)

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Repeated dose toxicity:

Information on: Fiberglass

This product contains glass fibers which are compounded into the polymer matrix and thus are not expected to present the same hazards as fiberglass wool.



Safety data sheet

ULTRADUR® S 4090 G4 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2007/01/04

Version: 1.0

Page: 2/5

(30035786/MDS_GEN_US/EN)

Information on: Fiberglass

Animal implantation studies have indicated that fiberglass wool is an animal carcinogen. A small study of Canadian glass wool workers reported a statistically significant increase in deaths due to lung cancer; however, animal inhalation studies and several large-scale studies of U.S. and European fiberglass wool workers have shown no statistically significant increases in lung cancer. The International Agency for Research on Cancer (IARC) has classified this material in Category 2B.

Information on: Fiberglass

These findings are based on glass wool, which has a smaller diameter than continuous glass filament or glass fiber chopped strands or rovings. Fiberglass wool is not used in this product.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Assist in breathing if necessary. Keep patient calm, remove to fresh air. Consult a physician.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

If irritation develops, seek medical attention. In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Autoignition: > 400 °C (ASTM D1929)

Suitable extinguishing media:

water, dry extinguishing media, foam

Hazards during fire-fighting:

carbon monoxide, tetrahydrofuran, acrylonitrile, Styrene, alpha-Methylstyrene, n-butyl acrylate, can be emitted at > 300 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

Further information:



Safety data sheet

ULTRADUR® S 4090 G4 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2007/01/04

Version: 1.0

Page: 3/5

(30035786/MDS_GEN_US/EN)

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

Protection against fire and explosion:

Take precautionary measures against static discharges.

Storage

General advice:

Keep container tightly closed. Avoid deposition of dust.

Storage stability:

Protect against moisture.

8. Exposure controls and personal protection

Components with workplace control parameters

Glass, oxide, chemicals

ACGIH

TWA value 5 mg/m³ Inhalable fraction ; TWA value 1
fibers/cm³ Fiber ; TWA value 1 fibers/cm³ Fiber ; TWA
value 0.2 fibers/cm³ Fiber ;

Advice on system design:

Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Safety glasses

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid inhalation of vapour.

9. Physical and chemical properties

Form:	granules
Odour:	odourless
Colour:	various, depending on the colourant
melting range:	220 - 225 °C (DIN EN ISO 3146)
Density:	1.30 - 1.50 g/cm ³ (EN ISO 1183-1)
Bulk density:	600 - 900 kg/m ³
Solubility in water:	insoluble



Safety data sheet

ULTRADUR® S 4090 G4 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2007/01/04
Version: 1.0

Page: 4/5
(30035786/MDS_GEN_US/EN)

10. Stability and reactivity

Conditions to avoid:

Temperature: > 300 degrees Celsius

Decomposition products:

Hazardous decomposition products: carbon monoxide, tetrahydrofuran, acrylonitrile, Styrene, alpha-Methylstyrene, n-butyl acrylate

11. Toxicological information

Chronic toxicity

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation:

The product will not be readily bioavailable due to its consistency and insolubility in water..

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling.

May be disposed of or combusted with domestic refuse according to local regulations.

Container disposal:

Packs must be completely emptied. Completely emptied packagings can be given for recycling.

14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG



Safety data sheet

ULTRADUR® S 4090 G4 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Revision date : 2007/01/04

Page: 5/5

Version: 1.0

(30035786/MDS_GEN_US/EN)

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

State regulations

State RTK

CAS Number

65997-17-3

Chemical name

Glass, oxide, chemicals

State RTK

MA, NJ, PA

16. Other information

Local contact information

Tech Desk

1-800-527-8324

ULTRADUR® S 4090 G4 UNCOLORED POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Corporation or BASF AG

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

