

Safety data sheet

ULTRASON® E 2010 G6 UNCOLORED POLYARYLETHERSULFONE

Revision date : 2006/04/28

Version: 1.0

Page: 1/5
(30047240/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information
CHEMTRIC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Synonyms: Poly ether sulfone

2. Composition/information on ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25608-63-3	= 60.0 - <= 80.0 %	Polyethersulfone (PES)
65997-17-3	= 20.0 - <= 40.0 %	Glass, oxide, chemicals

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns.

Irritation:

Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Repeated dose toxicity:

No known chronic effects.

Information on: Fiberglass

This product contains glass fibers which are compounded into the polymer matrix and thus are not expected to present the same hazards as fiberglass wool.



Safety data sheet

ULTRASON® E 2010 G6 UNCOLORED POLYARYLETHERSULFONE

Revision date : 2006/04/28

Page: 2/5

Version: 1.0

(30047240/MDS_GEN_US/EN)

Information on: Fiberglass

Animal implantation studies have indicated that fiberglass wool is an animal carcinogen. A small study of Canadian glass wool workers reported a statistically significant increase in deaths due to lung cancer; however, animal inhalation studies and several large-scale studies of U.S. and European fiberglass wool workers have shown no statistically significant increases in lung cancer. The International Agency for Research on Cancer (IARC) has classified this material in Category 2B.

Information on: Fiberglass

These findings are based on glass wool, which has a smaller diameter than continuous glass filament or glass fiber chopped strands or rovings. Fiberglass wool is not used in this product.

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Burns caused by molten material require hospital treatment.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Flash point:

Autoignition: 580 - 600 °C

No data available.

(DIN 54836)

Suitable extinguishing media:

water, foam, dry extinguishing media

Hazards during fire-fighting:

carbon monoxide, can be emitted at > 400 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').



Safety data sheet

ULTRASON® E 2010 G6 UNCOLORED POLYARYLETHERSULFONE

Revision date : 2006/04/28

Page: 4/5

Version: 1.0

(30047240/MDS_GEN_US/EN)

Solubility in water: insoluble

10. Stability and reactivity

Conditions to avoid:

Temperature: > 400 degrees Celsius

Decomposition products:

Hazardous decomposition products: carbon monoxide, Gaseous products of degradation can be given off if the product is greatly overheated.

Thermal decomposition:

> 400 °C

11. Toxicological information

Chronic toxicity

Other information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation: Experience shows this product to be inert and non-degradable.

Bioaccumulation:

The product will not be readily bioavailable due to its consistency and insolubility in water..

13. Disposal considerations

Waste disposal of substance:

Check for possible recycling.

May be disposed of or combusted with domestic refuse according to local regulations.

Container disposal:

Packs must be completely emptied.

14. Transport information

Land transport
USDOT



Safety data sheet

ULTRASON® E 2010 G6 UNCOLORED POLYARYLETHERSULFONE

Revision date : 2006/04/28

Version: 1.0

Page: 5/5

(30047240/MDS_GEN_US/EN)

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

State regulations

State RTK

CAS Number
65997-17-3

Chemical name
Glass, oxide, chemicals

State RTK
MA, NJ, PA

16. Other information

Local contact information

Tech Desk

1-800-527-8324

ULTRASON® E 2010 G6 UNCOLORED POLYARYLETHERSULFONE is a registered trademark of BASF Corporation or BASF AG

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

