

# Safety Data Sheet

## ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE

Revision date : 2013/04/16

Page: 1/6

Version: 1.0

(30047243/SDS\_GEN\_US/EN)

### 1. Product and Company Identification

Company

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

Synonyms:

Poly ether sulfone

### 2. Hazards Identification

Emergency overview

## CAUTION:

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
INGESTION MAY CAUSE GASTRIC DISTURBANCES.

Use with local exhaust ventilation.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Wear NIOSH-certified chemical goggles.

Wear protective clothing.

Eye wash fountains and safety showers must be easily accessible.

State of matter: solid

Colour: light yellow to brownish

Odour: odourless

Potential health effects**Primary routes of exposure:**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

**Acute toxicity:**

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

**Irritation / corrosion:**

Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

**Sensitization:**

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

**Chronic toxicity:**

# Safety Data Sheet

## ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE

Revision date : 2013/04/16

Page: 2/6

Version: 1.0

(30047243/SDS\_GEN\_US/EN)

**Carcinogenicity:** Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

**Genotoxicity:** Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

**Signs and symptoms of overexposure:**

No significant reaction of the human body to the product known.

No hazard is expected under intended use and appropriate handling.

**Potential environmental effects**

**Aquatic toxicity:**

The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

**Degradation / environmental fate:**

The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

### 3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
25608-63-3	>= 80.0 - <= 100.0 %	Polyethersulfone (PESU)

### 4. First-Aid Measures

**General advice:**

Remove contaminated clothing.

**If inhaled:**

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Consult a physician.

**If on skin:**

Burns caused by molten material require hospital treatment.

**If in eyes:**

If irritation develops, seek medical attention. In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

**If swallowed:**

Ingestion is not likely in the available physical form. If ingested, seek medical attention. Consult a physician.

### 5. Fire-Fighting Measures

Flash point:		not applicable
Autoignition:	580 - 600 °C	(DIN 54836)
Lower explosion limit:		The substance / product decomposes therefore not determined.
:		not applicable, the product does not form flammable aerosols)
Flammability:	not self-igniting	
Self-ignition temperature:		not self-igniting

**Suitable extinguishing media:**

water spray, carbon dioxide, dry powder, foam



# Safety Data Sheet

## ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE

Revision date : 2013/04/16

Page: 3/6

Version: 1.0

(30047243/SDS\_GEN\_US/EN)

### **Hazards during fire-fighting:**

carbon monoxide, Sulphur dioxide, can be emitted at > 400 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

### **Protective equipment for fire-fighting:**

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

---

## 6. Accidental release measures

### **Environmental precautions:**

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

### **Cleanup:**

Reclaim for processing if possible.

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of.

### **Further information:**

High risk of slipping due to leakage/spillage of product.

---

## 7. Handling and Storage

### **Handling**

#### **Protection against fire and explosion:**

No explosion proofing necessary.

### **Storage**

#### **General advice:**

Keep container tightly closed. Avoid deposition of dust. Protect against moisture.

#### **Storage stability:**

Protect against moisture.

---

## 8. Exposure Controls and Personal Protection

### **Advice on system design:**

Provide local exhaust ventilation to control dusts/vapours.

### **Personal protective equipment**

#### **Respiratory protection:**

Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination.

#### **Hand protection:**

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

#### **Eye protection:**

Safety glasses with side-shields.

#### **General safety and hygiene measures:**

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Wash soiled clothing immediately.



# Safety Data Sheet

## ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE

Revision date : 2013/04/16

Page: 4/6

Version: 1.0

(30047243/SDS\_GEN\_US/EN)

### 9. Physical and Chemical Properties

Form:	pellets	
Odour:	odourless	
Colour:	light yellow to brownish	
pH value:		not applicable
glass transition temperature:	225 °C	
Boiling range:		The substance / product decomposes therefore not determined.
Vapour pressure:		not applicable
Density:	1.30 - 1.40 g/cm3	( 20 °C) (EN ISO 1183-1)
Relative density:		No data available.
Bulk density:	700 - 800 kg/m3	
Vapour density:		not applicable
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Viscosity, kinematic:		not applicable, the product is a solid
Solubility in water:		insoluble

### 10. Stability and Reactivity

#### Conditions to avoid:

Temperature: > 400 degrees Celsius

#### Substances to avoid:

No substances known that should be avoided.

#### Decomposition products:

Hazardous decomposition products: carbon monoxide, Sulphur dioxide, Gaseous products of degradation can be given off if the product is greatly overheated.

#### Thermal decomposition:

> 400 °C

Thermal decomposition above the indicated temperature is possible.

#### Corrosion to metals:

No corrosive effect on metal.

### 11. Toxicological information

#### Aspiration Hazard:

No aspiration hazard expected.

#### Other Information:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### 12. Ecological Information

#### Degradability / Persistence

#### Biological / Abiological Degradation



# Safety Data Sheet

## ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE

Revision date : 2013/04/16

Page: 5/6

Version: 1.0

(30047243/SDS\_GEN\_US/EN)

Evaluation:

Experience shows this product to be inert and non-degradable.

---

### 13. Disposal considerations

**Waste disposal of substance:**

Incinerate in a licensed facility. Do not discharge substance/product into sewer system.

**Container disposal:**

Dispose of in accordance with national, state and local regulations.

---

### 14. Transport Information

**Land transport**

USDOT

Not classified as a dangerous good under transport regulations

**Sea transport**

IMDG

Not classified as a dangerous good under transport regulations

**Air transport**

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

### 15. Regulatory Information

**Federal Regulations**

**Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):**

Not hazardous;

**State regulations**

**CA Prop. 65:**

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

---

### 16. Other Information

Recommended use: Polymer for industrial processing only

Suitable for use in industrial sector: Polymers industry;



# Safety Data Sheet

## ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE

Revision date : 2013/04/16

Page: 6/6

Version: 1.0

(30047243/SDS\_GEN\_US/EN)

### HMIS III rating

Health: 1      Flammability: 1      Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

### SDS Prepared by:

BASF NA Product Regulations

msds@basf.com

SDS Prepared on: 2013/04/16

ULTRASON® E 3010 NATURAL POLYARYLETHERSULFONE is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

