

Safety data sheet

ULTRAFORM® N2320 003 UNCOLORED Q600

POLYACETAL

Revision date : 2008/02/27

Version: 2.1

Page: 1/5

(30192032/MDS_GEN_US/EN)

1. Substance/preparation and company identification

Company

BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

Synonyms:

POLYOXYMETHYLENE COPOLYMER

2. Composition/information on ingredients

CAS Number

24969-26-4

Content (W/W)

> 90.0 %

Chemical name

polyoxymethylene copolymerizate (POM)

3. Hazard identification

Emergency overview

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
MAY CAUSE RESPIRATORY SENSITIZATION (OSHA 29 CFR 1910.1048)
UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO
PREVENT THERMAL BURNS.
HEATING DURING PROCESSING OF PRODUCT MAY RESULT IN RELEASE OF THE
DECOMPOSITION PRODUCT FORMALDEHYDE.
MAY EMIT FORMALDEHYDE WHICH CAN CAUSE CANCER.

Potential health effectsPrimary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Acute toxicity:

Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Irritation:

Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes.

Repeated dose toxicity:

No adverse effects have been reported in the processing and use of the product. No known chronic effects.



Safety data sheet

ULTRAFORM® N2320 003 UNCOLORED Q600

POLYACETAL

Revision date : 2008/02/27

Version: 2.1

Page: 2/5

(30192032/MDS_GEN_US/EN)

Medical conditions aggravated by overexposure:

The use of products that contain or liberate formaldehyde is regulated under the OSHA Formaldehyde Standard (see 29 CFR 1910.1048).

Potential environmental effects

Aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

4. First-aid measures

General advice:

Burns caused by molten material require hospital treatment.

If inhaled:

If formaldehyde vapour is inhaled, remove person to fresh air and keep warm, if necessary summon physician.

If on skin:

If contacted with decomposition products wash affected areas with soap and water.

If in eyes:

In case decomposition products come into contact with the eyes, immediately flush with running water for at least 15 minutes.

If swallowed:

Ingestion is not likely in the available physical form. If ingested, seek medical attention.

5. Fire-fighting measures

Flash point: 320 - 340 °C (ASTM D1929)

Suitable extinguishing media:

water, foam, dry extinguishing media

Hazards during fire-fighting:

carbon monoxide, formaldehyde,

Formation of further decomposition and oxidation products depends upon the fire conditions.

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

6. Accidental release measures

Environmental precautions:

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

Reclaim for processing if possible. Sweep/shovel up. Place into suitable containers for reuse or disposal in a licensed facility.

Further information:



Safety data sheet

ULTRAFORM® N2320 003 UNCOLORED Q600

POLYACETAL

Revision date : 2008/02/27

Version: 2.1

Page: 3/5

(30192032/MDS_GEN_US/EN)

High risk of slipping due to leakage/spillage of product.

7. Handling and storage

Handling

General advice:

Avoid inhalation of dusts/mists/vapours. Provide appropriate exhaust ventilation at machinery.

Protection against fire and explosion:

Containers should be grounded against electrostatic charge.

Storage

General advice:

Keep container tightly closed. Avoid deposition of dust.

Storage stability:

Protect against moisture.

8. Exposure controls and personal protection

Advice on system design:

Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) particulate respirator. Wear respiratory protection if ventilation is inadequate.

Hand protection:

Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

General safety and hygiene measures:

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. Wash soiled clothing immediately.

9. Physical and chemical properties

Form:	pellets	
Odour:	odourless	
Colour:	opaque	
pH value:		No data available.
Relative density:	1.35 - 1.6	
Bulk density:	850 kg/m3	
Solubility in water:		insoluble

10. Stability and reactivity

Conditions to avoid:



Safety data sheet

ULTRAFORM® N2320 003 UNCOLORED Q600

POLYACETAL

Revision date : 2008/02/27

Version: 2.1

Page: 4/5

(30192032/MDS_GEN_US/EN)

Avoid prolonged exposure to extreme heat.

Substances to avoid:
inorganic acids, organic acids

Hazardous reactions:
Do not process with PVC or other plastics containing halogenated flame retardants.

Decomposition products:
Possible decomposition products: carbon monoxide, Formaldehyde

Thermal decomposition:
> 240 °C

Corrosion to metals:
No corrosive effect on metal.

11. Toxicological information

12. Ecological information

13. Disposal considerations

Waste disposal of substance:
Incinerate in a licensed facility.
Do not discharge substance/product into sewer system.

Container disposal:
Dispose of in accordance with national, state and local regulations.

14. Transport information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations



Safety data sheet

ULTRAFORM® N2320 003 UNCOLORED Q600

POLYACETAL

Revision date : 2008/02/27

Version: 2.1

Page: 5/5

(30192032/MDS_GEN_US/EN)

15. Regulatory information

Federal Regulations

Registration status:

TSCA, US

released / listed

SARA hazard categories (EPCRA 311/312): Not hazardous

16. Other information

HMIS III rating

Health: 1

Flammability: 1

Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

Tech Desk

1-800-527-8324

ULTRAFORM® N2320 003 UNCOLORED Q600 POLYACETAL is a registered trademark of BASF Corporation or BASF SE

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET

