

# LITEPOL® L15 GFHB/1020 NERO

## LITEPOL®

Polypropylene, 10% glass fiber and 20% hollow glass bubbles reinforced, chemically coupled, low density.

### Product information

Resin Identification	PP-(GF+GB)30	ISO 1043
Part Marking Code	>PP-(GF+GB)30<	ISO 11469

### Rheological properties

Melt mass-flow rate	8 g/10min	ISO 1133
Melt mass-flow rate, Temperature	230 °C	
Melt mass-flow rate, Load	2.16 kg	
Moulding shrinkage range, parallel	0.4 - 0.6 %	ISO 294-4, 2577
Moulding shrinkage range, normal	0.5 - 0.7 %	ISO 294-4, 2577

### Typical mechanical properties

Tensile modulus	3400 MPa	ISO 527-1/-2
Tensile stress at yield, 50mm/min	45 MPa	ISO 527-1/-2
Tensile strain at yield, 50mm/min	3 %	ISO 527-1/-2
Tensile strain at break, 50mm/min	3.5 %	ISO 527-1/-2
Flexural modulus	3200 MPa	ISO 178
Charpy impact strength, 23 °C	30 kJ/m <sup>2</sup>	ISO 179/1eU
Charpy notched impact strength, 23 °C	5.5 kJ/m <sup>2</sup>	ISO 179/1eA
Izod notched impact strength, 23 °C	6.5 kJ/m <sup>2</sup>	ISO 180/1A
Poisson's ratio	0.37 <sup>[C]</sup>	

[C]: Calculated

### Thermal properties

Temperature of deflection under load, 1.8 MPa	130 °C	ISO 75-1/-2
Vicat softening temperature, 50 °C/h 50N	105 °C	ISO 306
Coefficient of linear thermal expansion (CLTE), parallel	47.1 E-6/K	ISO 11359-1/-2
Coefficient of linear thermal expansion (CLTE), normal	104 E-6/K	ISO 11359-1/-2

### Flammability

Burning Behav. at 1.5mm nom. thickn.	HB class	IEC 60695-11-10
Thickness tested	1.5 mm	IEC 60695-11-10
Burning Behav. at thickness h	HB class	IEC 60695-11-10
Thickness tested	3.2 mm	IEC 60695-11-10
FMVSS Class	B	ISO 3795 (FMVSS 302)
Burning rate, Thickness 2 mm	76.2 mm/min	ISO 3795 (FMVSS 302)

### Physical/Other properties

Density	830 kg/m <sup>3</sup>	ISO 1183
---------	-----------------------	----------

# LITEPOL® L15 GFHB/1020 NERO

## LITEPOL®

### Injection

Back pressure

2 MPa

### Characteristics

Processing

Injection Moulding

### Additional information

Processing Notes

### Storage

This product should be stored in a covered facility and kept away from moisture and heat.

### Automotive

OEM

Stellantis

STANDARD

MS.50042 / PP-H.GB20-GF10.2700F.6I

ADDITIONAL INFORMATION

Dashboard structural parts