

SAFETY DATA SHEET(SDS)

Issued: February 25, 2014

Revised: June 14, 2016

FileNo. 4003

1. Chemical Product & Company Identification

CHEMICALPRODUCT NAME: LAPEROS® A430 Colored
NAME OF COMPANY: Polyplastics Co.,Ltd.
ADDRESS: 2-18-1 Konan, Minato-ku, Tokyo,108-8280 Japan
SECTION IN CHARGE: Quality Assurance Dept.
TELEPHONE NUMBER: 03-6711-8605
FACSIMILE NUMBER 03-6711-8616

2. Hazards identification

[GHS CLASSIFICATION]

Physical and Chemical Hazards : ·Flammable solids : Classification not possible
·Self-reactive substances and mixtures : Not applicable
·Pyrophoric solids : Not classified
·Self-heating substances and mixtures : Not classified
·Substances and mixtures, which in contact with water, emit flammable gases : Not classified
·Oxidizing solids : Not classified
·Corrosive to metal : Not classified

Health Hazards : ·Carcinogeneses : No hazard
·Specific target organ/systemic toxicity (Repeated exposure) : No hazard

Environmental Hazards : No hazard

[SYMBOL] : None
[SIGNAL WORD] : None
[HAZARD STATEMENT] : None
[PRECAUTIONARY STATEMENTS]

Prevention : ·Wash hands thoroughly after handling.
·Wear protective gloves.


Response : -

Storage : Avoid direct sunlight and store in a well-ventilated place.

Disposal : Dispose of contents/container in accordance with local & national regulations.

3. Composition/information on ingredients

SUBSTANCE/PREPARATION : Mixture
COMMON CHEMICAL NAME : p-hydroxybenzoic acid·6-hydroxy-2-naphthoic acid copolymer
SYNONYMS : Aromatic Liquid Crystal Polymer(LCP)
INGREDIENTS AND COMPOSITION : LCP ≥ 73%, Polytetrafluoro ethylene(PTFE) ≤ 25%,
Others ≤ 2%

CHEMICAL FORMURA : 

SERIAL No. IN OFFICIAL GAZETTE : 7-2251(base resin)
(Law Concerning Examination and Regulation of Manufacture, etc., of Chemical Substances)

CAS No. : 70679-92-4(base resin)
INGREDIENTS CONTRIBUTING TO THE HAZARD : Cadmium, lead, hexavalent chromium and mercury are not used in this grade.

4. First-aid measures

INGESTION : When a gas generated from the molten polymer has been inhaled, move to area of fresh air without delay and wait until the victim is

	recovered. When a fume generated by heat or burning has been inhaled, move to area of fresh air. If sick feeling continues, ask a physician for advice.
SKIN CONTACT	: Cool the contacted skin with clean water without delay, if a contact with the polymer in a molten form. Do not force to remove the solid resin on the skin. If any burns are observed on the skin, ask a physician for advice.
EYE CONTACT	: Cool and rinse the eye with clean water for at least 15 minutes when the eyes had contact with molten polymer. In case of wearing contact lenses, remove the lenses as soon as possible, and ask a physician for advice. When the eye had contact with the polymer in an ordinary solid form, rinse the eye with clean water without delay. If the discomfort persists, ask a physician for advice.
SWALLOW	: Help to vomit as much as possible. If sick feeling continues, ask a physician for advice.
<hr/>	
5. Fire-fighting measures	
EXTINGUISHING MEDIA	: Water, foam fire-extinguishing agent, powder fire-extinguishing agent, and carbon dioxide gas.
SPECIFIC METHODS	: Extinguish the fire with water. A method of extinguishing an ordinary fire may be applied. Do not apply water directly to processing machines.
SPECIFIC HAZARDS	: Incomplete combustion leads to generation of toxic gases such as carbon monoxide or phenol, in addition to carbonic acid gas and water. The filler, PTFE, generates hazardous fume and gases when it is heated up to a high temperature.
SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS	: In case the fire gained force, use a gas mask or other protective equipment. When PTFE is exposed to fierce fires, use a totally enclosed gas mask or other protective appliances such as air aspirator or protective clothes.
<hr/>	
6. Accidental release measures	
PERSONAL PRECAUTIONS	: When pellets were spilled on the road or floor, wipe them off with a broom or cleaner not to cause slipping.
ENVIRONMENTAL PRECAUTION	: Handle the spillage in accordance with provisions given in the "Resin pellet spillage preventive manual", in order to prevent intakes by marine animals and birds.
<hr/>	
7. Handling and storage	
HANDLING	: LCP polymer in a pellet form will neither ignite nor explode at room temperatures.
HANDLING 2	: This pellets spilled on the floor are likely to cause slipping. Remove such spillage at any times.
HANDLING 3	: For molding work, effective means for local exhaust are required to discharge gases generated by melt processing.
HANDLING 4	: Avoid inhaling of gases generated in molding work. Do not directly touch resin of high temperature.
HANDLING 5	: Avoid retaining hot resin in the processing machines for many hours.
STORAGE	: Keep the substance away from any fire or heat sources for the sake of safe storage.
STORAGE 2	: Handle in accordance with municipal rules and regulations.
STORAGE 3	: No smoking at a storage.
STORAGE 4	: Smoking a cigarette to which a PTFE product is adhered may lead to inhaling a decomposed gas. Therefore, prohibit smoking at working places. Wash your face and hands after handling products. Keep it in mind that the products will not adhere to the cigarettes.

	Close the cover of products after handling products.
RECOMMENDED PACKAGING MATERIALS	: No information.
<hr/>	
8. Exposure controls/ personal protection	
CONTROL CONCENTRATION	: None at present
PERMISSIBLE CONCENTRATION	: OSHA PEL/1985 Max. permissible concentration of inactive powder 15mg/m ³ – ditto – (Aspiration) 5 mg/m ³ ACGIH TLV/1992 1993 Exposure limit of the powder TWA 10 mg/m ³
ENGINEERING MEASURE	: ·When handling dust: Use totally enclosed containers resisting dust explosion. ·When heat melted in molding: Effective local ventilation must be provided.
PERSONAL PROTECTIVE EQUIPMENT	
RESPIRATORY PROTECTION	: Wear a dust-proof mask.
HAND PROTECTION	: Wear heat-resisting gloves against burns, when handling molten polymer.
EYE PROTECTION	: Wear protective glasses or goggles.
SKIN & BODY PROTECTION	: Wear long sleeve clothes against burns, when handling molten polymer.
<hr/>	
9. Physical and chemical properties	
APPEARANCE etc.	: Pellet
BOILING POINT	: Not applicable
VAPOUR PRESSURE	: Not applicable
VOLATILITY	: Not applicable
INITIAL BOILING POINT	: Not applicable
SUBLIMATION	: None
MELTING POINT	: 275~285°C
DENSITY	: 1.56
SOLUBILITY	: Insoluble in water
FLASH POINT	: No finding
IGNITION POINT	: 540°C or higher
EXPLOSION PROPERTY	: Not applicable
INFLAMMABILITY	: It is flammable, but shows self-fire extinguishing characteristics when kept away from flame.
REACTIVITY WITH WATER	: None
OXIDIZABILITY	: None
SELF-REACTIVITY	: None
DUST EXPLOSIVENESS	: No finding
<hr/>	
10. Stability and reactivity	
STABILITY AND REACTIVITY	: Stable for normal storage or handling.
CONDITIONS TO AVOID	: The filler PTFE could react with powdered metals such as aluminium or magnesium and with oxidizing agents such as fluorine and fluorides like fluorine trichloride and cause fire or explosion.
HAZARDOUS DECOMPOSITION PRODUCTS	: The filler PTFE starts decomposing very slowly at a temperature higher than 260°C. The decomposition rate increases at a temperature higher than 400°C. 〈Temperature level and constituents likely to start formation〉 Tetrafluoroethylene 430°C or higher Hexafluoropropylene 440°C or higher Perfluoroisobutylene 475°C or higher Carbonyl fluoride 500°C or higher
<hr/>	
11. Toxicological information	

SKIN CORROSION/IRRITATION	: No finding.
SERIOUS EYE DAMAGE/IRRITATION	: Gas generated in drying or melting is irritating eyes and skins.
RESPIRATORY OR SKIN SENSITISATION	: No finding
SUBACUTE TOXICITY	: No finding.
CHRONIC TOXICITY	: No finding.
CARCINOGENECITY	: No finding.
MUTAGENECITY(Micro organisms, chromosomal aberration)	: No finding.
REPRODUCTIVE TOXICITY	: No finding.
TERATOGENICITY	: No finding.
OTHERS(Including generation of hazardous gases by reaction with water, for example)	: No finding in this report means that there will be no hazard in general, but no proving data available at the time of reporting.
OTHER CAUTIONS	: With regard to dust, the maximum permissible concentration and limits are fixed by OSHA and ACGIH.
OTHER CAUTIONS 2	: Hazardousness of PTFE, the filler is as follows:

(Animal test)

- Not stimulative to the skin. Inhaling PTFE dusts of high concentration leads to stimulation to the lung. No notable toxic effect observed by repeated dosing. Dosing for a long period causes changes in White blood counts. No genic toxicity noted in animal and culture studies of bacterial cells.

(Influences to human health)

- Inhaling fume generated during combustion is likely to cause polymer fume fever with symptoms like transient influenza accompanying fever, chills and coughing lasting for 24 hours. No absorption from the skin. No report on sensitization available.

(Adverse effects of hydrogen fluoride)

- Inhaling hydrogen fluoride of low concentration causes firstly hard breathing following by coughing and severe irritation of eyes, nose and throat, then successive chills for 1 or 2 days, and finally difficulty in breathing, cyanosis and pulmonary edema. Exposure to hydrogen fluoride of high concentration, for short time or long time, will give damages to liver and kidneys.

(Adverse effects of carbonyl fluoride)

Skin : Unpleasantness or herpes

Eyes : Corneal or conjunctival ulceration

Respiratory organs : Irritation

Lungs : Transient irritation such as coughing unpleasantness, hard breathing or short breathing

Carcinogenicity : No description with Japan Industrial Hygiene Society (1933 edition), OSHA (1993 edition), NTP (1989 edition) IARC (1987 edition): Group 3

12. Ecological information

BIODEGRADABILITY	: No finding.
BIOACCUMULATION	: No finding.
FISH TOXICITY	: No finding.
HAZARDS TO OZONE LAYER	: None

13. Disposal considerations

WASTE FROM RESIDUES	: This is designated as waste plastics among industrial wastes by the Wastes Disposal Law. Disposal waste pellets through licensed wastes handlers or local autonomous bodies if they are handling wastes disposal.
---------------------	---

WASTE FROM RESIDUES 2	:	When disposed by incineration, use the well controlled incinerators in accordance with the Wastes Disposal Law, Air Pollution Control Law and Water Pollution Prevention Law.
<hr/>		
14. Transport information		
UN CLASSIFICATION NUMBER	:	Not restricted for ICAO/IATA.
OTHER CAUTIONS	:	Handle with care so as not to give damages to containers or not to be subjected to wetting.
OTHER CAUTIONS 2	:	Secure the containers firmly so as not to cause collapsing.
<hr/>		
15. Regulatory information		
WASTE DISPOSAL LAW	:	Waste plastics among industrial wastes.
<hr/>		
16. Other information		
HANDLING OF THE DETAILS GIVEN ABOVE	:	This SDS is the English version translated from the Japanese SDS which is prepared for domestic use. Details given above are based on references, information and data available at this moment, but no warranty can be made on exactness of these details. They are also prepared on the assumption that the product will be handled in a normal way. For special handling, adequate safety and environmental measures should be taken in respect to its applications. Our products are not specifically intended for implants for medical and dental applications, and therefore they are not recommended for such applications. "No finding" in this report means that there will be no hazard in general, but no proving data is available at the time of reporting.
WHERE TO CALL FOR FURTHER INFORMATION	:	Polyplastics Co. , Ltd. Quality Assurance Dept. Tel. No 03-6711-8605

*LAPEROS® is a registered trademark of Polyplastics Co., Ltd. in Japan and other countries.

