

# SAFETY DATA SHEET (SDS)

Issued: March 2, 2016

Revised: May 17, 2019

FileNo. 2001

## 1. Chemical Product & Company Identification

CHEMICAL PRODUCT NAME: DURANEX® 300FP EF201R  
RECOMMENDED USE: Industrial products  
RESTRICTED USE: Contact sales division about medical equipment products.  
NAME OF COMPANY: Polyplastics Co., Ltd.  
ADDRESS: 2-18-1 Konan, Minato-ku, Tokyo, 108-8280 Japan  
SECTION IN CHARGE: Quality Assurance Dept.  
TELEPHONE NUMBER: +81-3-6711-8605  
FACSIMILE NUMBER: +81-3-6711-8616  
EMERGENCY NUMBER: +81-3-6711-8605

## 2. Hazards identification

### [ GHS CLASSIFICATION ]

Physical and Chemical Hazards : ·Flammable solids : Classification not possible  
·Self-reactive substances and mixtures : Not applicable  
·Pyrophoric solids : Not classified  
·Self-heating substances and mixtures : Not classified  
·Substances and mixtures, which in contact with water, emit flammable gases : Not classified  
·Oxidizing solids : Not classified  
·Corrosive to metal : Not classified

Health Hazards : ·Carcinogenicity : No hazard  
·Specific target organ/systemic toxicity (Repeated exposure) : No hazard

Environmental Hazards : No hazard

[ SYMBOL ] : None

[ SIGNAL WORD ] : None

[ HAZARD STATEMENT ] : None

### [ PRECAUTIONARY STATEMENTS ]

Prevention : ·Wash hands thoroughly after handling.  
·Wear protective gloves.


Response : -

Storage : Avoid direct sunlight and store in a well-ventilated place.

Disposal : Dispose of contents/container in accordance with local & national regulations.

## 3. Composition/information on ingredients

SUBSTANCE/MIXTURES : Substance  
COMMON CHEMICAL NAME : Polybutyleneterephthalate  
SYNONYMS : Polybutyleneterephthalate(PBT)  
INGREDIENTS AND COMPOSITION : PBT 100%  
CHEMICAL FORMULA :



CAS No. : 26062-94-2, 30965-26-5 (base resin)

INGREDIENTS CONTRIBUTING TO THE HAZARD : Cadmium, lead, hexavalent chromium and mercury are not used in this grade.

The specific chemical identities and percentages of composition are withheld as trade secrets.

## 4. First-aid measures



INHALATION	:	When a gas generated from the molten polymer has been inhaled, move to area of fresh air without delay and wait until the victim is recovered. If sick feeling continues, ask a physician for advice.
SKIN CONTACT	:	Cool the contacted skin with clean water without delay, if a contact with the polymer in a molten form. Do not force to remove the solid resin on the skin. If any burns are observed on the skin, ask a physician for advice.
EYE CONTACT	:	Cool and rinse the eye with clean water for at least 15 minutes when the eyes had contact with molten polymer. In case of wearing contact lenses, remove the lenses as soon as possible, and ask a physician for advice. When the eye had contact with the polymer in an ordinary solid form, rinse the eye with clean water without delay. If the discomfort persists, ask a physician for advice.
INGESTION	:	Help to vomit as much as possible. If sick feeling continues, ask a physician for advice.
MOST IMPORTANT SYMPTOMS	:	No data available
IMMEDIATE MEDICAL ATTENTION	:	None needed

---

#### 5. Fire-fighting measures

EXTINGUISHING MEDIA	:	Water, foam fire-extinguishing agent, powder fire-extinguishing agent, and carbon dioxide gas.
SPECIFIC METHODS	:	Extinguish the fire with water. A method of extinguishing an ordinary fire may be applied. Do not apply water directly to processing machines.
SPECIFIC HAZARDS	:	Incomplete combustion leads to generation of toxic gases such as carbon monoxide or tetrahydrofuran, in addition to carbonic acid gas and water.
SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS	:	In case the fire gained force, use a gas mask or other protective equipment.

---

#### 6. Accidental release measures

PERSONAL PRECAUTIONS	:	When pellets were spilled on the road or floor, wipe them off with a broom or cleaner not to cause slipping.
METHODS FOR CLEANING UP	:	Handle the spillage in accordance with provisions given in the "Resin pellet spillage preventive manual", in order to prevent intakes by marine animals and birds.

---

#### 7. Handling and storage

HANDLING	:	Polybutyleneterephthalate resin in a pellet form will neither ignite nor explode at room temperatures. Keep it away from the igniting sources, as it quickly gains force once it is ignited.
HANDLING 2	:	This pellets spilled on the floor are likely to cause slipping. Remove such spillage at any times.
HANDLING 3	:	For molding work, effective means for local exhaust are required to discharge gases generated by melt processing.
HANDLING 4	:	Avoid inhaling of gases generated in molding work. Do not directly touch resin of high temperature.
HANDLING 5	:	Avoid retaining hot resin in the processing machines for many hours.
STORAGE	:	Keep the substance away from any fire or heat sources for the sake of safe storage.
STORAGE 2	:	This polymer is an inflammable synthetic resin and should be handled in accordance with municipal rules and regulations (concerning fire-fighting equipment, indoor storage, for instance).
RECOMMENDED PACKAGING MATERIALS	:	No information.

---

#### 8. Exposure controls/ personal protection



CONTROL CONCENTRATION	:	None at present
PERMISSIBLE CONCENTRATION	:	OSHA PEL Max. permissible concentration of inactive powder 15mg/m <sup>3</sup> - ditto - (Aspiration ) 5 mg/m <sup>3</sup> ACGIH TLV Exposure limit of the powder TWA 10 mg/m <sup>3</sup>
ENGINEERING MEASURE	:	·When handling dust: Use totally enclosed containers resisting dust explosion. ·When heat melted in molding: Effective local ventilation must be provided.
PERSONAL PROTECTIVE EQUIPMENT		
RESPIRATORY PROTECTION	:	Wear a dust-proof mask.
HAND PROTECTION	:	Wear heat-resisting gloves against burns, when handling molten polymer.
EYE PROTECTION	:	Wear protective glasses or goggles.
SKIN & BODY PROTECTION	:	Wear long sleeve clothes against burns, when handling molten polymer.

9. Physical and chemical properties

APPEARANCE etc.	:	Pellet
ODOR	:	No data available
ODOR THRESHOLD	:	No data available
PH	:	No data available
MELTING POINT	:	223°C
BOILING POINT	:	Not applicable
FLASH POINT	:	300°C or higher
EVAPORATION RATE	:	No data available
FLAMMABILITY	:	Flammable
EXPLOSIVE LIMITS	:	Upper explosion limit : Not applicable. Lower explosion limit : 35g/m <sup>3</sup>
VAPOR PRESSURE	:	Not applicable
VAPOR DENSITY	:	No data available
RELATIVE DENSITY	:	1.31
SOLUBILITY	:	Insoluble in water
PARTITION COEFFICIENT (n-octanol/water)	:	No data available
AUTO-IGNITION TEMPERATURE	:	300°C or higher
DECOMPOSITION TEMPERATURE	:	No data available
VISCOSITY	:	No data available

10. Stability and reactivity

STABILITY AND REACTIVITY	:	Stable for normal storage or handling.
POSSIBILITY OF HAZARDOUS REACTIONS	:	No data available
CONDITIONS TO AVOID	:	Keep the substance away from any fire or heat sources for the sake of safe storage.
INCOMPATIBLE MATERIALS	:	No data available
HAZARDOUS DECOMPOSITION PRODUCTS	:	Incomplete combustion leads to generation of toxic gases such as carbon monoxide or tetrahydrofuran, in addition to carbonic acid gas and water

11. Toxicological information

SKIN CORROSION/IRRITATION	:	No finding.
SERIOUS EYE DAMAGE/IRRITATION	:	Gas generated in drying or melting is irritating eyes and skins.
RESPIRATORY OR SKIN SENSITISATION	:	No finding
ACUTE TOXICITY(INCLUDING LD50)	:	No finding.
SUBACUTE TOXICITY	:	No finding.



CHRONIC TOXICITY	:	No finding.
CARCINOGENICITY	:	No finding.
MUTAGENICITY(Micro organisms, chromosomal aberration)	:	No finding.
REPRODUCTIVE TOXICITY	:	No finding.
TERATOGENICITY	:	No finding.
OTHERS(Including generation of hazardous gases by reaction with water, for example)	:	No finding in this report means that there will be no hazard in general, but no proving data available at the time of reporting.
OTHER CAUTIONS	:	With regard to dust, the maximum permissible concentration and limits are fixed by OSHA and ACGIH.
<hr/>		
12. Ecological information		
BIODEGRADABILITY	:	No finding.
BIOACCUMULATION	:	No finding.
FISH TOXICITY	:	No finding.
HAZARDS TO OZONE LAYER	:	None
<hr/>		
13. Disposal considerations		
WASTE FROM RESIDUES	:	This is designated as waste plastics among industrial wastes by the Wastes Disposal Law. Disposal waste pellets through licensed wastes handlers or local autonomous bodies if they are handling wastes disposal.
WASTE FROM RESIDUES 2	:	When disposed by incineration, use the well controlled incinerators in accordance with the Wastes Disposal Law, Air Pollution Control Law and Water Pollution Prevention Law.
<hr/>		
14. Transport information		
UN CLASSIFICATION NUMBER	:	Not restricted for ICAO/IATA.
OTHER CAUTIONS	:	Handle with care so as not to give damages to containers or not to be subjected to wetting.
OTHER CAUTIONS 2	:	Secure the containers firmly so as not to cause collapsing.
<hr/>		
15. Regulatory information		
TSCA INVENTORY	:	All ingredients are listed on the TSCA inventory
CA PROPOSITION 65	:	None are listed.
<hr/>		
16. Other information		
HANDLING OF THE DETAILS GIVEN ABOVE	:	Details given above are based on references, information and data available at this moment, but no warranty can be made on exactness of these details. They are also prepared on the assumption that the product will be handled in a normal way. For special handling, adequate safety and environmental measures should be taken in respect to its applications. Our products are not specifically intended for implants for medical and dental applications, and therefore they are not recommended for such applications. "No finding" in this report means that there will be no hazard in general, but no proving data is available at the time of reporting.
WHERE TO CALL FOR FURTHER INFORMATION	:	Polyplastics Co.,Ltd. Quality Assurance Dept. Tel. No +81-3-6711-8605
DATE OF PREPARATION	:	May 17, 2019

\*DURANEX® is a registered trademark of Polyplastics Co., Ltd. in Japan and other countries.