



Component - Plastics

File Number: E56070

CHI MEI CORPORATION

59-1 SAN CHIA

JEN TE

TAINAN, 717 Taiwan

POLYLAC: PA-757G J08

Acrylonitrile Butadiene Styrene (ABS), pellets



Flammability	Value	Test Method
Flame Rating		
1.5 mm, BK	HB	UL 94
3.0 mm, BK	HB	UL 94
3.0 mm, BK	HB40	IEC 60695-11-10, -20
1.5 mm, BK	HB75	IEC 60695-11-10, -20
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746A
1.5 mm	PLC 5	
3.0 mm	PLC 5	
High Amp Arc Ignition (HAI)		UL 746A
1.5 mm	PLC 1	
3.0 mm	PLC 1	
Comparative Tracking Index (CTI)	PLC 3	UL 746A
High Voltage Arc Tracking Rate (HVTR)	PLC 3	UL 746A
Arc Resistance	PLC 7	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746B
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746B
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Str		UL 746B
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	