

ExxonMobil™ LDPE

LD 653

Product Description

LD 653 is an easy flowing LDPE grade with medium stiffness and good toughness.

General 1

Availability	• Africa & Middle East	• Europe	
Additive	• Antiblock: No	• Heat Stabilizer: No	• Slip: No
Revision Date	• 6/2006		

Resin Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Melt Index	22	22	ExxonMobil Method
Density	0.924 g/cm ³	0.924 g/cm ³	ExxonMobil Method
Peak Melting Temperature	228 °F	109 °C	ExxonMobil Method

Thermal	Typical Value (English)	Typical Value (SI)	Test Based On
Vicat Softening Temperature	196 °F	91.0 °C	ISO 306

Molded Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Tensile Modulus	29000 psi	200 MPa	ISO 527-1, -2/1
Tensile Stress (Break)	1310 psi	9.00 MPa	ISO 527-1, -2/50
Tensile Strain (Break)	120 %	120 %	ISO 527-1, -2/50
Shore Hardness (Shore A)	44	44	ISO 868

Additional Properties

- Applications
- tough medium sized moldings
- caps
- bottle closures
- Toys
- houseware

Processing Statement

The molded properties have been measured on 4 mm (157.5 mil) thick injection molded specimen, based on ISO 1872-2.

Foodlaw & Medical Use Statement

LD 653 can - in principle - be used in food contact applications in various EU Member States and in the USA (FDA). Migration or use limitations may apply. Please contact your ExxonMobil Chemical representative for more detailed information and/or actual compliance certification documents for the specific grade of interest.

ExxonMobil Polyethylene is not intended for use in medical applications.

Notes

Product may not be available in one or more countries in the identified Availability regions. Contact your Sales Representative for complete Country Availability.

Value reported is an estimate based on ExxonMobil's correlation from melt flow rate data measured at other standard conditions, based on ASTM D 1238.

Typical properties: these are not to be construed as specifications.

© 2008 Exxon Mobil Corporation. To the extent the user is entitled to disclose and distribute this document, the user may forward, distribute, and/or photocopy this copyrighted document only if unaltered and complete, including all of its headers, footers, disclaimers, and other information. You may not copy this document to a Web site. ExxonMobil does not guarantee the typical (or other) values. Analysis may be performed on representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, suitability, accuracy, reliability, or completeness of this information or the products, materials, or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage, or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. There is no endorsement of any product or process, and we expressly disclaim any contrary implication. The terms, "we", "our", "ExxonMobil Chemical", or "ExxonMobil" are used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates they directly or indirectly own or control. ExxonMobil, the ExxonMobil Chemical Emblem, the "Interlocking X" Device, Enable, Exceed, Exact, Exxco, Escorene, Escor, lotek, NTX, Polybilt, Paxon, Opterna are trademarks or service marks of Exxon Mobil Corporation.