

SAFETY DATA SHEET



1. Identification

Covestro LLC
1 Covestro Circle
Pittsburgh, PA 15205
USA

Product Name: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH
Material Number: 58093975
Chemical Family: Thermoplastic Polymer Sheet
Use: For the production of plastic sheet products

2. Hazards Identification

GHS Classification

This product is not hazardous in the form in which it is shipped by the manufacturer.

GHS Label Elements

Signal word: Warning

Hazard statements: If fine particles are generated during further processing, handling or by other means, product may form combustible dust concentrations in air.

3. Composition/Information on Ingredients

Hazardous Components

The following potentially hazardous ingredient(s) are used to formulate this product. As supplied, the ingredient(s) are bound in the polymer matrix. Because they are bound in the matrix, they are not expected to create any unusual hazards when handled and processed according to good manufacturing and industrial hygiene practices and the guidelines provided in this SDS.

The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade secret.

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH

Material Number: 58093975

4. First Aid Measures

Most Important Symptom(s)/Effect(s)

Acute: Contact with heated material can cause thermal burns., Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.

Eye Contact

In case of contact, flush eyes with plenty of lukewarm water.

Skin Contact

Cool melted product on skin with plenty of water. Do not remove solidified product. Get medical attention if thermal burn occurs.

Inhalation

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.

Ingestion

Get medical attention.

5. Firefighting Measures

Suitable Extinguishing Media: Water fog, Dry chemical, Carbon dioxide (CO2), Foam

Unsuitable Extinguishing Media: High Pressure Water Streams

Fire Fighting Procedure

Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

Hazardous Decomposition Products

By Fire and Thermal Decomposition: ; Phenol Carbon oxides, Hazardous decomposition products due to incomplete combustion

Unusual Fire/Explosion Hazards

Toxic and irritating gases/fumes may be given off during burning or thermal decomposition. Avoid generating dust: fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard.

6. Accidental Release Measures

Spill and Leak Procedures

If molten, allow material to cool and place into an appropriate marked container for disposal. Sweep up and shovel into suitable containers for disposal. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture as they are released into the atmosphere in sufficient concentrations. Avoid dispersal of dust in the air (e.g., cleaning dust from surfaces with compressed air).

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH /
SMOOTH

Material Number: 58093975

7. Handling and Storage

Handling/Storage Precautions

Handle in accordance with good industrial hygiene and safety practices. Wash thoroughly after handling. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dust does not accumulate on surfaces. Solid particulate can generate electrical charging during operations such as unloading from containers and pneumatic transfer. Provide adequate precautions, such as electrical grounding and bonding, where conductive equipment is involved.

Storage Period:

None.

Storage Temperature

Maximum: 49 °C (120.2 °F)

Storage Conditions

Containers should be tightly closed to prevent contamination with foreign materials and moisture.

Substances to Avoid

None known.

8. Exposure Controls/Personal Protection

Exposure Limits

Country specific exposure limits have not been established or are not applicable

Any component which is listed in section 3 and is not listed in this section does not have a known ACGIH TLV, OSHA PEL or supplier recommended occupational exposure limit.

Industrial Hygiene/Ventilation Measures

General dilution and local exhaust as necessary to control airborne vapors, mists, dusts and thermal decomposition products below appropriate airborne concentration standards/guidelines, especially during cutting, grinding and high heat operations.

Respiratory Protection

Although no exposure limit has been established for this product, the OSHA PEL for Particulates Not Otherwise Regulated (PNOR) of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction is recommended. In addition, the ACGIH recommends 3 mg/m³ - respirable particles and 10 mg/m³ - inhalable particles for Particles (insoluble or poorly soluble) Not Otherwise Specified (PNOS).

Hand Protection

Wear heat resistant gloves when handling molten material.

Eye Protection

Safety glasses with side-shields

Skin Protection

No special skin protection requirements during normal handling and use.

Additional Protective Measures

Employees should wash their hands and face before eating, drinking, or using tobacco products. Educate and train employees in the safe use and handling of this product. Purgings should be collected as small flat thin shapes or thin strands to allow for rapid cooling.

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH /
SMOOTH

Material Number: 58093975

9. Physical and Chemical Properties

State of Matter:	solid
Appearance:	Sheet
Color:	Clear
Odor:	Odorless
Odor Threshold:	No Data Available
pH:	No Data Available
Melting Point:	220 - 230 °C (428 - 446 °F)
Boiling Point:	No Data Available
Flash Point:	No Data Available
Evaporation Rate:	No Data Available
Flammability:	No Data Available
Lower explosion limit:	No Data Available
Upper Explosion Limit:	No Data Available
Vapor Pressure:	No Data Available
Vapor Density:	No Data Available
Density:	ca. 1.2 g/cm ³ @ 20 °C (68 °F) (DIN 53479)
Relative Vapor Density:	No Data Available
Specific Gravity:	No Data Available
Solubility in Water:	insoluble
Partition Coefficient: n-octanol/water:	No Data Available
Auto-ignition Temperature:	> 450 °C (842 °F)
Decomposition Temperature:	>= 380 °C (716 °F)
Softening point:	150 - 160 °C (302 - 320 °F)
Dynamic Viscosity:	not applicable
Kinematic Viscosity:	No Data Available

10. Stability and Reactivity

Hazardous Reactions

Hazardous polymerisation does not occur.

Stability

Stable

Materials to Avoid

None known.

Conditions to Avoid

Generation of dust clouds.

Hazardous Decomposition Products

By Fire and Thermal Decomposition: Phenol; Carbon oxides, Hazardous decomposition products due to incomplete combustion

11. Toxicological Information

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH

Material Number: 58093975

Likely Routes of Exposure: Inhalation
Skin Contact
Eye Contact

Health Effects and Symptoms

Acute: Contact with heated material can cause thermal burns., Gases and fumes evolved during the thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract.

Toxicity Data for: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH

No data available for this product.

Carcinogenicity:

Isopropanol **IARC** - Overall evaluation: 3 Not classifiable as to carcinogenicity to humans.

12. Ecological Information

Ecological Data for: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH

No data available for this product.

13. Disposal Considerations

Waste Disposal Method

Waste disposal should be in accordance with existing federal, state and local environmental control laws.

14. Transportation Information

Land transport (DOT)

Non-Regulated

Sea transport (IMDG)

Non-Regulated

Air transport (ICAO/IATA)

Non-Regulated

15. Regulatory Information

United States Federal Regulations

US. Toxic Substances Control Act: Excluded: Article.

No substances are subject to TSCA 12(b) export notification requirements.

US. EPA CERCLA Hazardous Substances (40 CFR 302) Components:

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH

Material Number: 58093975

None

SARA Section 311/312 Hazard Categories:

Non-hazardous under Section 311/312

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III

Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) Components:

None

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III

Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required Components:

None

US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

Under RCRA, it is the responsibility of the person who generates a solid waste, as defined in 40 CFR 261.2, to determine if that waste is a hazardous waste.

State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

The concentrations reported below in units of parts per million (ppm) or parts per billion (ppb) are maximum values.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

<u>Weight percent</u>	<u>Components</u>	<u>CAS-No.</u>
>=1%	Bisphenol A Polycarbonate	25971-63-5
>=1%	Bisphenol A Polycarbonate	CAS# is a trade secret
0.1 - 1%	Isopropanol	67-63-0

New Jersey Environmental Hazardous Substances List and/or New Jersey RTK Special Hazardous Substances Lists:

<u>Weight percent</u>	<u>Components</u>	<u>CAS-No.</u>
0.1 - 1%	Isopropanol	67-63-0
0.1 - 1%	Methanol	67-56-1
0.1 - 1%	1-Butanol	71-36-3
0.1 - 1%	Propylene Glycol Methyl Ether	107-98-2

Massachusetts Right to Know Extraordinarily Hazardous Substance List:

<u>Weight percent</u>	<u>Components</u>	<u>CAS-No.</u>
<=3 ppm	Methylene Chloride	75-09-2

California Prop. 65:

Warning! This product contains chemical(s) known to the State of California to be Carcinogenic. Developmental toxin. Female reproductive toxin.

<u>Weight percent</u>	<u>Components</u>	<u>CAS-No.</u>
0.1 - 1%	Methanol	67-56-1
<=3 ppm	Methylene Chloride	75-09-2
Trace element	Bisphenol A	80-05-7

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH / SMOOTH

Material Number: 58093975

Covestro polycarbonate sheet products as sold contain BPA at concentrations below which would require the need for a warning under the Act.

CFATS (Chemical Facility Anti-Terrorism Standards) Chemicals

To the best of our knowledge, this product does not contain Appendix A Chemicals of Interest (COI), at or above the Screening Threshold Quantity (STQ), as defined by the Department of Homeland Security Chemical Facility Anti-terrorism Standard (CFATS, 6 CFR Part 27).

Based on information provided by our suppliers, this product is considered "DRC Conflict Free" as defined by the SEC Conflict Minerals Final Rule (Release No. 34-67716; File No. S7-40-10; Date: 2012-08-22).

16. Other Information

The method of hazard communication for Covestro LLC is comprised of product labels and safety data sheets. Safety data sheets for all of our products and general product declarations are available for download at www.productsafetyfirst.covestro.com.

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of Covestro LLC. The information in this SDS relates only to the specific material designated herein. Covestro LLC assumes no legal responsibility for use of or reliance upon the information in this SDS.

|| Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Material Name: HYGARD® MS1250 CLEAR-A00, SMOOTH /
SMOOTH

Material Number: 58093975

