



组件 - 塑料

UL 档案号: E41613

COVESTRO DEUTSCHLAND AG [PC RESINS]

Chempark
Gebäude B207
Leverkusen, 51368 Germany



Bayblend: M850 XF+

Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), pellets, impact modified

+ - Material designations may be followed by a six digit numerical code denoting color.

可燃性	值	测试方法
UL 阻燃等级		
0.9 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
0.9 mm, ALL	HB75	IEC 60695-11-10, -20
热性能	值	测试方法
RTI Elec		UL 746B
0.9 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746B
0.9 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI		UL 746B
0.9 mm	60.0 °C	
3.0 mm	60.0 °C	



UL 94 小规模测试数据与建筑材料、家具和有关内容不相关。ANSI/UL 94 小规模测试数据仅用于确定成品设备和装置的组中所用塑料材料的易燃性，其中组合的可接受性由 UL 确定。

