



Trinseo LLC
900 1st Ave
King of Prussia, PA 19406-1308 United States



Plexiglas, Altuglas: V-044 (f2), V-045 (f2), V-647-10 (f2), V-811 (f2), V-825 (f2)

Polymethyl Methacrylate (PMMA), pellets

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

NOTE - Grade designations may be followed by letters and/or numbers indicating color.

可燃性	值	测试方法
UL 阻燃等级		
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
电气性能	值	测试方法
热丝引燃 (HWI)		UL 746A
1.5 mm	PLC 4	
3.0 mm	PLC 4	
高电弧燃烧指数(HAI)		UL 746A
1.5 mm	PLC 0	
3.0 mm	PLC 0	
热性能	值	测试方法
RTI Elec		UL 746B
1.5 mm	90.0 °C	
3.0 mm	90.0 °C	
RTI Imp		UL 746B
1.5 mm	90.0 °C	
3.0 mm	90.0 °C	
RTI		UL 746B
1.5 mm	90.0 °C	
3.0 mm	90.0 °C	
物理性能	值	测试方法
室外适用性	f2	UL 746C

