

Description

MDPE LF 38 YSCF is a yellow stripe compound designed to be used in combination with the black PE 80 grade MDPE 3802 B for gas networks.

An accredited laboratory has proved fusion compatibility of the base polymer of MDPE LF 38 YSCF with MDPE 3802 B.

Characteristics

| Property | Method | Unit | Typical value (*) |
|-----------------------------|----------------------|----------|-------------------|
| Melt Flow Rate (190°C/5 kg) | ISO 1133/T | g/10 min | 0.9 |
| Thermal stability 200°C | EN 728 / ISO 11357-6 | min | > 20 |
| Water content (**) | EN 12118 | ppm | ≤ 300 |

(*) Data not intended for specification purposes

(**) Measured at the stage of compound manufacturing

Handling and storage

Please refer to the safety data sheet (SDS) for handling and storage information. It is advisable to convert the product within one year after delivery provided storage conditions are used as given in the SDS of our product. SDS may be obtained from the website: www.totalrefiningchemicals.com

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Petrochemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.

