

Data sheet: Lumicene

Lumicene®

利明稀

Asia

亚洲

		Melt Index		
Product name	Density	熔体流动速率	Melting Temp °C	Applications / Markets
产品	密度 g/cm ³	(2.16 Kg-190°C) g/10'	熔体温度 °C	主要用途
Lumicene M 2310 EP 利明稀 M 2310 EP		Film, Blown 薄膜、吹膜		
Lumicene M 2704 EP S01 利明稀 M 2704 EP S01		Film, Blown 薄膜、吹膜		
Lumicene M 2710 EP 利明稀 M 2710 EP		Film, Blown 薄膜、吹膜		
Lumicene M 3410 EP 利明稀 M 3410 EP		Film, Blown 薄膜、吹膜		



Product name 产品	Density 密度 g/cm ³	Melt Index 熔体流动速率 (2.16 Kg-190°C) g/10'	Melting Temp °C 熔体温度 °C	Applications / Markets 主要用途
Lumicene M 3427 利明稀 M 3427	Film, Fibers, Cast, Artificial Grass, CF/BCF- Monofilament 薄膜、纤维、流延薄膜、人造草坪妙、CF/BCF 单 丝			
Lumicene M 3509 利明稀 M 3509	Blow Molding, Consumer Packaging 中空成型、消费品包装			
Lumicene M 3581 UV 利明稀 M 3581 UV	Rotomolding 旋转模塑			
Lumicene M 4040 利明稀 M 4040	Film, Pipes & cables, Cast, Pressure Pipes & Fittings 薄膜、管道与管线、流延薄膜、压力管道与管材			
Lumicene M 4041 UV 利明稀 M 4041 UV	Rotomolding 旋转模塑			



Product name 产品	Density 密度 g/cm ³	Melt Index 熔体流动速率 (2.16 Kg-190°C) g/10'	Melting Temp °C 熔体温度 °C	Applications / Markets 主要用途
Lumicene M 4707 EP 利明稀 M 4707 EP	Film, Blown 薄膜、吹膜			
Lumicene M 5220 利明稀 M 5220	Injection Molding, Blow Molding, Caps & Closures, Dairy 注塑、中空成型、瓶盖与封口产品、奶类制品包装			
Lumicene M 5220 M 利明稀 M 5220 M	Injection Molding, Caps & Closures 注塑、瓶盖与封口产品			
Lumicene M 5510 EP 利明稀 M 5510 EP	Film, Blown 薄膜、吹膜			
Lumicene M2010 利明稀 M2010	Film, Blown 薄膜、吹膜			
Lumicene M6091 利明稀 M6091	Film, Coating, Cast 薄膜、涂层、流延薄膜			

