

Data sheet: XSene

XSene

XSene

Asia

亚洲

Product name 产品	Density 密度 g/cm ³	Melt Index 熔体流动速率 (5 Kg-190°C) g/10'	Melt Index 熔体流动速率 (21.6 Kg-190°C) g/10'	Color 颜色	Applications / Markets 主要用途
XSene 4206 B					Pipes & cables, Coating 管道与管线、涂层
XSene 55060					Blow Molding, Industrial Packaging 吹膜、工业包装
XSene BM593					Pipes & cables, Blow Molding, Non Pressure Pipes, Consumer Packaging 管道与管线、吹膜、非压力管道、消费品包装
XSene HD 55110					Film, Blown 薄膜、吹膜



Product name 产品	Density 密度 g/cm ³	Melt Index 熔体流动速率 (5 Kg-190°C) g/10'	Melt Index 熔体流动速率 (21.6 Kg-190°C) g/10'	Color 颜色	Applications / Markets 主要用途
XSene XLS 12 B	Pipes & cables, Pressure Pipes & Fittings 管道与管线、压力管道与管材				
XSene XRC 20 B	Pipes & cables, Pressure Pipes & Fittings 管道与管线、压力管道与管材				
XSene XS 10 B	Pipes & cables, Pressure Pipes & Fittings 管道与管线、压力管道与管材				
XSene XS 10 H	Pipes & cables, Pressure Pipes & Fittings, Stripe Compounds 管道与管线、压力管道与管材、嵌条专用料				
XSene XS 10 Orange YCF	Pipes & cables, Pressure Pipes & Fittings 管道与管线、压力管道与管材				

