

Technical Data Sheet

Eastman AQ™ 65S Polymer

Applications

- Carpet & area rugs
- Film modification
- General industrial coatings
- Wood coatings

Product Description

Eastman AQ™ 65S polymer is a polyester supplied as pellets. Aqueous dispersions of Eastman AQ™ 65S polymer provide excellent water resistance, alcohol resistance, fast drying rates, low odor, and a consistently low coefficient of friction.

Typical Properties

Property ^a	Typical Value, Units ^b
General	
Chemical Type	Polyester
Form	Amber-coloured pellets
Solids	100%
Glass Transition Temperature (T _g)	63 °C
Odor	Low odor

^aUnless noted otherwise, all tests are run at 23°C (73°F) and 50% relative humidity.

^bUnits are in SI or US customary units.

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

2/28/2018 11:35:39 AM