

Technical Data Sheet

Eastman™ Cellulose Acetate Propionate (CAP-482-20), Food Contact

Applications

- Commerical printing inks
- Flexographic printing inks
- Food can coatings internal
- Graphic arts
- Gravure printing inks
- Inkjet printing inks
- Labels - food packaging - food contact
- Pack & carton coatings
- Packaging inks food contact
- Screen printing inks
- Tape - food packaging - food contact

Product Description

Eastman Cellulose Acetate Propionate (CAP-482-20, Food Contact) is similar to Eastman CAP-482-0.5, Food Contact in solubility and compatibility but Eastman CAP-482-20, Food Contact has a higher viscosity. CAP 482-20, Food Contact is useful as a film former in inks and overprint varnishes. It may be used alone or in combination with Eastman CAP-482-0.5, Food Contact. When CAP-482-20, Food Contact is dissolved in appropriate solvents a clear, colorless solution is produced.

Eastman CAP-482-20, Food Contact is based on cellulose, one of the most abundant natural renewable resources, from trees harvested from sustainably managed forests. The calculated approximate bio-content value of 43% for Eastman CAP-482-20, Food Contact was determined by using six bio-based carbon atoms per anhydroglucose unit divided by the total number of carbons per anhydroglucose unit. Although the value reported is not specifically measured for bio-carbon, it can be estimated based on typical partition data.

This product is manufactured, stored, handled and transported by Eastman under conditions adhering to current Good Manufacturing Practices for food contact applications. This product meets requirements for use in certain food contact applications under regulations of the U.S. Food and Drug Administration (21 CFR), European Commission (Regulation 10/2011) and the Swiss Ordinance on Materials & Articles in Contact with Food (SR 817.023.21). Contact your Eastman representative or authorized Eastman distributor for specific regulatory compliance documentation.

For applications that do not require food contact compliance, please refer to Eastman CAP-482-20.

Typical Properties

Property	Typical Value, Units
General	
Viscosity ^a	
s	20
Poise	76.5
Acetyl Content	1.3 wt %
Propionyl Content	48 wt %
Hydroxyl Content	1.7 wt %
Moisture Content	3.0 max %
T _g ^b	147 °C
Melting range	188-210 °C

Specific Gravity @ 20°C/25°C	1.22
Acidity as Acetic Acid	0.01 wt %
Ash Content	0.017 wt %
Refractive Index	1.475 n(25°C/D)
Tukon Hardness	23 Knoop
Wt/Vol @ 20°C	1.22 kg/L (10.2 lb/gal)
Form	Powder

^aViscosity determined by ASTM Method D 1343. Results converted to poises (ASTM Method D 1343) using the solution density for Formula A as stated in ASTM Method D 817 (20% Cellulose ester, 72% acetone, 8% ethyl alcohol).

^bGlass Transition Temperature

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

10/21/2019 6:21:17 AM