

Technical Data Sheet

Eastman Tetrashield™ IC3000

Applications

- General industrial coatings

Key Attributes

- Enhanced long term weathering performance
- Extended durability due to increased hydrolytic stability
- Improved chemical & stain resistance
- Improved mar/scratch resistance and toughness due to higher Tg
- Reduced VOC and enhanced productivity due to higher solids at low viscosity

Product Description

Eastman Tetrashield™ IC3000 is a durable polyester resin system that improves the performance of both clearcoats and pigmented topcoats. Tetrashield™ protective resin systems are designed to enhance coating performance, reduce environmental impact, and optimize the coating process for agricultural and construction equipment manufacturers and their suppliers.

Typical Properties

Property	Typical Value, Units
General	
Solvents	n-butyl acetate
Volatiles	24-26 %
Color	
APHA	< 63
Viscosity	12-32 poise
Hydroxyl Number	120-150 mg KOH/g
Acid Number	< 10 mg KOH/g

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

2/28/2018 11:35:39 AM