

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name: Piccotac(TM) 1098 Hydrocarbon Resin

Product No.: EAN 800935. 1098, P7600501, P760050A, P76005SP, P7600502, P76005TT, P76005RC, P7600500, E7600501, P76005ST

Synonyms, Trade Names: 76005-00

Relevant identified uses of the substance or mixture and uses advised against Identified uses: Adhesive, Coatings, Plastic additive Uses advised against: None known.

Details of the supplier of the safety data sheet

Manufacturer / Supplier Eastman Chemical Company 200 South Wilcox Drive Kingsport, TN 37660-5280 US +14232292000

Visit our website at www.EASTMAN.com or email emnmsds@eastman.com

Emergency telephone number:

For emergency health, safety, and environmental information, call 1-423-229-4511 or 1-423-229-2000.

For emergency transportation information, in the United States: call CHEMTREC at 800-424-9300 or call 423-229-2000.

SECTION 2: Hazards identification

Hazard Classification:

OSHA Specified Hazards:

Combustible dust

If converted to small particles during further processing, handling or by other means may form combustible dust concentrations in air.

Warning label items including precautionary statement:

Signal Words:	WARNING!	
Hazard Statement(s):	If converted to small particles during further processing, handling or by	
	other means may form combustible dust concentrations in air.	

Precautionary Statement:

Disposal:

Sal: P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.



Hazard(s) not otherwise classified (HNOC):

None known.

SECTION 3: Composition/information on ingredients

Substances / Mixtures

General information:

Concentration	Additional identification	Notes
>99%	CAS-No.: proprietary	
<0.1%	CAS-No.: proprietary	
	>99%	>99% CAS-No.: proprietary

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

This substance has w orkplace exposure limit(s).

SECTION 4: First aid measures

Description of first aid measures

Inhalation:	Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. Get medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin contact:	Wash with soap and water. Get medical attention if symptoms occur. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn. Get medical attention.
Ingestion:	Seek medical advice.
Most important symptoms and effects, both acute and delayed:	Burns should be treated as thermal burns. The material will come off as healing occurs; therefore, immediate removal from the skin is not necessary.
Indication of any immediate med	lical attention and special treatment needed
Hazards:	Contact with molten substance/product may cause severe burns to skin and eyes.
Treatment:	Treat symptomatically.
SECTION 5: Firefighting mea	

General Fire Hazards:	Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures.
Extinguishing media Suitable extinguishing media:	Water spray. Dry chemical. Carbon Dioxide.



Unsuitable extinguishing media:	None known.
Special hazards arising from the substance or mixture:	Powdered material may form explosive dust-air mixtures.
Advice for firefighters Special fire fighting procedures:	Minimize dust generation and accumulation.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
SECTION 6: Accidental relea	ase measures
Personal precautions, protective equipment and emergency procedures:	Wear appropriate personal protective equipment.
Environmental Precautions:	Not regarded as dangerous for the environment.
Methods and material for	
containment and cleaning up:	Sweep up and place in a clearly labeled container for chemical waste.

SECTION 7: Handling and storage:

Precautions for safe handling:	Avoid contact with molten material. Minimize dust generation and accumulation.
Conditions for safe storage, including any incompatibilities:	Keep container closed.
Specific end use(s):	Adhesive Coatings Plastic additive

SECTION 8: Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Country specific exposure limits have not been established or are not applicable unless listed below.

Exposure controls



Appropriate engineering controls:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measure	es, such as personal protective equipment
General information:	Eye bath. Washing facilities.
Eye/face protection:	It is a good industrial hygiene practice to minimize eye contact. Wear a face shield when working with molten material.
Skin protection Hand Protection:	It is a good industrial hygiene practice to minimize skin contact. When material is heated, wear gloves to protect against thermal burns.
Other:	No data available.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air- purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices.
Environmental Controls:	No data available.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	
Physical state:	solid/liquid
Form:	Pellet liquid (molten)
Color:	Pale yellow
Odor:	Slight
Odor Threshold:	Not determined.
pH:	No data available.
Softening Point:	98 - 102 °C
Boiling Point:	No data available.
Flash Point:	232 °C (Cleveland Open Cup)
Evaporation Rate:	Not determined.
Flammability (solid, gas):	No data available.
Flammability Limit - Upper (%)–:	No data available.
Flammability Limit - Lower (%)–:	No data available.
Vapor pressure:	Not determined.

©COPYRIGHT 2015 BY EASTMAN CHEMICAL COMPANY



Vapor density (air=1):	No data available.
Specific Gravity:	0.92 (25 °C)
Solubility(ies)	
Solubility in Water:	Negligible
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Autoignition Temperature:	No data available.
Decomposition Temperature:	Thermal stability not tested. Low stability hazard expected at normal operating temperatures.
Dynamic viscosity:	No data available.
Kinematic viscosity:	Not determined.
Explosive properties:	No data available.
Oxidizing properties:	No data available.

SECTION 10: Stability and reactivity

Reactivity:	None known.
Chemical Stability:	Stable
Possibility of Hazardous Reactions:	None known.
Conditions to Avoid:	None at ambient temperatures.
Incompatible Materials:	Strong oxidizing agents.
Hazardous Decomposition Products:	Carbon Monoxide. Carbon Dioxide.

SECTION 11: Toxicological information

Information on likely routes of exposure Inhalation: None known.	
Ingestion:	None known.
Skin contact:	Molten material will produce thermal burns.
Eye contact:	Molten material will produce thermal burns.

Information on toxicological effects

Oral Product: Specified substance(s):	No data available.
hydrocarbon resin	Oral LD-50: (Rat): > 2,000 mg/kg
Dermal Product:	No data available.



Product:	No data available.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritatio Product:	n No data available.
Respiratory or Skin Sensitization Product:	No data available.
Carcinogenicity Product:	No data available.
Toxicity to reproduction Product:	No data available.
Developmental toxicity Product:	No data available.
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Specific Target Organ Toxicity - Product:	Single Exposure No data available.
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

SECTION 12: Ecological information



Ecotoxicity:

Acute hazards to the aquatic environment:		
Fish Product:	No data available.	
Specified substance(s): hydrocarbon resin	LC-50 (Common Carp, 48 h): > 10 g/l	
Aquatic Invertebrates Product:	No data available.	
Chronic hazards to the aquatic environment:		
Fish Product:	No data available.	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
Specified substance(s): hydrocarbon resin	12.7 % (28 d) Not readily degradable.	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative Potential Bioconcentration Factor (BC Product:	F) No data available.	
Partition Coefficient n-octanol / water (log Kow)Product:No data available.		
Mobility in Soil:	No data available.	
Other Adverse Effects:	No data available.	

SECTION 13: Disposal considerations

Waste treatment methods

General information: No data available.



Disposal methods:

Dispose of waste and residues in accordance with local authority requirements. Incinerate.

SECTION 14: Transport information

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

DOT

Class 9, Packing Group III when liquid is offered for transport or is transported, in bulk packaging, at or above 100°C and below its flash point; otherwise, not regulated.

Possible Shipping Description(s):

UN 3257 Elevated temperature liquid, n.o.s. (molten resin) 9 III

IMDG - International Maritime Dangerous Goods Code

Class 9, Packing Group III when liquid is offered for transport or is transported at or above 100°C and below its flash point; otherwise, not regulated.

Possible Shipping Description(s):

UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (molten resin) 9 III

ΙΑΤΑ

Class Solid forms of this product are not regulated. Forbidden on aircraft if transported molten in bulk at temperatures equal to or exceeding 100 C (212 F).

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture.:

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations. WHMIS (Canada) Status: noncontrolled

SARA 311-312 Hazard Classification(s): fire hazard

US EPCRA (SARA Title III) Section 313 - Toxic Chemical List NONE

OSHA: hazardous



TSCA (US Toxic Substances Control Act): This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act): This product is listed on the DSL. Any impurities present in this product are exempt from listing.

AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): This product is listed on AICS or otherwise complies with NICNAS.

ECL (Korean Toxic Substances Control Act): This product is listed on the Korean inventory or otherwise complies with the Korean Toxic Substances Control Act.

Inventory of Existing Chemical Substances in China: All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

SECTION 16: Other information

HMIS® Hazard Ratings: Health - 1, Flammability - 1, Chemical Reactivity - 0

HMIS® rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.

Revision Information:	New SDS
Key literature references and sources for data:	No data available.
Training information:	No data available.
Issue Date: SDS No.:	05/18/2015
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.