

# Technical Data Sheet

## Skydrol® 500B-4 Fire Resistant Hydraulic Fluid

### Applications

- Aviation hydraulic fluid

### Product Description

The Skydrol 500 series of fluids has the longest service history among phosphate ester products. The first version, Skydrol 500, was introduced in 1952. Steady improvements to the formulation led in 1977 to the current version, Skydrol™ 500B-4 which contains the same breakthrough anti erosion additive and acid scavenger found in Skydrol™ LD-4 . Skydrol 500B-4 is the most worker friendly of the aviation phosphate esters. This has given the product enormous popularity for use in work shops and indoor test stands..

### Typical Properties

Property	Test Method	Typical Value, Units
<b>General</b>		
Acid Number (mg KOH/g)		0.10 Maximum
Appearance		Clear, oily liquid
Autoignition Temperature	ASTM D 2155	460 °C (860 °F ) Minimum
Color		Purple, essentially equivalent to intensity and hue standard
Elemental Content		
Calcium		10 ppm, Maximum
Chlorine		50 ppm, Maximum
Potassium		30 ppm, Maximum
Sodium		10 ppm, Maximum
Sulfur		1185-1460 ppm
Fire Point		
COC		191 °C (375 °F ) Minimum
Flash Point		
COC		177 °C (350 °F ) Minimum
Moisture		0.20 % Maximum
Particle Contamination <sup>a</sup>		
15-25 micron size		5,700 Maximum
25-50 micron size		1,012 Maximum
50-100 micron size		180 Maximum
5-15 micron size		32,000 Maximum
Over 100 micron size		32 Maximum
Pour Point		-62 °C (-80 °F ) Maximum
Specific Gravity		
@ 25°C/25°C		1.050-1.062
Viscosity		
@ 38°C (100°F)		11.40-12.40 cSt
@ -54°C (-65°F)		2900 cSt Maximum
@ 99°C (210°F)		3.68-4.00 cSt

<sup>a</sup>NAS 1638 particle counts per AS4059F

## Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

---

*Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.*

8/28/2018 3:59:33 PM

© 2019 Eastman Chemical Company or its subsidiaries. All rights reserved. As used herein, ® denotes registered trademark status in the U.S. only.