

Technical Data Sheet

TamiSolve® NxG

Applications

- Architectural coatings
- Commercial printing inks
- Leather coatings
- Paints & coatings
- Polymer processing
- Polyurethanes
- Process solvents
- Resins
- Solvents/stripping agents
- Wire wrappers
- Wood coatings

Product Description

TamiSolve™ NxG is a high-boiling, dipolar aprotic solvent. TamiSolve NxG has good solvency for a wide range of compounds and has high chemical and thermal stability.

TamiSolve NxG has an established performance in specialty polymer coatings (wire enamels & coated cooking gear), micro-electronics manufacturing (photoresist stripper), coatings (PUD's), paint strippers and inks, chemical synthesis and agrochemical formulations.

In many applications it can be used to replace NMP or NEP (N (m)ethylpyrrolidone), as well as other solvents like dimethyl sulfoxide (DMSO) and Dipropylene Glycol Dimethyl Ether (DMM). As opposed to NMP and NEP, TamiSolve NxG is not classified as developmental reprotoxic.

Typical Properties

Property	Typical Value, Units
General	
Molecular Formula	C ₈ H ₁₅ NO
Molecular Weight	141.21 g/mol
Autoignition Temperature	212 °C
Boiling Point	241 °C
Density	
@ 25°C	0.96 g/cm ³
Flammability limits in air	
Lower	0.9 Vol %
Upper	8.7 Vol %
Flash Point	
Closed Cup	108 °C
Freezing Point	<-75 °C
Hansen Solubility Parameters	
Dispersion	17.8 (MPa) ^{1/2}
Hydrogen Bonding	5.9 (MPa) ^{1/2}
Polar	8.2 (MPa) ^{1/2}
Total	20.5 (MPa) ^{1/2}
Heat of Combustion	35 580 kJ/kg

pH	
10% solution in water	7.65
Refractive Index	1.4675
Specific Heat	
@ 20°C	1.98 J/g.K
Surface Tension	
1% aqueous solution	67.31 mN/m
Thermal Conductivity	
@ 25°C	121 mW/m.K
Vapor Pressure	
@ 25°C	13 Pa
Viscosity	
@ 25°C	4 mPa·s
Water solubility	Completely miscible

Packaging

- Bulk
- PE drums (200 kg net)
- IBC containers (970 kg net)

Storage

It is advised to store TamiSolve® NxG under a nitrogen blanket.
A carbon steel tank is adequate for storing TamiSolve® NxG.

Comments

Properties reported here are typical of average lots. Eastman makes no representation that the material in any particular shipment will conform exactly to the values given.

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability of fitness of any product, and nothing herein waives any of the Seller's conditions of sale.

4/30/2019 3:31:07 PM