

APEX® 32022RV-55NT CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

General Information				
General				
Material Status	 Commercial: Active 			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Features	BPA FreeE-beam SterilizableEthylene Oxide Sterilizable	Latex FreeNo Animal Derived ComponentsNon-Phthalate - Citrate Plasticizer	Non-Phthalate Plasticizer Radiation (Gamma) Resistant Radiation Sterilizable	
Agency Ratings	• EC 1907/2006 (REACH)	 OEHHA (California) Proposition 65 		
RoHS Compliance	 RoHS Compliant 			
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.20		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength			ASTM D638	
50% Strain	290	psi		
100% Strain	490	psi		
300% Strain	1150	psi		
Tensile Strength (Break)	1480	psi	ASTM D638	
Tensile Elongation (Break)	420	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A, 15 sec, Operating Stand	50			
Shore A, 15 sec, Hand Held	55			

Additional Information

EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors

Blood Pressure Bulbs

Canulae

Caps

Connectors

Drip/Sight Chambers

Ear Protection

Endotracheal Airway Cuffs

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136814)

Revision Date: 8/9/2019

<u>+135-3858-6433</u> +188-1699-6168

APEX® 32022RV-55NT CBL B8 NF

Teknor Apex Company - Flexible Polyvinyl Chloride

Processing Information		
Extrusion	Nominal Value Unit	
Melt Temperature	315 to 335 °F	

Notes

Revision Date: 8/9/2019

¹ Typical properties: these are not to be construed as specifications.