

APEX® 32022RV-85NT CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

General Information				
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Features	BPA FreeE-beam SterilizableEthylene Oxide Sterilizable	Latex FreeNo Animal Derived ComponentNon-Phthalate - Citrate Plasticizer	Non-Phthalate Plasticizer Radiation (Gamma) Resistant Radiation Sterilizable	
Agency Ratings	• EC 1907/2006 (REACH)	OEHHA (California) Proposition 65	1	
RoHS Compliance	 RoHS Compliant 			
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹			
Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.27		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
50% Strain	1020	psi	
100% Strain	1570	psi	
300% Strain	2670	psi	
Tensile Strength (Break)	2680	psi	ASTM D638
Tensile Elongation (Break)	310	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Operating Stand	79		
Shore A, 15 sec, Hand Held	85		

Additional Information

EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors

Blood Pressure Bulbs

Canulae

Caps

Connectors

Drip/Sight Chambers

Ear Protection

Endotracheal Airway Cuffs

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136784)

Revision Date: 8/9/2019

+135-3858-6433 +188-1699-6168

APEX® 32022RV-85NT CBL B8 NF

Teknor Apex Company - Flexible Polyvinyl Chloride

Processing Information		
Extrusion	Nominal Value Unit	
Melt Temperature	345 to 365 °F	

Notes

Revision Date: 8/9/2019

¹ Typical properties: these are not to be construed as specifications.